

PHILIPS

LCD monitor

Business Monitor

3000 series

27" (68.5 cm)

1920 x 1080 (Full HD)

27B2N3200A



Redefining workflow productivity

This Philips Full HD (1920x1080) monitor is equipped with an IPS panel for wide viewing angles. The 120Hz refresh rate ensures smooth performance, while the Low Blue Light-emitting panel minimises eye strain to support all-day productivity.

Superb Picture Quality

- IPS LED wide view technology for image and colour accuracy
- 16:9 Full HD display for crisp, detailed images
- 120Hz refresh rates for ultra-smooth images

Designed for the way you work


- Ultra Slim Bezel: for minimal edges and more screen
- SoftBlue Technology: for comfortable viewing
- Less eye strain with Flicker-free technology
- Eyesafe certified blue light protection and colour accuracy
- SmartErgoBase enables people-friendly ergonomic adjustments
- Built-in stereo speakers for multimedia
- D-Mode: Optimised for subtle greyscale perception

Easy to use

- VESA mount for convenience
- HDMI ensures universal digital connectivity


Highlights

IPS technology



IPS displays use advanced technology which gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays give you remarkably crisp images with vivid colours, making them ideal not only for photos, films and web browsing, but also for professional applications which demand colour accuracy and consistent brightness at all times.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD providing crisp detail, paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

120Hz fast refresh rate



The smoother the motion, the less strain on your eyes. This Philips monitor is equipped with an improved 120Hz refresh rate. Whenever you


scroll, switch between applications or navigate complex spreadsheets, you experience smoother and more precise movements. That means you can work for as long as you need with minimal visual fatigue—all while increasing the speed of your workflow.

Ultra Slim Bezel



This monitor makes your viewing experience feel more seamless and complete by reducing the amount of frame surrounding the screen. The Ultra Slim Bezel feature creates an elegant transition from the screen to the narrow monitor bezel, thereby making it more beautiful in form and function.

SoftBlue Technology with Low Blue Light Panel



SoftBlue technology offers increased visual comfort and protection against adverse health effects caused by prolonged exposure to blue light. With the low blue-light panel, the ratio of display emission light in the range of 415-455 nm to 400-500nm is reduced to less than 50%. As a result, SoftBlue technology provides optimal visual comfort, minimises eye strain and supports sustained focus. In addition, SoftBlue LED technology is tested and TÜV Rheinland Low Blue Light (Hardware Solution) certified for its effectiveness in reducing blue light emissions.

Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience screen flicker, which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

Eyesafe® CERTIFIED 2.0 (RPF 40)



The Philips display meets the eyesafe® CERTIFIED 2.0 standard to truly protect you from prolonged exposure to blue light. The always-on blue light filter not only helps reduce digital eye strain, but also guarantees colour integrity.

SmartErgoBase



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base can swivel, tilt and rotate to various angles to ensure maximum comfort. The height-adjustable stand guarantees the optimal viewing level, reducing the physical strain of a long working day, while cable management reduces cable clutter and keeps the workspace neat and professional.




Highlights

Built-in stereo speakers



A pair of high-quality stereo speakers built into a display device. They can be visible front-firing speakers, or invisible down-firing, top-firing, rear-firing speakers, etc., depending on the model and design.

D-Mode



Reveal every hidden detail in the dark-toned areas of your display. D-Mode enhances greyscale detail to make subtle tonal differences easier to see. Based on the greyscale perception model defined by the DICOM Part 14 GSDF standard, it improves the visibility of details that standard display settings may miss. The result is clearer differentiation between subtle shades and improved detail visibility in greyscale content such as technical illustrations, scans, and other high-detail imagery.

HDMI Ready



An HDMI-ready device has all the hardware required to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

Specifications

Picture/Display

Panel Size: 27 inch / 68.6 cm
Aspect ratio: 16:9
LCD panel type: IPS technology
Backlight type: W-LED system
Pixel pitch: 0.3114 (H)mm x 0.3114 (V)mm
Brightness: 350 cd/m²
Display colours: 16.7M (true 8 bits)
Colour gamut (typical): sRGB 102% , NTSC 92%
 *
Contrast ratio (typical): 1500:1
SmartContrast: 50,000,000:1
Response time (typical): 4 ms (Grey to Grey)*
Viewing angle: 178° (H)/178° (V), @ C/R > 10
Picture enhancement: SmartImage
Maximum resolution: 1920x1080@75Hz(VGA), 1920x1080@120Hz(HDMI)
Effective viewing area: 597.89(H)x 336.31(V) mm
Scanning Frequency: VGA: 30K-85KHz (H) / 48 -75 Hz (V); HDMI/DP: 30K-140KHz (H) / 48 -120 Hz (V)
sRGB
SoftBlue
Flicker-free
Pixel Density: 82 PPI
Display Screen Coating: Anti-glare, 3H, Haze 25%
EasyRead
Adaptive sync (VRR)
EyeSafe
DICOM (D-mode)

Connectivity

Signal Input: VGA x 1, HDMI 1.4 x 1, DisplayPort 1.2 x 1
Sync Input: Separate Sync, Sync on Green
Audio (In/Out): Audio-in
HDCP: HDCP 1.4 (HDMI / DisplayPort)

Convenience

Built-in Speakers: 2 W x 2
Plug & Play Compatibility: DDC/CI, Mac OS, sRGB, Windows 11/10
User convenience: SmartImage, Input, Brightness, Menu, Power On/Off

OSD Languages: Brazil Portuguese, Czech, Dutch, English, French, Finnish, German, Greek, Hungarian, Italian, Japanese, Korean, Portuguese, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian

Other convenience: Kensington lock, VESA mount (100 x 100 mm)

Control software: SmartControl, SmartManagement

Stand

Pivot: -/+90 degree
Height adjustment: 150 mm
Swivel: -/+180 degree
Tilt: -5/30 degree

Power

ECO mode: 7.8 W (typ.)
Power supply: Built-in, 100–240 VAC, 50–60 Hz
Off mode: 0.3 W (typ.)
On mode: 14.56 W (typ.) (Energy Star test method)
Standby mode: 0.3 W (typ.)
Power LED indicator: Operation - White, Standby mode - White (flashing)
Energy Label Class: C

Dimensions

Packaging in mm (W x H x D): 690 x 445 x 139 mm
Product without stand (mm): 616 x 362 x 46 mm
Product with stand (max height): 616 x 539 x 228 mm

Weight

Product with packaging (kg): 7.71 kg
Product with stand (kg): 5.24 kg
Product without stand (kg): 3.24 kg

Operating conditions

Altitude: Operating: +12,000ft (3,658m), Non-operating: +40,000ft (12,192m)
Temperature range (operation): 0°C to 40°C
Relative humidity: 20%-80%
Temperature range (storage): -20°C to 60°C

MTBF (demonstrated): 70,000 hrs (excluding backlight)

Sustainability

Environmental and energy: Energy Star, EPEAT*, RoHS
Post-consumer recycled plastic: 85%
Recyclable packaging material: 100 %
Specific Substances: PVC/BFR free housing

Compliance and standards

Regulatory Approvals: CB, CE Mark, South Africa Energy, MEPS, PSB, PSE, KCC, CEL, CCC, CECP, VCCI, UKCA, EMF, FCC, ICES-003, TÜV Rheinland Low Blue Light (Hardware Solution), eyesafe® CERTIFIED 2.0
Warranty: 5 years*

Cabinet

Finish: Texture
Foot: Black
Front bezel: Black
Rear cover: Black

What's in the box?

Cables: HDMI cable / DP cable / Power cable
Monitor with stand
User Documentation

- * The "IPS" word mark/trade mark and related technology patents belong to their respective owners.
- * Response time value equal to SmartResponse
- * sRGB area based on CIE 1931, NTSC area based on CIE 1976.
- * The EPEAT rating is valid only where Philips registers the product. Please visit <https://www.epeat.net/> for the registration status in your country.
- * The cable(s) supplied with the product may vary in type, quantity and specifications in line with country- or region-specific requirements.
- * The 5-year warranty is a voluntary manufacturer's limited warranty. It applies only in the countries listed on this page: <https://www.philips.co.uk/c-e/so/monitors/tco-certified-edge>. For consumers, it is provided in addition to, and without affecting, their legal rights under applicable national laws. For non-consumer (business/professional) end users, only the manufacturer's limited warranty terms apply.
- * The products and accessories listed in this leaflet may differ by country and region.
- * The monitor may look different from the images shown.

