

Alphacool Eiswolf 2 AIO 360mm RTX 3080/3090 Gaming/Eagle with Backplate

Alphacool article number: 14416

The Alphacool Eiswolf 2 is the first full cover GPU AIO waterblock from Alphacool. It is based on the Alphacool GPX Eisblock Aurora GPX water block, a pump unit and a 360mm NexXoS ST30 full copper radiator. The latter is equipped with the Alphacool Aurora Rise Digital RGB fans.

Alphacool Eiswolf 2 AIO 360mm RTX 3080/3090 Gaming/Eagle mit Backplate



- Full copper radiator
- Virtually silent DC-LT 2 pump
- Nickel-plated copper cooler
- Digital RGB illuminated cooler
- Digital RGB 120 mm fans

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Compatibility

- Gigabyte GeForce RTX 3080 Eagle OC 10G, 10GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Gaming OC 10G, 10GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Turbo 10G, 10GB GDDR6X, 2x HDMI, 2x DP
- Gigabyte GeForce RTX 3080 Vision OC 10G, 10GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Ti Eagle 12G, 12GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Ti Eagle OC 12G, 12GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Ti Vision OC 12G, 12GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3080 Ti Gaming OC
- Gigabyte GeForce RTX 3090 Eagle OC 24G, 24GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3090 Gaming OC 24G, 24GB GDDR6X, 2x HDMI, 3x DP
- Gigabyte GeForce RTX 3090 Turbo 24G, 24GB GDDR6X, 2x HDMI, 2x DP
- Gigabyte GeForce RTX 3090 Vision OC 24G, 24GB GDDR6X, 2x HDMI, 3x DP

Scope of delivery

1 x Alphacool Eiswolf 2
1 x Mounting set GPU
1 x Radiator
3 x Fans
1x Backplate
4 x M2x5 screws
4 x M2x5 washers

6 x M2x11 screws
12 x M3x30 screws
12 x M3x5 screws
2 x M3x5 screws (flat head)
2 x M3x5 nuts
1 x Y-Adaptor 4-Pin PWM
1 x Thermal Grease
1 x 3-Pin JST to 3-Pin 5V adaptor
1 x Plug tool

Data radiator

L x W x H	395 x 124 x 30mm (+/- 3%)
Material cooling fins	Copper
Material chambers	Copper
Material cooling channels	Copper
Material threads	Brass
Material outer housing	stainless steel
G 1/4" threads	2 x for tubes (+ 1x Fillport G1/4")
For fan size	120 mm
Possible fan assembly	3 x one-sided / 6 x both-sided

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Data cooler and pump

L x W x H	152,5 x 266 x 46 mm
Material cooler bottom	Nickel plated copper
Material cooler top	PMMA
Threads	2 x G1/4"
Pump type	DC-LT 2
Pump speed	2600 rpm (+/- 10%)
Head of delivery	0,95 m
Maximum flow rate	75 L/h
Voltage	12V DC
Power consumption	4W
MTBF	50.000 h

Data liquid

Color	Clear
Ingredient 1	Distilled water (CAS-Nummer 7732-18-5)
Ingredient 2	Glysantin (CAS-Nummer 1017-21-1)
Working temperatures	-15 C° / +90 °C

Data quick fasteners

L x D	95 x 27 mm
Material	Nylon
For tube size	12,7 / 7,6 mm
Color	Black

Data fittings

L x D straight fitting	24 x 18 mm
Quantity straight fittings	2x
L x B x H 90° fitting	35 x 27 x 17 mm
Quantity 90° fittings	2x
For tube size	12,7 / 7,6 mm
Material fittings	Brass

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Data tube

Length	50 cm
Material tube	TPV (EPDM/PP)
Color	Matt black
Tube size	12,7 / 7,6 mm
Hardness grade	35 Shore-A to 50 Shore-D
Working temperature	-50 to +155 °C

Data fan

Speed	0 - 2500 RPM
Static pressure	3,17 mm H2O
Air flow rate	119,8 m³/h
Bearings	Sleeve bearing
Fan connector	4-Pin PWM
Connection Digital aRGB	3-Pin JST + 3-Pin 5V
Dimensions	120 x 120 x 25 mm
Net weight	187 g
Max working temperature	60 °C
Certificates	CE, FC, ROHS

Download links

Product pics	http://www.alphacool.com/download/1020894_Eiswolf_2_AIO_360mm_RTX_3080_3090_Gaming_Eagle_BP_pics.zip
Manual	http://www.alphacool.com/download/Eiswolf_2_AIO_manual.pdf

Packaging dimensions 1 unit

L x B x H	47 x 37,5 x 16 cm
Weight	4,7 kg

Other data

Certificates	CE, FC, RoHS
EAN	4250197144162
Customs code	84195080900

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Article text

The Alphacool Eiswolf 2 is the first full cover GPU AIO waterblock from Alphacool. It is based on the Alphacool GPX Eisblock Aurora GPX water block, a pump unit and a 360mm NexXoS ST30 full copper radiator. The latter is equipped with the Alphacool Aurora Rise Digital RGB fans.

Fullcover Waterblock?

The Eiswolf 2 graphics card AIO water block not only cools the GPU with liquid but also all relevant components that require active cooling. This includes the graphics memory, the VRM and, if necessary, other components that require direct cooling. By using the Eisblock GPX Aurora water cooler, the cooling capacity is identical to that of a DIY graphics card water cooler.

Pump

The Eiswolf 2 has a pump unit in place of the normal connection terminal. This pump unit houses the DC-LT 2 pump. An improved and quieter version of the well-known DC-LT Low Noise Ceramic Pump. Despite looking rather large, the pump unit is only 5 mm wider than a normal connection terminal.

Fittings and Tubing

As with all new AIO units, Alphacool uses only TPV hoses from the Enterprise Solution range for (usually reserved for servers and workstations) in the Eiswolf 2. The tubing is made of EPDM/PP and are extremely heat-resistant, durable, and free of plasticizers. All fittings are also based on the Enterprise Solution range and match the TPV hoses perfectly.

Expandability

By using the quick-release fastener, the Eiswolf 2 can be connected to another Alphacool AIO unit to achieve a larger loop in seconds. Alphacool offers various prefilled components with which the loop can be easily extended. For safety reasons, the quick-release fasteners are firmly screwed together and not just plugged together.

Lighting and fans

The Eiswolf 2 cooler has a digital RGB LED lighting, also called addressable RGB LEDs. They run along the entire back of the graphics card cooler and provide complete illumination of the water cooler. The pump unit is more discreet and offers a green glowing logo for Nvidia and a red glowing logo for AMD cards. The name "Eiswolf" on the pump unit remains unlit, discreetly in the background. The fan used is the Aurora Rise with 120mm. Due to the special blade design, the fan is extremely quiet and the addressable RGB LEDs provide brilliant illumination. The Alphacool Aurora Rise fan convinces with a max. static pressure of 3.17mm/H₂O and offers a max. air flow of 119.8m³/h. The PWM control allows the fan to be controlled over a wide speed range. In addition, it offers a zero control. It can therefore be regulated down to 0 rpm and then starts with approx. 350 rpm.

NexXoS Radiator

As with all AIO units, Alphacool uses radiators from the world renowned NexXoS series. The full copper radiators offer a much higher cooling capacity than aluminium radiators and have contributed significantly to Alphacool's worldwide success.

The combination of all of the components results in a solution that is as simple as an AIO solution to install, but with the performance of a pre-assembled and prefilled custom loop.