



50753532



IP55

Blind series push-button with imprinted symbol arrow surface-mounted Berker W.1, polar white matt

Technical features

Architecture

Type of control unit	double rocker
----------------------	---------------

Configuration

- with mechanical and electrical interlock to prevent mutual activation

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	32 mm
Height	75 mm
Width	75 mm

Installation, mounting

- for screw fastening

Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Pins of quick-release lock made of ZAMAK