


41108914

SCHUKO socket outlet with control LED and "ZSV" imprint with labelling field, enhanced contact protection, Screw-in lift terminals, Berker S.1/B.3/B.7, orange glossy

Technical features

Architecture

Design	according to DIN 49440
Technical version	Imprint "ZSV"

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- Central cover plate

Materials

RAL colour	RAL 2003 - Pastel orange
Design lines special colours	orange
Colour	orange
Colour	orange
Material	duroplastic
Surface appearance	glossy

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to VDE 0620-1

- with screw-in lift terminals

Use

- with labelling field
- enhanced contact protection
- Screw-in lift terminals

Standards

Execution SV, ZSV	according to VDE 0100-710

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Berker S.1/B.3/B.7

Instructions

- Labelling field height arranged for P-touch strips 6 mm.
- Insert colour-coded.