


2873



Rotary dimmer (R, L, LED) with soft-lock, Light control, others

Technical features

Main electrical features

Nominal voltage 230 V

Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

Electric current

Control current 100 mA

Fuse

Fine-wire fuse T 3.15 H 250

- with spare fuse
- short-circuit and overload proof (fine-wire fuse)

Power

Dimmable conventional transformers 20 ... 500 VA

Dimmable conventional transformers with LV-LED 20 ... 100 VA

Loss power at full load ≈ 5 W

Materials

Colour not applicable

Material Plastic/metal

Dimensions

Axis dimension Ø 4 mm

Fluorescent bulbs control

Compact fluorescent lamps 3 ... 100 W

LED control

Dimmable 230 V retrofit LED lamps 3 ... 100 W

Incandescent bulbs control

230 V incandescent lamps and halogen lamps 20 ... 500 W

Installation, mounting

- with spreader claws

Connection

Connection cross section (solid-core) 1, 2,5 mm²

Type of load Universal and LED Retrofit

- with terminal for base load from mains isolator
- with plug-in terminals

Settings

- basic brightness programmable

Equipment

- phase cut-on
- with change-over pressure switch

Use

- with soft-lock

Safety

Halogen free yes

temperatur

Ambient temperature 5 ... 45 °C

Identification

Application, usage	Light control
Main design line	Light control
Secondary design line(s)	House electronics

Instructions

- Possible to change fuse without removing cover.