

EUROLITE LED IP PIX Strobe RGB CW+WW 5pin MK2

Outdoor spotlight (IP65) for strobescope, ambient and animation effects

Art. No.: 52200941

GTIN: 4026397742404



List price: 260.61 €

incl. 19% VAT.

Features:

- Compact and bright
- Show programs for white and colored LEDs on separate DMX channels
- 240 powerful LEDs 0,5 W SMD 5050 3in1 TCL RGB
8 segments controlled separately
- 40 powerful LEDs 1 W SMD 3030 2in1 BCL CW/WW
4 segments controlled separately
- Background color adjustable; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; running light adjustable
- 20 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- Preprogrammed in Light Captain; Light J
- Flicker-free
- With a beam angle of 120°
- Variable color temperature 3200 K - 6600 K
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; installation; stage; mobile djs / entertainer; architecture
- Silent operation
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket

Logistic

EAN / GTIN: 4026397742404

Weight: 4,05 kg

Length: 0.41 m

Width: 0.24 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	T 5 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	240 x 0,5 W SMD 5050 3in1 TCL RGB 40 x 1 W SMD 3030 2in1 BCL CW/WW
Flash rate:	1 - 25 Hz
DMX channels:	6; 10; 18; 24; 25; 32
DMX input:	1 x 5-pin XLR (M) mounting version IP
DMX output:	1 x 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Preprogrammed in:	Light Captain; Light J
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3200K - 6600K adjustable
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 38 cm Depth: 11 cm Height: 17,6 cm
Weight:	3,60 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø13mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 1,5 mm² H07RN-F
Cable length:	Approx. 1,2 m
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting