

OVERVIEW



| | |
|--|---------------------|
| 1. Headphone / microphone combo jack (3.5mm) | 5. Ethernet (RJ-45) |
| 2. USB 3.2 Gen 1 | 6. HDMI 2.0 |
| 3. USB 3.2 Gen 1 | 7. USB-C 3.2 Gen 1 |
| 4. Power connector | |

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 5 / 7 Processor

Processor

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|-------------------|-------|---------|----------------|---------------|------------------|----------------|----------------------|
| AMD Ryzen 5 5600H | 6 | 12 | 3.3GHz | 4.2GHz | 3MB L2 / 16MB L3 | DDR4-3200 | AMD Radeon™ Graphics |
| AMD Ryzen 7 5800H | 8 | 16 | 3.2GHz | 4.4GHz | 4MB L2 / 16MB L3 | DDR4-3200 | AMD Radeon Graphics |

Operating System

Operating System

- Windows® 10 Pro 64
- Windows 10 Home 64
- No operating system

Graphics

Graphics

| Graphics | Type | Memory | Boost Clock | TGP | Key Features |
|---------------------------------------|----------|-----------|---------------------|-----|----------------------|
| NVIDIA® GeForce® GTX 1650 | Discrete | 4GB GDDR6 | - | - | DirectX® 12 |
| NVIDIA GeForce RTX™ 3050 Laptop GPU | Discrete | 4GB GDDR6 | 1500 MHz | 75W | DirectX 12 |
| NVIDIA GeForce RTX 3050 Ti Laptop GPU | Discrete | 4GB GDDR6 | 1485 MHz | 75W | DirectX 12 |
| NVIDIA GeForce RTX 3060 Laptop GPU | Discrete | 6GB GDDR6 | 1282 MHz / 1485 MHz | 90W | VR ready, DirectX 12 |

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 3840x2162@60Hz)

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 16GB DDR4-3200 offering

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

- Model with RTX 3060: up to two drives, 2x M.2 SSD
 - M.2 2242 SSD up to 512GB
 - M.2 2280 SSD up to 1TB
- Non-RTX 3060 model: up to two drives, 1x 2.5" HDD + 1x M.2 2242 SSD or 1x M.2 2242/2280 SSD + 1x M.2 2242 SSD

IdeaPad Gaming 3 15ACH6

- 2.5" HDD up to 1TB
- M.2 2242 SSD up to 512GB
- M.2 2280 SSD up to 1TB

Storage Slot^[1]

- RTX 3060 model: two M.2 slots
 - One M.2 2242 PCIe Gen 3x4 slot, supports M.2 2242 SSD
 - One M.2 2280 PCIe Gen 3x2 slot, supports M.2 2242/2280 SSD
 - Non-RTX 3060 model: one 2.5" drive slot + two M.2 slots
 - One 2.5" drive slot, supports 2.5" HDD
 - One M.2 2242 PCIe Gen 3x4 slot, supports M.2 2242 SSD
 - One M.2 2280 PCIe Gen 3x2 slot, supports M.2 2242/2280 SSD
- 2.5" drive slot and M.2 2280 slot are used exclusively

Storage Type

| Disk Type | Interface | RPM | Offering | Security |
|---------------|------------------------|------|----------|----------|
| 2.5" SATA HDD | SATA 6Gb/s | 5.4K | - | - |
| M.2 2242 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - | - |

Notes:

1. Installed M.2 2280 SSD is PCIe 3x4 but run at PCIe 3x2 due to M.2 SSD adapter limitation

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Nahimic Audio

Microphone

Dual array microphone

Camera

720p, with camera shutter, fixed focus

Battery

Battery

- Integrated Li-Polymer 45Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- Integrated Li-Polymer 60Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life^[1]

- MobileMark® 2018: 5 hr (45Wh)
- MobileMark 2018: 7 hr (60Wh)

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

- 135W slim tip (3-pin) AC adapter
- 170W slim tip (3-pin) AC adapter

DESIGN

Display

Display^[1]

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|-----------------|-------|------|------------|------------|--------------|----------------|-------------|---------------|--|
| 15.6" | FHD (1920x1080) | None | IPS | 250 nits | Anti-glare | 16:9 | 800:1 | 45% NTSC | 170° | Refresh rate 60Hz, DC dimmer |
| 15.6" | FHD (1920x1080) | None | IPS | 250 nits | Anti-glare | 16:9 | 800:1 | 45% NTSC | 170° | Refresh rate 120Hz, Free-Sync, DC dimmer |
| 15.6" | FHD (1920x1080) | None | IPS | 300 nits | Anti-glare | 16:9 | 1000:1 | 100% sRGB | 170° | Refresh rate 165Hz, Free-Sync, DC dimmer |

Touchscreen

Non-touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.

For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

- White backlight
- 4-Zone RGB backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

| Models | Dimensions |
|------------|--|
| All models | 359.6 x 251.9 x 24.2 mm (14.16 x 9.92 x 0.95 inches) |

Weight^[1]

| Models | Weight |
|------------|--------------------|
| All models | 2.25 kg (4.96 lbs) |

Case Color

Shadow black

Surface Treatment

IMR (in-mold decoration by roller)

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet

WLAN + Bluetooth®

- 802.11ac 1x1 Wi-Fi® + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.0, M.2 card

Ports^[1]**Standard Ports^[2]**

- 2x USB 3.2 Gen 1
- 1x USB-C 3.2 Gen 1 (support data transfer only)
- 1x HDMI 2.0
- 1x Ethernet (RJ-45)
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

No fingerprint reader

BIOS Security

- Supervisor password
- Power-on password
- Hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

ACCESSORIES

Bundled Accessories

Bundled Accessories

- Lenovo Gaming M100 RGB Mouse (USB connector)
- None

CERTIFICATIONS

Green Certifications

Green Certifications

- ErP Lot 3
- RoHS compliant



AMD



AMD



AMD



AMD



AMD



AMD