



7 Port USB 3.2 Gen 2 Metal Hub

No.: 43275

7 additional USB 3.2 Gen 2 ports - perfect for industrial applications

Description

- Connects 4 Type A and 3 Type C USB 3.2 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.2 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.2 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- USB Standard: USB 3.2 / 3.1 Gen 2
- Supported Bandwidth: 10Gbps
- Chipset: 2x VL820
- Compatibility: USB Type C equipped computers, Thunderbolt 3 (incl. Apple M1)
- Power Delivery: -
- Special Features: Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

Connectors

- Inputs: 1 x USB Type C (Female)
- Outputs: 3 x USB Type C (Female), 4 x USB Type A (Female)
- Power: DC screw connector

Physical Properties

Dimensions WxDxH: 184.5x64.3x20mm (7.26x2.53x0.79in)

[Fixed] Cable Length: -

Housing Material: Metal

Net Weight: 0.3kg (0.66lb)

Operating Temperature: 0°C - 50°C (32°F -122°F)

Storage Temperature: -20°C - 60°C [-4°F -140°F]

Humidity: 90% RH (non-condensing)

Power Requirements: 16VDC 3A

Colour: Black

Miscellaneous

Packaging Type: Carton Box

Packaging Dimensions: 260x180x70mm (10.24x7.09x2.76in)

Gross Weight: 0.844kg (1.86lb)

Warranty (Years): 2

Product Compliance: CE, FCC, RoHS, REACH, California Proposition 65

Package Contents

7 Port USB 3.2 Gen 2 Metal Hub

0.55m USB 3.2 Gen 2 Dual Screw Type C Male to Male Cable

Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector

Lindy Manual

Purchasing Information

No.: 43275

EAN: 4002888432757