



Busch-Radio DAB+

Functions at a glance

- Aufgrund des weltweit andauernden Mangels an Bauteilen kommt es zu erheblichen Lieferzeiten.
- DAB+ and RDS stereo radio alarm clock for flush-mounted installation.
- With high-resolution colour display for showing additional information.
- Reception frequency: 87.50 MHz - 108.00 MHz.
- Receive frequency (DAB+): 174 MHz - 240 MHz.
- With external AUX input/output, reversible.
- For mono/stereo operation.
- 8 radio stations storable.
- With time and date display.
- With individual alarm and snooze function.
- With automatic switch-off function (automatic sleep mode).
- With extension input to remote-controlled ON/OFF switches.
- With integrated antenna.
- With additional connection for external antenna.
- Permitted speaker impedance: 4 - 8 Ohm
- Can be installed as 1gang and in multiple combinations.
- Control element: 4-button operation via floating rocker
- Display elements: ICU graphic display with 280 DPI.
- Rated voltage: 230 V~, +10 % / -10 %
- Rated frequency: 50 Hz / 60 Hz
- Power dissipation: 0.4 W
- Control/Signal outputs: 2 Loudspeaker output, impedance 4 Ohm
- Rated output: 2 W (RMS)
- Protection class (device): IP 20
- Temperature range (device): 5 °C - 40 °C
- Storage temperature range: -20 °C - 70 °C
- Dimensions: (L x W x D): 71 mm x 71 mm x 47 mm
- Mounting depth: 32 mm
- No claw. Screw-fixing via keyholes.

Order details

Article No.:	8215 U-101
Order No.:	2CKA008200A0275
EAN:	4011395304914
Customs tariff number:	85279200
Price group:	19
Price:	147,00 EUR plus VAT

Downloads

Instruction manual

- » [Installation and operating instructions](#)
- » [Launch flyer](#)
- » [Product manual](#)

Certificates

- » [EU-declaration of conformity](#)
- » [ROHS product declaration](#)

Software

- » [Open Source Software licenses](#)