

DATASHEET

19" Wall Housing BASIC, Depth 600 mm, RAL9010



Description

19" Wall housing 1-part, type Flat Pack
 Steel sheet housing screwable, not pre-assembled
 Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
 Front door lockable, Door opening angle 120°
 Door stop easy changeable (right/left)
 Sidewalls not detachable
 Roof prepared for mounting of 2 x single fans
 Roof and bottom with cable entry 145 x 70 mm
 Inside 2 x 19" profile rails, depth-adjustable, with lateral opening for cable routing
 Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
 Width 535 mm, depth 450 / 600 mm
 Max. load 80 kg (static, equally distributed)
 Protection degree IP20
 Incl. key
 Delivery unassembled in 1 carton with handle

General data

Mounting level	Front side
Type of profile rail	L-shaped
Type of ventilation	Passive
Modular spacing	482.6 mm (19 inch)
With roof plate	True

This datasheet was created automatically on 29-07-2021 . Technical changes reserved.



DATASHEET

19" Wall Housing BASIC, Depth 600 mm, RAL9010

General data

With front door	True
With sidewall	True
Demountable	True
Model	With permanent frame
Material	Steel
Type of surface	With powder coating
Degree of protection (IP)	IP20
Number of doors	1
Number of cartons	1

Available variants

Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour
WGB-1906WS.60	19" 06U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	6	535 mm	30 mm	600 mm	80 kg	9010	White
WGB-1909WS.60	19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	9	535 mm	437 mm	600 mm	80 kg	9010	White
WGB-1912WS.60	19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	12	535 mm	571 mm	600 mm	80 kg	9010	White
WGB-1915WS.60	19" 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	15	535 mm	707 mm	600 mm	80 kg	9010	White

accessory

WGB-PRO06	19" Mounting Rails for Wall Housing BASIC
EK631DE.3	19" 1U Socket Strip 7 x CEE 7/3 with Surge Protection
EK631DE.2	19" 1U Socket Strip 8 x CEE 7/3 with Switch
EK631DE.1	19" 1U Socket Strip 9 x CEE 7/3 without Switch
EK504.2V2	Power Cable CEE7/7 90° - C13 180°, black
691656WS	Fan Unit, 2-Fans for Wall Housings, Plug & Play, RAL9010

This datasheet was created automatically on 29-07-2021 . Technical changes reserved.

