

HANN.S·G











by HANNspree

HS241HPB | EU

60cm / 23.6" Diagonal White LED-Backlight



- 1920 x 1080 WUXGA Resolution (60cm / 23.6" Diagonal)
- LED Backlight Monitor
- ULTRA-WIDE VIEWING ANGLE
- Full HD 1080P
- 80,000,000:1 Active Contrast
- 5ms Response Time
- VGA+DVI+HDMI Compatible Inputs
- Multi-Video Modes : PC / Movie / Game / ECO
- Built-In Stereo Speakers
- Tilt and Wall-Mountable (VESA)
- Low Power Consumption

 Backlight LED	 1920x1080 RESOLUTION	 80,000,000:1	 5ms FAST RESPONSE TIME	 LOW POWER CONSUMPTION
 VIDEO MODES	 STEREO	 VESA WALL-MOUNTABLE	 178° ULTRA-WIDE VIEWING ANGLE	
 ASPECT RATIO	 16:9	 23.6" VIEWABLE SCREEN	 HDCP	 FULL HD 1080P

HS241HPB | EU

60cm / 23.6" Diagonal White LED-Backlight

HANNING

by **HANNspree**

EAN



4 711404 020513

LCD Panel	Display size	60cm / 23.6" Diagonal White LED-Backlight	
	Brightness	250cd/m2 (Typical)	
	Contrast	1000:1 (Typical) 80,000,000:1 (Active Contrast)	
	Pixel pitch	0.271(H) x 0.271(V)	
	Resolution (H x V)	1920 x 1080	
	Aspect Ratio	16:9	
	Response time	5ms	
	View angles LR,UD	H/V 178°/178°Ultra Wide Viewing Angle (IPS, ADS, PLS... type of panel)	
	Color	WARM,NATURE,COOL, User Mode	
	Panel surface	Anti-glare	
	Display colors	16.7M Colors	
	PC Input Range	Horizontal Freq.	30 to 83KHz
		Vertical Freq.	56Hz to 75Hz
Max. display frequency (Resolution H*V/Fv)		1920 x 1080 /60 Hz	
Interface	Input	D-Sub x 1, HDMI x1,PC Audio x1 ,DVI-D (HDCP) x1	
Output Terminal	Earphone	Yes	
	Speaker	Yes	
Power	Consumption	On: 30 W; Standby<=0.5W, Off<=0.5W	
	AC Power Range	AC 100~240V, 50~60Hz	
	Power Mode Indicator Light	Power on : Green (LED) Power saving : Orange(LED)	
Operating Condition	Temperature	5°C ~ 35°C	
	Humidity	20% ~ 85%, non-condensing	
Physical	Dimension (W*D*H)	561 x 220 x 399mm	
	Packing Dimension (W*D*H)	614 x 109 x 465mm	
	Net weight	4.4Kg	
	Gross weight	5.7Kg	
	Tilt	-5° ~ 15°	

Physical	Kensington Lock	Yes
	VESA mounting	100 x 100mm
Controls	Front control	MENU ▲/☼ ▼/🔊 i/📺 ⏻
	On Screen Display	12 language : EN, TC, DE, FR, ES, IT, PT, NL, SC, JS, KR, Russian
	Preset Mode	PC, Movie, Game, ECO Modes
Container Loading	40' Standard	EU: 1470
	20' Standard	EU: 700
Accessories	Power Cable(1.5m), VGA Cable(1.5m), Audio Cable(1.5m), User Manual (CD), Quick Start Guide (Paper)	
Color Plan	Arm / Base /Bezel / Rear Cover - Texture	
Carton box	Brown carton	
Green product (Jan. 2009)	Yes	
Window 8	NA	
Others	PC99 function(must)	
Certification	CE, CB, EnergyStar6.x ,TCO6.0,G5	

Contact Information

Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local Hannspree authorized representatives for the availability of specific products in your area. Hannspree reserves the right to alter design and specifications as well as to change the accessories with equivalents without notice.