Item No. 87691

Delock Displayport 1.2 Splitter 1 x Displayport in > 2 x Displayport out 4K

Description

This splitter by Delock receives a Displayport signal from a PC or laptop and splits it to two connected displays. Thereby one Displayport connection can be used to operate two Displayport monitors. The outputs are dual-mode capable (DP++), so that HDMI or DVI monitors can be connected with suitable adapters.



Specification

- Connector:
  Input:
  1 x Displayport 20 pin female
  1 x DC 5 V power connector
  Output:
  2 x Displayport 20 pin female
- Chipset: STDP4320
- Displayport 1.2a specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Maximum resolution (depending on the system and the connected hardware):
  Displayport 1.1 or 1.2 Single Stream Transport (SST):
  up to 1920 x 1080 @ 60 Hz (mirror)
  Displayport 1.2 Multi Stream Transport (MST):
  up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (mirror or extended)
- Displayport output supports Dual Mode DP++
- Supports audio and video signals
- Supports Eyefinity / Single Large Surface (SLS)
- Audio input formats: 7.1 channel up to 192 kHz sample rate
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 71 x 61 x 21 mm
- Length: power cable USB Type-A > DC ca. 50 cm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 9 mm

System requirements

- A free Displayport female port
- Displayport cable

Package content

Additional Information

EAN: 4043619876914

Country of origin: China

Package: Retail Box




© 2017 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

- Displayport Splitter
- USB power cable
- External power supply
- User manual

Images







© 2017 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Specification:	Displayport 1.2a
Interface	
Output:	2 x Displayport 20 pin female
Input:	1 x Displayport 20 pin male
Technical characteristics	
Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Physical characteristics	
Housing material:	metal
Cable length incl. connector:	30 cm
Length:	100 mm
Width:	67 mm
Height:	23 mm
Colour:	black

© 2017 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.