

# SUB-10

Order No.: 0259875

## PRODUCTINFOS

**This 25 cm (10") passive subwoofer**

has been developed to deliver a powerful bass reproduction from compact cabinets and features a power rating of 500 W max. The band-pass cabinet with its 10" bass speaker of long excursion generates a dry and deep bass. It can be used as subwoofer support for PA systems in restaurants and bars or shops to ensure a rich and powerful sound. Nevertheless, it can also be used as an additional subwoofer for smaller PA speakers and simply be connected in parallel due to the integrated crossover network (low-pass filter at approx. 200 Hz).

**Passive subwoofer, 500 W/8 Ω**

- Band-pass subwoofer with double ventilation
- 1 x 25 cm (10") top-class woofer
- Slimline and compact design for upright and horizontal setup
- High-quality lacquered cabinet made of plywood, front grille with inner lining
- Integrated crossover network (low-pass) with crossover frequency at 200 Hz
- 4 x M8 lateral threaded insert as installation aid
- Speakers connected to the subwoofer in parallel must have a nominal impedance of 8 Ω min.
- Stand sleeve at the top

# TECHNICAL SPECIFICATIONS

**SUB-10**

| | |
|---|---|
| Active/passive | passive |
| Transmission technology | cable |
| Total power rating | 500 W |
| Power rating (RMS) | 250 W |
| Impedance | 8 Ω |
| Frequency range | 40-200 Hz |
| System | band-pass subwoofer |
| Bass speaker | 1 x 25 cm (10") |
| Number of speakers | 1 |
| Speaker size | 25 cm (10") |
| SPL | 92 dB/W/m |
| Max. rated SPL | 116 dB |
| Beam angle | omnidirectional |
| Housing material | multiplex |
| Colour | black |
| Mounting device | threaded inserts |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 300 x 610 x 410 mm |
| Width | 300 mm |
| Height | 610 mm |
| Depth | 410 mm |
| Weight | 19.84 kg |
| Inputs | 1 x NEUTRIK SPEAKON, speaker terminals |
| Packing dimensions (W x H x L) | 0.42 x 0.74 x 0.53 m |
| Gross weight | 23.66 kg |
| Net weight | 19.84 kg |