



30753525



IP55

Blind series switch 1pole with imprinted symbol arrow surface-mounted Berker W.1, grey/light grey matt

Technical features

Architecture

Type of control unit double rocker

Configuration

- with mechanical and electrical interlock to prevent mutual switch-on

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Electric current

Switching current 10 A

Materials

RAL colour RAL 7011 - Iron grey

Colour of design line grey/light grey

Colour dark grey

Colour iron grey

Material thermoplastic

Surface appearance matt

Dimensions

Depth 62 mm

Height 76 mm

Width 76 mm

Installation, mounting

- for screw fastening

Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP IP55

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Pins of quick-release lock made of ZAMAK