Delock USB Type-C™ Docking Station for 4 x SATA HDD / SSD

Description

This HDD / SSD Docking Station in by Delock enables an external connection of up to **four 2.5″ or 3.5″ SATA HDDs** / **SSDs** through the USB-C™ interface, as well as the simple exchange of the drives by Hot Swap.

Four bays for HDD / **SSD**
Up to four HDDs or SSDs can be inserted and accessed simultaneously.

USB Type-C™ connection and separate power supply
Due to the **USB Type-C™** port and the included USB-C™ cable, the docking station can easily be connected to laptops, netbooks and ultrabooks. In addition, the power supply included in the delivery content ensures a **sufficient power supply** for the storage devices used.

Specification

- Connectors:
  4 x SATA 6 Gb/s 22 pin receptacle
  1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
  1 x DC jack
- Chipset: Genesys Logic GL3523, JMicron JMS578
- Function key:
  1 x On / Off switch
- For 2.5″ and 3.5″ SATA HDD / SSD
- Suitable for all SATA HDDs / SSDs up to SATA 6 Gb/s
- Data transfer rate up to:
  SuperSpeed 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- 10 x LED indicator
- Bootable
- Dimensions (LxWxH): ca. 166 x 127 x 65 mm
- Hot Swap, Plug & Play

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2 A
- Output: 12 V / 6.5 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 10 mm

System requirements

- Chrome OS
- Linux Kernel 3.19 or above
- Mac OS 10.14.2 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port

Package content

- Docking station
- 1 x Cable USB-C™ male to USB-C™ male, length ca. 80 cm
- External power supply
- User manual

Item no. 63930

EAN: 4043619639304

Country of origin: China

Package: • Retail Box

Images

General	
Function:	Hot Swap
	Plug & Play
	bootable
Suitable for data medium:	2.5″
	3.5″
	SSD or HDD
Supported operating system:	Chrome OS
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 3.17 or above
	Mac OS 10.14.2 or above
Interface	
External:	1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
	1 x DC 12 V power connector
Internal:	4 x SATA 6 Gb/s 22 pin receptacle
Technical characteristics	
Chipset:	Genesys Logic GL3523
	JMicron JMS578
Data transfer rate:	5 Gbps
Physical characteristics	
Housing material:	Plastic
Length:	166 mm
Width:	127 mm
Height:	65 mm
Colour:	black