



SPEZIFIKATIONEN

FRAME	
GRÖSSEN	S, M, L, XL
FARBEN	Metal / Black Diamond
RAHMEN	ALUXX SL-Grade Aluminum front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
GABEL	RockShox Yari RC, 170mm, 15x110 Maxle Stealth, 44mm offset, custom tuned for Giant
DÄMPFER	RockShox Deluxe Select+, 205/60, custom tuned for Giant
KOMONENTEN	
LENKER	Giant Contact TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SATTEL	Giant Romero
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano SLX SL-M7100, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano SLX RD-M7100
BREMSEN	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]203mm
BREMSHEBEL	Shimano Deore BL-MT501
KASETTE	Shimano Deore M6100, 10x51
KETTE	Shimano
KURBELSATZ	Shimano SLX, 32t S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant AM 29, alloy
NABEN	alloy, sealed
SPEICHEN	Sapim
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, EXO+, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

ERFAHREN SIE MEHR....

- Rahmen: ALUXX SL-Grade Aluminum front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
- Gabel: RockShox Yari RC, 170mm, 15x110 Maxle Stealth, 44mm offset, custom tuned for Giant
- Schalthebel: Shimano SLX SL-M7100, 1x12
- Kurbelsatz: Shimano SLX, 32t S:165mm, M:170mm, L:170mm, XL:170mm
- Farben: Metal / Black Diamond

Preis: € 3.299

GEOMETRIEDATEN

FRAME	S	M	L	XL
Sitzrohrlänge (mm)	431	431	464	496
Sitzrohrwinkel	76,4°	76,4°	76,4°	76,4°
Oberrohrlänge (mm)	574	601	640	666
Steuerrohrlänge (mm)	100	100	110	120
Steuerrohrwinkel	64,6°	64,6°	64,6°	64,6°
Gabel (mm)	44	44	44	44
Spur (mm)	132,7	132,7	132,7	132,7
Radstand (mm)	1191	1220	1262	1289
Kettenstrebenlänge (mm)	439	439	439	439
Tretlager (mm)	27	27	27	27
Stapel (mm)	622	622	631	640
Reichweite (mm)	423	451	488	511
Überstandshöhe (mm)	757	759	781	804
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	40	40	40
Kurbellänge (mm)	165	170	170	170
Radgröße	29"	29"	29"	29"

Preis- und Farbänderungen vorbehalten. Aufgrund der aktuell durch das Corona-Virus verursachten Probleme in den Lieferketten sämtlicher Zulieferer kann das Bike, entgegen der hier kommunizierten Spezifikation, mit abweichenden Komponenten ausgeliefert werden.