


DATASHEET

Network Cabinet OFFICE 18U, 600x600 mm, RAL9005



General data

19" network cabinet according to DIN41494

Steel sheet housing, self-supporting, completely pre-assembled, self-ventilated

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Front door full glass, 1-part (thickness 4 mm)

Front door with 1-point latch-locking

Door stop possible left or right-sided

Bottom and rear with pre-punched openings for cable entry (ca. 245 x 25 mm)

Roof and bottom prepared for accommodation of 1 x fan unit (Art.-No. 691664)

Internal earthing of all cabinet sections

Paint finish RAL7035, light grey / RAL9005, jet black

- Max. load 12U 30 kg, 15U 38 kg, 18U 45 kg

Protection degree IP20

Included in delivery: 1 x brush, 4 x leveling feet M8, 2 x key

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

Network Cabinet OFFICE 18U, 600x600 mm, RAL9005

Delivery in transport packaging on disposable pallet

Technical properties

Cabinet Series	Office
Degree of protection	
Demountable	
Material	
Modular spacing	
Mounting level	
Surface finishing	
Toolless depth adjustment	False
Type of back door	Rear wall
Type of front door	Full glass door 1-part
Type of profile rail	
Type of ventilation	
With backside door	
With earthing	
With front door	
With roof plate	
With sidewall	
With socket	

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Max. Load Capacity	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen
OFF-1266TS.V1RW	Network Cabinet OFFICE 12U, 600x600 mm, RAL9005	black	600 mm	30 kg	12 U	600 mm	604 mm	9005	1
OFF-1566TS.V1RW	Network Cabinet OFFICE 15U, 600x600 mm, RAL9005	black	600 mm	38 kg	15 U	600 mm	737 mm	9005	1
OFF-1866TS.V1RW	Network Cabinet OFFICE 18U, 600x600 mm, RAL9005	schwarz	600 mm	45 kg	18 HE	600 mm	871 mm	9005	1


Drawings

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

Network Cabinet OFFICE 18U, 600x600 mm, RAL9005



This datasheet was created automatically on 11-09-2025 . Technical changes reserved.