



27" IPS monitor with USB-C

Equipped with a USB-C connector, the XUB2792HSC allows you to simplify your workspace by using a single cable to power and charge the notebook from the monitor. The IPS matrix offers accurate and consistent colour reproduction with wide viewing angles. The blue light reducer function with flicker free LCD technology reduce eye strain and offer a more comfortable viewing experience. Supplied with a 150mm height-adjustable stand featuring pivot and swivel functions, the XUB2792HSC allows you to easily adjust the screen position to your preferences.



IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.



USB-C

With one wire you can charge your laptop, connect video (DP-alt mode) and connect with your peripherals through the built-in USB 3.0 HUB.

01 DISPLAY CHARACTERISTICS

| | |
|---------------------|---|
| Design | 3-side borderless |
| Diagonal | 27", 68.6cm |
| Panel | IPS LED, matte finish |
| Native resolution | 1920 x 1080 @75Hz (2.1 megapixel Full HD) |
| Aspect ratio | 16:9 |
| Panel brightness | 250 cd/m ² |
| Static contrast | 1000:1 |
| Advanced contrast | 80M:1 |
| Response time (GTG) | 4ms |
| Viewing zone | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support | 16.7mIn (sRGB: 99%; NTSC: 72%) |
| Horizontal Sync | 30 - 85kHz |
| Viewable area W x H | 597.8 x 336.3mm, 23.5 x 13.2" |
| Pixel pitch | 0.311mm |
| Colour | matte, black |

02 INTERFACES / CONNECTORS / CONTROLS

| | |
|---------------------|--|
| Signal input | HDMI x1 DisplayPort x1 USB-C x1 (Power delivery 65W) |
| USB HUB | x2 (v.3.0 (DC5V, 900mA)) |
| HDCP | yes |
| Headphone connector | yes |
| USB-C | x1 (Power delivery 65W) |

03 FEATURES

| | |
|--------------------|---|
| Blue light reducer | yes |
| Flicker free | yes |
| Extra | i-Style colour |
| OSD languages | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL |
| Control buttons | Power, Menu/Select, + / Volume, - / ECO, Exit, Input |
| User controls | picture adjust (brightness, contrast, ECO, blue light reducer, ACR, OD), colour (colour temp., user preset, i-style colour), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, USB BC, MST, display information), input select (input source), audio (volume, mute) |
| Speakers | 2 x 2W |
| Convenience | Kensington-lock™ prepared, DDC2B, Mac OSX |

04 MECHANICAL

| | |
|------------------------------|---|
| Display position adjustments | height, swivel, tilt, pivot (rotation both sides) |
| Height adjustment | 150mm |
| Rotation (PIVOT function) | 90° |
| Swivel stand | 90°; 45° left; 45° right |
| Tilt angle | 23° up; 5° down |
| VESA mounting | 100 x 100mm |

Cable management system yes

05 ACCESSORIES INCLUDED

| | |
|--------|---------------------------------|
| Cables | power, HDMI, USB-C |
| Other | quick start guide, safety guide |

06 POWER MANAGEMENT


| | |
|-------------------|---|
| Power supply unit | internal |
| Power supply | AC 100 - 240V, 50/60Hz |
| Power usage | 20W typical, 0.5W stand by, 0.5W off mode |

07 SUSTAINABILITY

| | |
|---|---|
| Regulations | TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| TCO Certified | XUB2792HSC-B5 H |
| Energy efficiency class (Regulation (EU) 2017/1369) | E |
| REACH SVHC | above 0.1%: Lead |

08 DIMENSIONS / WEIGHT

| | |
|------------------------------|-------------------------------|
| Product dimensions W x H x D | 612 x 393.5 (543.5) x 209.5mm |
| Box dimensions W x H x D | 693 x 170 x 440mm |
| Weight (without box) | 6.6kg |
| Weight (with box) | 7.0kg |
| EAN code | 4948570121786 |



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED