

Hardware Maintenance Manual

Lenovo
LEGION

Lenovo

Lenovo Legion 5a (15", 11) and Lenovo Legion 5i (15", 11)

Second Edition (March 2026)

© Copyright Lenovo 2026.

LIMITED AND RESTRICTED RIGHTS NOTICE: If data or software is delivered pursuant to a General Services Administration "GSA" contract, use, reproduction, or disclosure is subject to restrictions set forth in Contract No. GS-35F-05925.

Contents

About this manual ii

Chapter 1. Safety requirements for hardware maintenance 1

General safety requirements	1
Electrical safety requirements	1
Safety inspection guide	3
Handling devices that are sensitive to electrostatic discharge	3
Important danger warning in multiple languages	4

Chapter 2. Diagnostics and troubleshooting 17

Diagnostics applications	17
Hardware scan in Legion Space	17
UEFI diagnostics application	18
Advanced diagnostics application (Windows version)	18
Advanced diagnostics application (bootable versions for Linux/UEFI)	18
Call Lenovo	19
Before you contact Lenovo	19
Lenovo Customer Support Center	19
Nonwarranted items and activities	20

Chapter 3. Parts, screws, and tools 21

Parts	21
Part type definition	21
Look up a part	22
Exploded view and part list	22
Screws	24
Screw list	24
Screw notices	25
Service tools	26

Chapter 4. Hardware replacement 29

General guidelines	29
Lower case	29
Label locations	30
Battery pack	31

M.2 solid-state drive	33
Wi-Fi card and Wi-Fi card mylar	36
Memory module shielding	38
Memory module	39
Speakers	40
Audio board	41
PMIC board (for selected models)	43
DC-in bracket	45
Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11	45
Legion 5 15IAX11	46
Thermal module	48
Handling thermal interface materials	51
USB board (for selected models)	54
System board, USB board cable (for selected models), and audio board cable	55
Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11	55
Legion 5 15IAX11	57
Write key product information to a replacement system board	60
Hinge cover	61
LCD/OLED module	62
LCD Self Test	64
Upper case (with keyboard)	64
Disassemble the LCD/OLED module	65
LCD/OLED bezel	65
Camera bracket	65
Strip cover	66
LCD/OLED panel	67
Camera board	70
Microphone rubbers	70
LCD/OLED cover	71

Appendix A. Important notice for Quebec consumers 72

Appendix B. Self-help resources 73

Trademarks	lxxiv
----------------------	-------

About this manual

This manual contains hardware maintenance instructions for the products listed in the following table. In this manual, you will read safety requirements for hardware maintenance, diagnostics and troubleshooting, hardware replacement instructions, and other reference information. Use the manual along with the diagnostics applications and service tools to troubleshoot problems effectively.

Product name	Machine type (MT)
Legion 5 15AGP11	83Q6
Lenovo Legion 5 15AGP11 D1	
Legion 5 15AHP11	83Q7
Lenovo Legion 5 15AHP11 D1	
Legion 5 15IAX11	83QE, 83VK
Lenovo Legion 5 15IAX11 D1	
Legion 5 15IPH11	83RW
Lenovo Legion 5 15IPH11 D1	

Important:

- Hardware configurations and software programs vary by machine type. Some statements or illustrations in this manual might be slightly different from your computer.
- It is recommended that the computer be repaired by trained service technicians.
- For customers electing to service the computer on their own, it is still recommended to speak to our Customer Support Center so that you can be directed to the correct documentation and repair information. See “Call Lenovo” on page 19. Depending on the complexity of the repair, it may be recommended to have a Lenovo-authorized service provider repair your computer.
- Before servicing a computer, please follow all instructions carefully and be sure to read all the information under Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.

Chapter 1. Safety requirements for hardware maintenance

This chapter presents the following safety information that you need to be familiar with before you service a Lenovo notebook computer.

General safety requirements

Meet the following requirements on environment, personnel and outfit, and operation to ensure general safety:

Environment requirements

Observe good housekeeping in the area of the machines during and after maintenance.

Personnel and outfit requirements

- Do not wear loose clothing that can be trapped in the moving parts of a machine. Make sure that your sleeves are fastened or rolled up above your elbows. If your hair is long, fasten it.
- Insert the ends of your necktie or scarf inside clothing or fasten it with a non-conductive clip, about 8 centimeters (3 inches) from the end.
- Do not wear jewelry, chains, metal-frame eyeglasses, or metal fasteners for your clothing.

Attention: Metal objects are good electrical conductors.

- Wear safety glasses when you are hammering, drilling, soldering, cutting wire, attaching springs, using solvents, or working in any other conditions that might be hazardous to your eyes.

Operation requirements

- Before you start the machine, make sure that no one is in a hazardous position.
- Do not perform any action that causes personal injury, or that makes the equipment unsafe.
- Keep your tool case away from walk areas so that other people will not trip over it.
- When lifting any heavy object:
 1. Make sure that you can stand safely without slipping.
 2. Distribute the weight of the object equally between your feet.
 3. Use a slow lifting force. Never move suddenly or twist when you attempt to lift.
 4. Lift by standing or by pushing up with your leg muscles; this action removes the strain from the muscles in your back. Do not attempt to lift any object that weighs more than 16 kg (35 lb) or that you think is too heavy for you.
- Place removed covers and other parts in a safe place, away from all personnel, while you are servicing the machine.
- After service, reinstall all safety shields, guards, labels, and ground wires. Replace any safety device that is worn or defective. Reinstall all covers correctly.
- Fan louvers on the machine help to prevent overheating of internal components. Do not obstruct fan louvers or cover them with labels or stickers.

Electrical safety requirements

To ensure electrical safety, meet the following requirements on environment, outfit, and operation when working on the computer:

Environment requirements

- Find the room emergency power-off (EPO) switch, disconnecting switch, or electrical outlet. If an electrical accident occurs, you can then operate the switch or unplug the power cord quickly.
- Do not work alone under hazardous conditions or near equipment that has hazardous voltages.

- Always look carefully for possible hazards in your work area. Examples of these hazards are moist floors, non-grounded power extension cables, power surges, and missing safety grounds.

Outfit requirements

- Do not use worn or broken tools and testers.
- Regularly inspect and maintain your electrical hand tools for safe operational condition.

Important:

- Use only approved tools and test equipment. Some hand tools have handles covered with a soft material that does not insulate you when working with live electrical currents.
- Many customers have, near their equipment, rubber floor mats that contain small conductive fibers to decrease electrostatic discharges. Do not use this type of mat to protect yourself from electrical shock.

Operation requirements

- Disconnect all power before:
 - Performing a mechanical inspection
 - Working near power supplies
 - Removing or installing main units
- Do not service the following parts with the power on when they are removed from their normal operating places in a machine:
 - Power supply units
 - Pumps
 - Blowers and fans
 - Motor generators
 - Similar units as listed above

This practice ensures correct grounding of the units.
- Electrical grounding of the computer is required for operator safety and correct system function. Proper grounding of the electrical outlet can be verified by a certified electrician.
- Observe the special safety precautions when you work with very high voltages; Instructions for these precautions are in the safety sections of maintenance information. Use extreme care when measuring high voltages.
- Before you start to work on the machine, unplug the power cord. If you cannot unplug it, ask the customer to power-off the wall box that supplies power to the machine, and to lock the wall box in the off position.
- Never assume that power has been disconnected from a circuit. First, check that it has been powered off.
- Do not touch live electrical circuits with the reflective surface of a plastic dental mirror. The surface is conductive; such touching can cause personal injury and machine damage.
- If you need to work on a machine that has exposed electrical circuits, observe the following precautions:
 - Ensure that another person, familiar with the power-off controls, is near you.

Attention: Another person must be there to switch off the power, if necessary.

- Use only one hand when working with powered-on electrical equipment; keep the other hand in your pocket or behind your back.

Attention: An electrical shock can occur only when there is a complete circuit. By observing the above rule, you may prevent a current from passing through your body.

- When using testers, set the controls correctly and use the approved probe leads and accessories for that tester.
- Stand on suitable rubber mats (obtained locally, if necessary) to insulate you from grounds such as metal floor strips and machine frames.
- If an electrical accident occurs:
 - Use caution; do not become a victim yourself.
 - Switch off power.
 - Send another person to get medical aid.

Safety inspection guide

The purpose of this inspection guide is to assist you in identifying potentially unsafe conditions. As each machine was designed and built, required safety items were installed to protect users and service technicians from injury. This guide addresses only those items. You should use good judgment to identify potential safety hazards due to attachment of non-Lenovo features or options not covered by this inspection guide.

If any unsafe conditions are present, you must determine how serious the apparent hazard could be and whether you can continue without first correcting the problem.

Consider these conditions and the safety hazards they present:

- Electrical hazards, especially primary power (primary voltage on the frame can cause serious or fatal electrical shock)
- Explosive hazards, such as a damaged cathode ray tube (CRT) face or a bulging capacitor
- Mechanical hazards, such as loose or missing hardware

To determine whether there are any potentially unsafe conditions, use the following checklist at the beginning of every service task. Begin the checks with the power off, and the power cord disconnected.

Checklist:

1. Check exterior covers for damage (loose, broken, or sharp edges).
2. Power off the computer. Disconnect the power cord.
3. Check the power cord for:
 - a. A third-wire ground connector is in good condition. Use a meter to measure third-wire ground continuity for 0.1 ohm or less between the external ground pin and the frame ground.
 - b. The power cord should be the authorized type specified for your computer. Go to: <http://www.lenovo.com/serviceparts-lookup>
 - c. Insulation must not be frayed or worn.
4. Check for cracked or bulging batteries.
5. Remove the cover.
6. Check for any obvious non-Lenovo alterations. Use good judgment as to the safety of any non-Lenovo alterations.
7. Check inside the unit for any obvious unsafe conditions, such as metal filings, contamination, water or other liquids, or signs of fire or smoke damage.
8. Check for worn, frayed, or pinched cables.
9. Check that the power-supply cover fasteners (screws or rivets) have not been removed or tampered with.

Handling devices that are sensitive to electrostatic discharge

Any computer part containing transistors or integrated circuits (ICs) should be considered sensitive to electrostatic discharge (ESD). ESD damage can occur when there is a difference in charge between objects. Protect against ESD damage by equalizing the charge so that the machine, the part, the work mat, and the person handling the part are all at the same charge.

Notes:

1. Use product-specific ESD procedures when they exceed the requirements noted here.
2. Ensure that the ESD protective devices you use have been certified (ISO 9000) as fully effective.

When handling ESD-sensitive parts:

- Keep the parts in protective packages until they are inserted into the product.
- Avoid contact with other people.
- Wear a grounded wrist strap against your skin to eliminate static on your body.
- Prevent the part from touching your clothing. Most clothing is insulative and retains a charge even when you are wearing a wrist strap.

- Use a grounded work mat to provide a static-free work surface. The mat is especially useful when handling ESD-sensitive devices.
- Select a grounding system, such as those listed below, to provide protection that meets the specific service requirement.

Note: The use of a grounding system to guard against ESD damage is desirable but not necessary.

- Attach the ESD ground clip to any frame ground, ground braid, or green-wire ground.
- When working on a double-insulated or battery-operated system, use an ESD common ground or reference point. You can use coax or connector-outside shells on these systems.
- Use the round ground prong of the ac plug on ac-operated computers.

Important danger warning in multiple languages

The safety notices in this section are provided in the following languages:

- English
- Arabic
- Brazilian Portuguese
- French
- German
- Hebrew
- Japanese
- Korean
- Spanish
- Traditional Chinese

English



DANGER

Before the computer is powered on after FRU replacement, make sure that all screws, springs, and other small parts are in place and are not left loose inside the computer. Verify this by shaking the computer and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.



DANGER

Some standby batteries contain a small amount of nickel and cadmium. Do not disassemble a standby battery, recharge it, throw it into fire or water, or short-circuit it. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

The battery pack contains small amounts of nickel. Do not disassemble it, throw it into fire or water, or short-circuit it. Dispose of the battery pack as required by local ordinances or regulations. Use only the battery in the appropriate parts listing when replacing the battery pack. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

The lithium battery can cause a fire, an explosion, or a severe burn. Do not recharge it, remove its polarized connector, disassemble it, heat it above 100°C (212°F), incinerate it, or expose its cell contents to water. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

If the LCD breaks and the fluid from inside the LCD gets into your eyes or on your hands, immediately wash the affected areas with water for at least 15 minutes. Seek medical care if any symptoms from the fluid are present after washing.



DANGER

To avoid shock, do not remove the plastic cover that protects the lower part of the inverter card.



DANGER

Though the main batteries have low voltage, a short-circuited or grounded battery can produce enough current to burn personnel or combustible materials.



DANGER

Unless hot swap is allowed for the FRU being replaced, do as follows before removing it: power off the computer, unplug all power cords from electrical outlets, remove the battery pack, and disconnect any interconnecting cables.

Arabic



قبل إعادة تشغيل الحاسب بعد الانتهاء من استبدال FRU، تأكد من أنه قد تم إعادة كل من المسامير و السوست وكل الأجزاء الصغيرة الأخرى في أماكنهم ولم يتم فقدهم داخل الحاسب. ويمكن التحقق من ذلك عن طريق هز الحاسب والاستماع لأي صوت صاخب يصدر منه. قد تؤدي الأجزاء أو الرقائق المعدنية إلى حدوث دائرة قصر.



تحتوي بعض البطاريات الاحتياطية على كمية صغيرة من مادتي النيكل والكادميوم. لا تقم بفك أو إعادة شحن البطارية الاحتياطية ولا تقم أيضا بالقاءها في النار أو الماء ولا تتسبب في احداث دائرة قصر بها. قم بالتخلص من البطارية كما هو موضح في القوانين المحلية. استخدم نوع البطارية المحدد والذي يوصى باستخدامه. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



تحتوي حزمة البطارية على كمية صغيرة من مادة النيكل. لا تقم بفكها أو القاءها في النار أو الماء ولا تتسبب في احداث دائرة قصر بها. تخلص من حزمة البطارية وفقا لما هو موضح في القوانين المحلية. قم، عند استبدال حزمة البطارية، باستخدام الأنواع المحددة فقط والتي يوصى باستخدامها. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



قد تتسبب بطارية الليثيوم في حدوث حريق أو انفجار أو حدوث حروق شديدة. لا تقم بإعادة شحن البطارية أو إزالة موصل الاستقطاب الخاص بها ولا تحاول أيضا فكها أو تسخينها لأكثر من ١٠٠ درجة مئوية (٢١٢ فهرنهايت) أو حرقها أو تعريض محتويات الخانة الخاصة بها للماء. قم بالتخلص من البطارية وفقا لما هو موضح في القوانين المحلية. استخدم نوع البطارية المحدد والذي يوصى باستخدامه. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



إذا ما انكسرت شاشة LCD ولامس السائل الداخلي عينيك أو يديك، قم في الحال بغسلهما بالماء لمدة لا تقل عن ١٥ دقيقة. إذا ما وجدت أي أعراض بعد الغسل اطلب عندئذ المساعدة الطبية.



لتجنب التعرض لأي صدمات، لا تقم بإزالة الغطاء البلاستيكي الذي يحمي الجزء الأسفل من بطاقة العاكس.



على الرغم من أن البطاريات الرئيسية يكون لها جهد منخفض، إلا أنه قد تقوم البطاريات التي حدث قصور بها أو التي تم توصيلها أرضيا بإصدار تيار يكفي لحدوث حروق للأفراد أو تعرض المواد القابلة للاشتعال للحريق.



ما لم يتم السماح بالتبديل الفوري لأي FRU الجاري استبداله بدون ضرورة إغلاق النظام، قم بتنفيذ ما يلي قبل إزالته. قم بإيقاف تشغيل الحاسب ونزع كل أسلاك الطاقة من المخارج الكهربائية وقم أيضا بإزالة حزمة البطارية ثم قم بفصل أي كابلات متصلة.

Brazilian Portuguese



PERIGO

Antes de ligar o computador após a substituição da FRU, certifique-se de que todos os parafusos, molas e outras peças pequenas estejam no lugar e não estejam soltos dentro do computador. Verifique isso sacudindo o computador e procurando ouvir sons de peças soltas. Peças metálicas ou lascas de metal podem causar curto-circuito.



PERIGO

Algumas baterias reserva contêm uma pequena quantidade de níquel e cádmio. Não desmonte uma bateria reserva, recarregue-a, jogue-a no fogo ou na água, ou deixe-a entrar em curto-circuito. Descarte a bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

O pacote da bateria contém uma pequena quantidade de níquel. Não o desmonte, jogue-o no fogo ou na água, ou deixe-o entrar em curto-circuito. Descarte o pacote da bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas ao substituir o pacote da bateria. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

A bateria de lítio pode causar incêndio, explosão ou graves queimaduras. Não a recarregue, remova seu conector polarizado, desmonte-a, aqueça-a acima de 100°C (212°F), incinere-a, ou exponha o conteúdo de sua célula à água. Descarte a bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

Se o LCD quebrar e o fluido de dentro dele entrar em contato com seus olhos ou com suas mãos, lave as áreas afetadas imediatamente com água durante pelo menos 15 minutos. Procure cuidados médicos se algum sintoma causado pelo fluido surgir após a lavagem.



PERIGO

Para evitar choque elétrico, não remova a capa plástica que protege a parte inferior da placa inversora.



PERIGO

Embora as principais baterias possuam baixa voltagem, uma bateria em curto-circuito ou aterrada pode produzir corrente o bastante para queimar materiais de pessoal ou inflamáveis.



PERIGO

A menos que uma hot swap seja permitida para a FRU que está sendo substituída, faça o seguinte antes de removê-la: desligue o computador, desconecte todos os cabos de energia das tomadas, remova o pacote de baterias e desconecte quaisquer cabos de interconexão.

French



DANGER

Avant de remettre l'ordinateur sous tension après remplacement d'une unité en clientèle, vérifiez que tous les ressorts, vis et autres pièces sont bien en place et bien fixées. Pour ce faire, secouez l'unité et assurez-vous qu'aucun bruit suspect ne se produit. Des pièces métalliques ou des copeaux de métal pourraient causer un court-circuit.



DANGER

Certaines batteries de secours contiennent du nickel et du cadmium. Ne les démontez pas, ne les rechargez pas, ne les exposez ni au feu ni à l'eau. Ne les mettez pas en court-circuit. Pour les mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la pile de sauvegarde ou celle de l'horloge temps réel, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. Une batterie ou une pile inappropriée risque de prendre feu ou d'exploser.



DANGER

La batterie contient du nickel. Ne la démontez pas, ne l'exposez ni au feu ni à l'eau. Ne la mettez pas en court-circuit. Pour la mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la batterie, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. En effet, une batterie inappropriée risque de prendre feu ou d'exploser.



DANGER

La pile de sauvegarde contient du lithium. Elle présente des risques d'incendie, d'explosion ou de brûlures graves. Ne la rechargez pas, ne retirez pas son connecteur polarisé et ne la démontez pas. Ne l'exposez pas à une température supérieure à 100°C, ne la faites pas brûler et n'en exposez pas le contenu à l'eau. Mettez la pile au rebut conformément à la réglementation en vigueur. Une pile inappropriée risque de prendre feu ou d'exploser.



DANGER

Si le panneau d'affichage à cristaux liquides se brise et que vous recevez dans les yeux ou sur les mains une partie du fluide, rincez-les abondamment pendant au moins quinze minutes. Consultez un médecin si des symptômes persistent après le lavage.



DANGER

Afin d'éviter tout risque de choc électrique, ne retirez pas le cache en plastique protégeant la partie inférieure de la carte d'alimentation.



DANGER

Bien que le voltage des batteries principales soit peu élevé, le court-circuit ou la mise à la masse d'une batterie peut produire suffisamment de courant pour brûler des matériaux combustibles ou causer des brûlures corporelles graves.



DANGER

Si le remplacement à chaud n'est pas autorisé pour l'unité remplaçable sur site que vous remplacez, procédez comme suit avant de retirer l'unité : mettez l'ordinateur hors tension, débranchez tous les cordons d'alimentation des prises de courant, retirez le bloc de batterie et déconnectez tous les câbles d'interconnexion.

German



VORSICHT

Bevor nach einem FRU-Austausch der Computer wieder angeschlossen wird, muß sichergestellt werden, daß keine Schrauben, Federn oder andere Kleinteile fehlen oder im Gehäuse vergessen wurden. Der Computer muß geschüttelt und auf Klappergeräusche geprüft werden. Metallteile oder-splitter können Kurzschlüsse erzeugen.



VORSICHT

Die Bereitschaftsbatterie, die sich unter dem Diskettenlaufwerk befindet, kann geringe Mengen Nickel und Cadmium enthalten. Sie darf nur durch die Verkaufsstelle oder den IBM Kundendienst ausgetauscht werden. Sie darf nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Die Batterie kann schwere Verbrennungen oder Verätzungen verursachen. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Bereitschafts-oder Systembatterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Akkus enthalten geringe Mengen von Nickel. Sie dürfen nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Die Systembatterie ist eine Lithiumbatterie. Sie kann sich entzünden, explodieren oder schwere Verbrennungen hervorrufen. Batterien dieses Typs dürfen nicht aufgeladen, zerlegt, über 100°C erhitzt oder verbrannt werden. Auch darf ihr Inhalt nicht mit Wasser in Verbindung gebracht oder der zur richtigen Polung angebrachte Verbindungsstecker entfernt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Die Leuchtstoffröhre im LCD-Bildschirm enthält Quecksilber. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Der LCD-Bildschirm besteht aus Glas und kann zerbrechen, wenn er unsachgemäß behandelt wird oder der Computer auf den Boden fällt. Wenn der Bildschirm beschädigt ist und die darin befindliche Flüssigkeit in Kontakt mit Haut und Augen gerät, sollten die betroffenen Stellen mindestens 15 Minuten mit Wasser abgespült und bei Beschwerden anschließend ein Arzt aufgesucht werden.



VORSICHT

Aus Sicherheitsgründen die Kunststoffabdeckung, die den unteren Teil der Spannungswandlerplatine umgibt, nicht entfernen.



VORSICHT

Obwohl Hauptbatterien eine niedrige Spannung haben, können sie doch bei Kurzschluß oder Erdung genug Strom abgeben, um brennbare Materialien zu entzünden oder Verletzungen bei Personen hervorzurufen.



VORSICHT

Wenn ein Austausch der FRU bei laufendem Betrieb nicht erlaubt ist, gehen Sie beim Austausch der FRU wie folgt vor: Schalten Sie den Computer aus, ziehen Sie alle Netzkabel von den Netzsteckdosen ab, entfernen Sie den Akku und ziehen Sie alle miteinander verbundenen Kabel ab.

Hebrew



סכנה

לפני הפעלת המחשב לאחר החלפת FRU יש לוודא שכל הברגים, הקפיצים, וחלקים קטנים אחרים נמצאים במקומם ואינם חופשיים לזוז בתוך המחשב. כדי לוודא זאת, יש לטלטל את המחשב ולחקשבו לגילוי קולות שקשוק. חלקי או שבבי מתכת עלולים לגרום לקצרים חשמליים.



סכנה

סוללות המתנה מסוימות מכילות כמות קטנה של ניקל וקדמיום. אין לפרק סוללת המתנה, לטעון אותה מחדש, להשליך אותה לאש או למים או לקצר אותה. יש לסלק את הסוללה כנדרש על ידי התקנות והחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימה. שימוש בסוללה לא מתאימה עלול לגרום להצתה או התפוצצות של הסוללה.



סכנה

מארז הסוללה מכיל כמות קטנה של ניקל וקדמיום. אין לפרק את מארז הסוללה, להשליך אותו לאש או למים או לקצר אותו. יש לסלק את מארז הסוללה כנדרש על ידי התקנות והחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימה בזמן התלפת מארז הסוללה. שימוש בסוללה לא מתאימה עלול לגרום להצתה או התפוצצות של הסוללה.



סכנה

סוללת הליתיום עלולה לגרום לשריפה, להתפוצצות או לכוויות קשות. אין לטעון אותה מחדש, לסלק את המחבר המקוטב שלה, לפרק אותה או לחמם אותה לטמפרטורה העולה על 100 מעלות צלזיוס. אין לשרוף את הסוללה ואין לחשוף את תוכן התא למים. יש לסלק את הסוללה כנדרש בתקנות ובחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימים. שימוש בסוללה אחרת עלול לגרום לסכנת שריפה או התפוצצות.



סכנה

אם מסך חגביש חזולי (LCD) נשבר וחוזל מתוך חמסד בא במגע עם עיניכם או ידיכם, שטפו את האזורים חגועים מיד במים במשך 15 דקות לפחות. פנו לקבלת עזרה רפואית אם תסמינים חגועים מחמג עם חוזל נמשכים לאחר חשטיפה.



סכנה

כדי למנוע התחשמלות, אין להסיר את מכסה הפלסטיק המגן על חלקו התחתון של הכרטיס ההפוך.



סכנה

אף שהסוללות הראשיות הן בעלות מתח נמוך, סוללה מקוצרת או מוארכת עלולה להפיק זרם מספיק לגרימת כוויות או להצתת חומרים דליקים.



סכנה

אלא אם כן מותרת 'החלפה חמו' של ה-FRU המוחלף, פעלו כדלחץ לפני חסרתו:
כבו את המחשב, נתקו את כל כבלי החשמל מחשקעים, הוציאו את מארז חסוללות ונתקו את כל חבבלים
המחברים.

Japanese



危険

FRUの交換後、ThinkPadの電源を入れる前に、ねじ、パネ、その他の小さな部品がすべて正しい位置にあり、またThinkPadの内部で緩んでいないことを確認してください。
これを確認するには、ThinkPadを振って、カチャカチャと音がしないか確かめます。金属部品や金属破片はショートの原因になることがあります。



危険

予備バッテリーの中には少量のニッケルとカドミウムが含まれているものがあります。したがって、予備バッテリーの分解、再充電、火または水の中への投棄、またはショートさせることは決して行わないでください。バッテリーを廃棄する場合は地方自治体の条例に従ってください。適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。



危険

バッテリー・パックには少量のニッケルが含まれています。バッテリー・パックを分解したり、火または水の中に投げ込んだり、ショートさせないでください。バッテリー・パックの廃棄にあたっては、地方自治体の条例または規則に従ってください。バッテリー・パックを交換するときは、適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。



危険

リチウム・バッテリーは、火災、爆発、または重症のやけどを引き起こすことがあります。バックアップ・バッテリーの充電、その極性コネクタの取り外し、バッテリー本体の分解、
100 °C (212 °F) 以上の加熱、焼却、電池の中身を水に浸すことはしないでください。バッテリーを廃棄する場合は地方自治体の条例に従ってください。適切なパーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発火したり、爆発したりすることがあります。



危険

LCDが破損し、LCDの中の液体が目に入ったり、手に触れたりした場合は、液体が触れた部分を少なくとも15分間洗い流してください。洗い流した後に、液体によって何らかの症状が現れた場合は、医師の治療を受けてください。



危険

感電を防ぐため、インバーター・カードの下部を保護しているプラスチック・カバーを外さないでください。



危険

メイン・バッテリーの電圧は低くても、ショートしたり、接地したバッテリーが、作業者にやけどを負わせたり、可燃物を燃やすだけの電流を発生させる場合があります。



危険

交換しようとしている FRU がホット・スワップに対応していない場合、それを取り外す前に、コンピューターの電源をオフにし、すべての電源コードをコンセントから抜き、バッテリー・パックを取り外して、相互接続しているケーブルをすべて切り離してください。

Korean



위험

FRU를 교체하고 나서 컴퓨터 전원을 켜기 전에 모든 나사, 스프링 및 기타 작은 부품들이 올바른 위치에 있는지, 컴퓨터 내부에 단단하게 연결되어 있는지 확인하십시오. 컴퓨터를 흔들어 달걀거리는 소리가 나지 않는지 확인하십시오. 금속 부품 또는 금속 조각은 누전을 일으킬 수 있습니다.



위험

일부 보조 배터리에는 소량의 니켈 및 카드뮴이 포함되어 있습니다. 보조 배터리를 분해하거나, 다시 충전하거나, 불 또는 물에 던지거나, 단락시키지 마십시오. 배터리 팩을 폐기할 때에는 해당 지역의 법률 규정을 따르십시오. 배터리 팩을 교체할 때에는 올바른 배터리만 사용하십시오. 올바르지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

배터리 팩에는 소량의 니켈이 포함되어 있습니다. 배터리 팩을 분해하거나, 불 또는 물에 던지거나, 단락시키지 마십시오. 배터리 팩을 폐기할 때에는 해당 지역의 법률 규정을 따르십시오. 배터리 팩을 교체할 때에는 올바른 배터리만 사용하십시오. 올바르지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

리튬 배터리는 화재, 폭발 또는 심각한 화상을 일으킬 수 있습니다. 리튬 배터리를 다시 충전하거나, 극성 커넥터를 제거하거나, 분해하거나, 100C(212F) 이상으로 가열하거나, 소각하거나, 전지 내용물을 물에 노출시키지 마십시오. 배터리를 폐기할 때에는 해당 지역을 법률 규정을 따르십시오. 올바른 배터리만 사용하십시오. 올바르지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

LCD가 파손되어 LCD 내부의 액체가 눈에 들어가거나 손에 묻으면 즉시 깨끗한 물로 15분 이상 닦아 내십시오. 씻은 후에 조금이라도 이상을 느끼면 즉시 병원에 가서 의사의 진찰을 받아야 합니다.



위험

전기적 위험을 방지하려면 인버터 카드의 아래 부분을 보호하는 플라스틱 덮개를 제거하지 마십시오.



위험

기본 배터리의 전압은 낮지만, 단락되거나 접지된 배터리는 화상을 입히기에 충분한 전류와 가연성 물질을 발생시킬 수 있습니다.



위험

FRU 교체 시 Hot Swap이 지원되지 않는 경우, FRU를 제거하기 전에 컴퓨터의 전원을 끄고, 전기 콘센트에서 전원 코드를 분리하고, 배터리를 제거한 후, 연결된 모든 케이블을 분리하십시오.

Spanish



PELIGRO

Antes de encender el sistema despues de sustituir una FRU, compruebe que todos los tornillos, muelles y demás piezas pequeñas se encuentran en su sitio y no se encuentran sueltas dentro del sistema. Compruébelo agitando el sistema y escuchando los posibles ruidos que provocarían. Las piezas metálicas pueden causar cortocircuitos eléctricos.



PELIGRO

Algunas baterías de reserva contienen una pequeña cantidad de níquel y cadmio. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.



PELIGRO

Las baterías contienen pequeñas cantidades de níquel. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas al sustituir la batería. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.



PELIGRO

La batería de repuesto es una batería de litio y puede provocar incendios, explosiones o quemaduras graves. No la recargue, ni quite el conector polarizado, ni la desmonte, ni caliente por encima de los 100°C (212°F), ni la incinere ni exponga el contenido de sus celdas al agua. Deséchela tal como dispone la normativa local.



PELIGRO

Si la LCD se rompe y el fluido de su interior entra en contacto con sus ojos o sus manos, lave inmediatamente las áreas afectadas con agua durante 15 minutos como mínimo. Obtenga atención medica si se presenta algún síntoma del fluido despues de lavarse.



PELIGRO

Para evitar descargas, no quite la cubierta de plástico que rodea la parte baja de la tarjeta invertida.



PELIGRO

Aunque las baterías principales tienen un voltaje bajo, una batería cortocircuitada o con contacto a tierra puede producir la corriente suficiente como para quemar material combustible o provocar quemaduras en el personal.



PELIGRO

Salvo que se permita el intercambio en caliente para la unidad sustituible localmente, realice lo siguiente antes de extraerla: apague el sistema, desconecte todos los cables de alimentación de las tomas de alimentación eléctrica, extraiga la batería y desconecte los cables de interconexión.

Traditional Chinese



危險

完成 FRU 更換之後，在開啟電腦的電源之前，請確定所有螺絲、彈簧及其他小零件都已歸位，沒有遺留在電腦內部。
若要確認這一點，請搖晃電腦，聽聽看是否有卡嗒的聲響。
金屬零件或儀錶的火花會造成電線短路。



危險

部分備用電池含有微量的鎳和鎘。請勿拆開備用電池、再充電、丟入火或水中，或使其形成短路。請按照當地法令或規定來棄置電池。
僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

電池套件含有微量的鎳。請勿拆開電池套件、丟入火或水中，或使其形成短路。請按照當地法令或規定來棄置電池套件。

更換電池套件時，僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

鋰電池會導致起火、爆炸或嚴重燒傷。請勿再充電、拔除其電極接頭、拆開、加熱超過 **100°C (212°F)**、焚燒，或讓電池組成物浸到水。請按照當地法令或規定來棄置電池。

僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

如果 LCD 破裂導致 LCD 流出的液體沾到您的眼睛或手，請立即以清水沖洗沾染部位至少 15 分鐘。如果在清洗後出現該液體所造成的任何症狀，請就醫治療。



危險

為避免電擊，請勿拆下轉換卡下面的塑膠護蓋。



危險

雖然主電池的電壓很低，但短路或接地電池所產生的電流，仍足以使人燒傷或使可燃物質起火。



危險

除非 FRU 允許以熱抽換來替換，否則請依下列方式將其移除：將電腦關機，拔除插座上所有電源線，移除電池包，並拔開任何交互連接的線材。

Chapter 2. Diagnostics and troubleshooting

This chapter introduces several diagnostics applications to help you identify and solve the problems of your computer. If you still need help after running the applications, you can call Lenovo Customer Support Center.

Diagnostics applications

The following table lists diagnostics applications available on your computer, their running environments, and brief introductions to each application.

Table 1. Diagnostics applications

Diagnostics application	Running environment	Brief introduction
"Hardware scan in Legion Space" on page 17*	Run in the operating system.	The Legion Space application is preinstalled on the computer. Hardware scan in the Legion Space application is an effective hardware testing tool to help you identify the hardware problems of your computer.
"UEFI diagnostics application" on page 18*	Run in the UEFI BIOS.	A UEFI diagnostics application is preinstalled on the computer. This application enables you to view system information and test some hardware components in your computer, especially when you cannot start up the operating system.
"Advanced diagnostics application (Windows version)" on page 18 "Advanced diagnostics application (bootable versions for Linux/UEFI)" on page 18	Run in the operating system or boot from USB (Need download).	Advanced diagnostics applications help you test a wider scope of hardware components in your computer that cannot be covered by hardware scan in the Legion Space application or the UEFI diagnostics application.

* for selected models

Important: Be extremely careful during such writing operations as copying, saving, or formatting. Drives in the computer that you are servicing sequence might have been altered. If you select an incorrect drive, data or programs might be overwritten.

Hardware scan in Legion Space

To run the hardware scan in Legion Space, do the following:

- Step 1. Launch the Legion Space app.
- Step 2. Select **Device Management** on the left side navigation bar.
- Step 3. In the **Computer Scan** section, select **Get started**.
- Step 4. To run a quick scan of all device components, select **Hardware scan → Scan**.
- Step 5. You can check the **Summary results** and find the detailed hardware problems from **Hardware Components**.

UEFI diagnostics application

UEFI Diagnostics is consistently available as a boot option on Lenovo machines. To access the tool, follow these instructions:

- For ThinkPad, Thinkbook, and SMB systems, press the **F10** key during the boot process.
- For IdeaPad systems, access the **Novo button menu**, then select **Lenovo UEFI Diagnostics** from the menu. The application will start automatically.

The following table displays the items on the main screen of the UEFI diagnostics application. Depending on the model, the items might differ slightly.

Table 2. Items on the main screen of the UEFI diagnostics application

Category	Items
Tests	• Storage • Memory • CPU • Display • Motherboard • Touch
Tools	• System Information • Bad Block Recovery • Smart Information

Prepare a USB flash drive formatted in FAT32. After the test is executed, select **View Log → Save Log**. The test log is saved in the USB flash drive. You can view the log to find possible solutions or send the log to Lenovo for helps.

Advanced diagnostics application (Windows version)

To use the advanced diagnostics application (Windows version), do the following:

- Step 1. Go to <https://support.lenovo.com/solutions/ht506581>.
- Step 2. Select a Windows package that fits your scenario for download.
- Step 3. Double-click the downloaded file and complete the installation.
- Step 4. Launch the app and follow the on-screen instructions for diagnostics.

After the test is completed, select **Export Log** to save the diagnostic result. You can view the log to find possible solutions or send the log to Lenovo for helps.

Advanced diagnostics application (bootable versions for Linux/UEFI)

To use the advanced diagnostics application (bootable versions for Linux/UEFI), do the following:

- Step 1. Prepare a USB flash drive larger than 2 GB and make a backup of the content in the USB flash drive. (During the following diagnosing process, the content in the USB flash drive content will be erased.)

Note: During the following diagnostic process, the content on the USB flash drive will be erased.
- Step 2. Go to <https://support.lenovo.com/solutions/bootableusb>.
- Step 3. Follow the on-screen instructions to create a bootable USB and run the application from the bootable USB.

After the test is executed, select **View Log → Export Log**. The test log is saved in the USB flash drive. You can view the log to find possible solutions or send the log to Lenovo for help.

Call Lenovo

If you have tried to correct the problem yourself and still need help, you can call Lenovo Customer Support Center.

Before you contact Lenovo

Record product information and problem details before you contact Lenovo.

Product information	Problem symptoms and details
• Product name • Machine type and serial number	• What is the problem? Is it continuous or intermittent? • Any error message or error code? • What operating system are you using? Which version? • Which software applications were running at the time of the problem? • Can the problem be reproduced? If so, how?

Note: The product name and serial number can usually be found on the bottom of the computer, either printed on a label or etched on the cover.

Lenovo Customer Support Center

During the warranty period, you can call Lenovo Customer Support Center for help.

Telephone numbers

For a list of the Lenovo Support phone numbers for your country or region, go to <https://pcsupport.lenovo.com/supportphonenumberlist>.

Note: Phone numbers are subject to change without notice. If the number for your country or region is not provided, contact your Lenovo reseller or Lenovo marketing representative.

Services available during the warranty period

- Problem determination - Trained personnel are available to assist you with determining if you have a hardware problem and deciding what action is necessary to fix the problem.
- Lenovo hardware repair - If the problem is determined to be caused by Lenovo hardware under warranty, trained service personnel are available to provide the applicable level of service.
- Engineering change management - Occasionally, there might be changes that are required after a product has been sold. Lenovo or your reseller, if authorized by Lenovo, will make selected Engineering Changes (ECs) that apply to your hardware available.

Services not covered

- Replacement or use of parts not manufactured for or by Lenovo or non-warranted parts
- Identification of software problem sources
- Configuration of UEFI/BIOS as part of an installation or upgrade
- Changes, modifications, or upgrades to device drivers
- Installation and maintenance of network operating systems (NOS)
- Installation and maintenance of programs

For the terms and conditions of the Lenovo Limited Warranty that apply to your Lenovo hardware product, see “Warranty information” in the *Safety and Warranty Guide* that comes with your computer.

Nonwarranted items and activities

During the warranty period, the customer may be responsible for repair costs if the computer damage was caused by misuse, accident, modification, unsuitable physical or operating environment, or improper maintenance by the customer. Following is a list of some common items that are not covered under warranty and some symptoms that might indicate that the system was subjected to stress beyond normal use.

Items not covered by warranty

- LCD panel cracked from the application of excessive force or from being dropped
- Scratched (cosmetic) parts
- Distortion, deformation, or discoloration of the cosmetic parts
- Plastic parts, latches, pins, or connectors that have been cracked or broken by excessive force
- Damage caused by liquid spilled into the system
- Damage caused by the improper insertion of a personal-computer card (PC card) or the installation of an incompatible card
- Improper disc insertion or use of an external optical drive
- Fuses blown by attachment of a non-supported device
- Forgotten computer password (making the computer unusable)
- Sticky keys caused by spilling a liquid onto the keyboard
- Use of an incorrect ac power adapter on laptop products

Symptoms that might indicate damage caused by non-warranted activities

- Missing parts might be a symptom of improper service or modification.
- Check for obvious damage to a hard disk drive. If the spindle of a hard disk drive becomes noisy, the hard disk drive might have been dropped or subject to excessive force.

Chapter 3. Parts, screws, and tools

Parts

Before proceeding with part replacement, get to know part type definition, learn to look up a part on the Lenovo Support Web site, and gain an overview of all CRUs/FRUs in this computer through the exploded view.

Part type definition

Your computer contains the following types of “Customer Replaceable Unit” (CRU)s and “Field Replaceable Unit” (FRU)s:

- **Self-service CRUs:** Refer to parts that can be replaced easily by customer themselves or by trained service technicians at an additional cost.
- **Optional-service CRUs:** Refer to parts that can be replaced by customers with a greater skill level. Trained service technicians can also provide service to replace the parts under the type of warranty designated for the customer’s product.
- **FRUs:** Refer to parts that are more complicated to replace and it is recommended that these parts should be replaced by trained service technicians. If customers elect to replace the FRU by themselves, we recommend that you ensure the correct instructions are carefully followed.

Important notes:

- **CRU statement for customers:**
 - You can resolve some problems with your product by replacing a CRU. For self-service CRUs, installation is your responsibility. For optional-service CRUs, you can either install the CRU yourself or you can request that a Service Provider install the CRU according to the warranty service for your product.
 - If you intend on installing the CRU, Lenovo will ship the CRU to you. CRU information and replacement instructions are shipped with your product and are available from Lenovo at any time upon request.
 - You can find a list of CRUs for your product in this *Hardware Maintenance Manual*. To find this manual, go to <https://support.lenovo.com> and search by product.
- **CRU/FRU statement:**
 - **Replace a CRU/FRU only with another CRU/FRU of the correct model.** When you replace a CRU/FRU, make sure that the model of the machine and the CRU/FRU part number are correct.
 - **A CRU/FRU should not be replaced because of a single unreproducible failure.** Single failures can occur for a variety of reasons that have nothing to do with a hardware defect, such as cosmic radiation, electrostatic discharge, or software errors. Consider replacing a CRU/FRU only when a problem recurs. If you suspect that a CRU/FRU is defective, clear the error log and run the test again. If the error does not recur, do not replace the CRU/FRU.
 - **Be careful not to replace a nondefective CRU/FRU.**
 - When you return a CRU/FRU, you must include the following information in the parts exchange form or parts return form that you attach to it:
 1. Name and phone number of service technician
 2. Date of service
 3. Date on which the machine failed
 4. Date of purchase
 5. Failure symptoms, error codes appearing on the display, and beep symptoms

6. Procedure index and page number in which the failing CRU/FRU was detected
7. Failing CRU/FRU name and part number
8. Machine type, model number, and serial number
9. Customer's name and address


Look up a part

1. For more detailed CRU/FRU information, including part numbers, descriptions, and substitution part numbers, go to <https://support.lenovo.com/partslookup>.
2. Type the product name, the machine type or the serial number in the corresponding field to get a general CRU/FRU list.

Exploded view and part list

By the exploded view and the part list, you can find the images, names, and types of all the CRU/FRUs of your computer.

Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:



Part list

Self-service CRUs:

- c** ac power adapter*
- d** Power cord*


FRUs:

- 1** "Upper case (with keyboard)" on page 64
- 2** "DC-in bracket" on page 45
- 3** "USB board" on page 54
- 4** "USB board cable" on page 55
- 5** "PMIC board*" on page 43
- 6** "Audio board" on page 41
- 7** "Audio board cable" on page 55
- 8** "M.2 solid-state drive" on page 33
- 9** "Wi-Fi card mylar" on page 36
- 10** "Wi-Fi card" on page 36
- 11** "Battery pack" on page 31
- 12** "Lower case" on page 29
- 13** "Speakers" on page 40
- 14** "System board" on page 55
- 15** "Memory module" on page 39
- 16** "Memory module shielding" on page 38
- 17** "Thermal module" on page 48
- a** Tape kit
- b** Screw kit

* for selected models

Legion 5 15IAX11:

Exploded view



Part list

Self-service CRUs:

- c** ac power adapter*
- d** Power cord*


FRUs:

- 1** "Upper case (with keyboard)" on page 64
- 2** "DC-in bracket" on page 46
- 3** "PMIC board*" on page 43
- 4** "Audio board" on page 41
- 5** "Audio board cable" on page 57
- 6** "M.2 solid-state drive" on page 33
- 7** "Wi-Fi card mylar" on page 36
- 8** "Wi-Fi card" on page 36
- 9** "Battery pack" on page 31
- 10** "Lower case" on page 29
- 11** "Speakers" on page 40
- 12** "System board" on page 57
- 13** "Memory module" on page 39
- 14** "Memory module shielding" on page 38
- 15** "Thermal module" on page 48
- a** Tape kit
- b** Screw kit

* for selected models

Exploded view

Part list



FRUs:


- 1 "LCD/OLED bezel" on page 65
- 2 "Strip cover" on page 66
- 3 "Microphone rubbers" on page 70
- 4 "Camera board" on page 70
- 5 "Camera bracket" on page 65
- 6 "LCD/OLED cover" on page 71
- 7 "Hinge cover" on page 61
- 8 "Stretch-release tape" on page 67
- 9 "LCD/OLED panel" on page 67

Screws

This section provides the screw list of this computer and the screw notices you need to know before hardware replacement.

Screw list

The following table includes screw specifications, torque information, and screw colors of this product.



The number after the letter L refers to the length of the screw shank measured from under the head to the tip of the screw. The number after the letter M refers to the width of the screw shank measured across the outermost points in a metric screw.

Table 3. Screw list of this product

Thread (mm)	Length (mm)	Torque (kgf.cm)	Color
M1.6	L2	1 ± 0.1	Black
M2	L3	1.85 ± 0.15	Black
M2	L4	1.85 ± 0.15	Black
M2	L4.5	1.85 ± 0.15	Black
M2	L7	1.85 ± 0.15	White
M2	L7.9	3.62	Black

Table 3. Screw list of this product (continued)

Thread (mm)	Length (mm)	Torque (kgf.cm)	Color
M2	L12	1.85 ± 0.15	Black
M2.5	L4	3 ± 0.3	Black

You can refer to the following table to choose a properly matched screwdriver.

Notes:

-  The Phillips head screw has a cross-shaped slot in the screw head.
-  The Torx head screw has a six-pointed star in the screw head.

Table 4. Choose a properly matched screwdriver

Screw head type	Thread (mm)	Screwdriver type
Phillips head	M1.6 — M2	PH0 or PH1
Phillips head	> M2	PH1
Torx head	M2	T5

Screw notices

Do the following when you service the computer:

- Carefully retain and reuse all screws.
- Keep the screw kit in your tool bag. For the part number of the screw kit, go to: <https://support.lenovo.com/partslookup>.
- Use the correct screw as shown in the CRU/FRU replacement procedures.
- Turn the screws in the direction as given by the arrow in the CRU/FRU replacement illustration.
- If you have a torque screwdriver, tighten all screws firmly to the torque specified in the screw information table for each step.
- Ensure torque screwdrivers are calibrated correctly following country specifications.


Loose screws can cause a reliability problem. In your computer, this problem is addressed with special nylon-coated screws that have the following characteristics:

- They maintain tight connections.
- They do not easily come loose, even with shock or vibration.
- They are harder to tighten.

Tighten screws as follows:


- **Plastic to plastic**

Turn an additional angle of 90 degrees after the screw head touches the surface of the plastic part.



- **Logic card to plastic**

Turn an additional angle of 180 degrees after the screw head touches the surface of the logic card.



Service tools

The following table lists all tools for servicing Lenovo products. Tools required to service a part are listed in the specific part disassembly topic. Prepare them before you service the product.




Table 5. Service tools

No.	Reference image	Tool name	Specification	Tool type
1		Screwdriver set	- PH0, PH00, PH1, PH2 - T5, T15, T20, T30 Note: Use a screwdriver with the shank length greater than 6 inches for Desktop, Workstation, and Smart device product.	Common tool
2		Pry tool	N/A	Common tool
3		Tweezers	- Conductive - Isolated	Common tool
4		Suction cup	N/A	Common tool
5		Hexagonal socket	- For VGA: H5 mm or H4.8 mm - For Tiny antenna: H8 mm	Common tool
6		Adjustable torque screwdriver	0.2 Nm to 4.0 Nm, Threadripper CPU, CAMM, etc	Common tool

Table 5. Service tools (continued)

No.	Reference image	Tool name	Specification	Tool type
7		ESD mat	N/A	Common tool
8		USB flash drive	For Golden Key, Chrome Reloads, AutoPilot, etc	Common tool
9		USB-C to USB-A converter	N/A	Common tool
10		Thermal pad	Variety of thickness, most common 0.5mm thickness pad under the component	Consumable tool
11		Thermal interface materials	N/A	Consumable tool
12		Acetate tape	N/A	Consumable tool
13		Polyimide tape	N/A	Consumable tool
14		Mylar tape	N/A	Consumable tool
15		Electrical tape	N/A	Consumable tool

Table 5. Service tools (continued)

No.	Reference image	Tool name	Specification	Tool type
16		Double-sided tape	N/A	Consumable tool
17		Conductive tape	N/A	Consumable tool
18		Eraser	N/A	Consumable tool
19		Cleaning wipes	N/A	Consumable tool
20		Touchpad jig (this might come with touchpad)	N/A	Consumable tool
21		Heat gun	N/A	Special tool
22		Brown brush	25 mm to 35 mm wide	Special tool
23		Contact cleaner spray	WD-40 Contact cleaner for battery connector	Special tool
24		Hexagonal socket	H17 mm	Special tool

Chapter 4. Hardware replacement

This chapter provides instructions on how to remove and install the hardware components of your computer.

General guidelines



Before removing any FRU or CRU, shut down the computer, unplug all power cords from electrical outlets, and wait about ten minutes to let the computer cool down.

When removing or replacing a CRU/FRU, ensure that you observe the following general guidelines:

1. Before replacing any CRU/FRU, ensure that you have read [Generic Safety and Compliance Notices](#).
2. Begin by removing any CRUs/FRUs that have to be removed before replacing the failing CRU/FRU. Any such CRUs/FRUs are listed at the beginning of each CRU/FRU replacement procedure. Remove them in the order in which they are listed.
3. Follow the correct sequence in the steps for removing a CRU/FRU, as shown in the illustrations by the numbers in square callouts.
4. When removing a CRU/FRU, move it in the direction as shown by the arrow in the illustration.

Attention:

- After replacing a CRU/FRU, do not turn on the computer until you have ensured that all screws, springs, and other small parts are in place and none are loose inside the computer. Verify this by shaking the computer gently and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.
- The system board is sensitive to and can be damaged by ESD. Before touching it, establish personal grounding by touching a ground point with one hand or by using an ESD strap (P/N 6405959).

Lower case

Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.

Step 1. Place the computer upside down on a flat surface.

Step 2. Remove 10 screws. Then, pry up the latches and remove the lower case.




Figure 1. Remove 10 screws and the lower case

Table 6. Screws used to secure the lower case

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
1	M2	4.5	1.85 ± 0.15	8
2	M2	12	1.85 ± 0.15	2

Step 3. Install the lower case in reverse order.

Label locations

When replacing the base cover, reapply all labels that come with the replacement base cover. If some original labels are not included with the replacement base cover, peel them off from the original base cover and paste them on the replacement base cover.




Figure 2. Label layout on the back side of the base cover

Labels attached to the base cover are country/region specific. Make sure to apply the appropriate labels to the replacement base cover.

Table 7. All base cover labels

Label	Label description	Applied country/region	Label dimensions
1	Rating label	All	100 mm x 30 mm
2	EAA QR label	EAA countries	17 mm x 26.1 mm
3	GML label	All	16.1 mm x 22.5 mm
4	CO2 offset label	All	18 mm x 18 mm
5	USA warning label	United States of America	120 mm x 20 mm

Battery pack

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 3. Disconnect the battery pack cable

- **Legion 5 15IAX11:**




Figure 4. Disconnect the battery pack cable

Step 2. Remove three screws and remove the battery pack.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 5. Remove three screws and the battery pack

- **Legion 5 15IAX11:**




Figure 6. Remove three screws and the battery pack

Table 8. Screws used to secure the battery pack

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4	1.85 ± 0.15	3

Step 3. Install the battery pack in reverse order.

M.2 solid-state drive

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 7. Disconnect the battery pack cable

- **Legion 5 15IAX11:**




Figure 8. Disconnect the battery pack cable

Step 2. Remove the M.2 solid-state drive.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**

Remove two screws and remove the M.2 solid-state drives by pulling them away from the slots.




Figure 9. Remove two screws and the M.2 solid-state drives

Table 9. Screws used to secure the M.2 solid-state drives

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	2

- **Legion 5 15IAX11:**

Remove one screw and remove the M.2 solid-state drive by pulling it away from the slot.




Figure 10. Remove one screw and the M.2 solid-state drive

Table 10. Screw used to secure the M.2 solid-state drive

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	1

Notes: For LCD/OLED panel with the factory color calibration feature, do the following to install new color profiles:

1. Go to <https://pcsupport.lenovo.com/us/en/downloads/DS543953> to download the installation software. Double-click the EXE file and follow the on-screen instructions to finish the installation.
2. X-RiteColorAssistant.exe will auto run. Click **Restore Profile** button from prompted window to restore the profile from Lenovo cloud.

Step 3. Install the M.2 solid-state drives in reverse order.

Wi-Fi card and Wi-Fi card mylar

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board and remove the Wi-Fi card mylar.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 11. Disconnect the battery pack cable and remove the mylar

- **Legion 5 15IAX11:**




Figure 12. Disconnect the battery pack cable and remove the mylar

Step 2. Disconnect the antennas from the Wi-Fi card, remove one screw, and remove the Wi-Fi card by pulling it away from the slot.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 13. Disconnect the antennas and remove one screw and the Wi-Fi card

- **Legion 5 15IAX11:**




Figure 14. Disconnect the antennas and remove one screw and the Wi-Fi card

Table 11. Screw used to secure the Wi-Fi card

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	1

Step 3. Install the Wi-Fi card and Wi-Fi card mylar in reverse order.

Memory module shielding

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board and remove the memory module shielding.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 15. Disconnect the battery pack cable and remove the memory module shielding

Step 2. Install the memory module shielding in reverse order.

Memory module

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Memory module shielding” on page 38

Step 1. Open the latches and remove the memory module.




Figure 16. Open the latches and remove the memory module

Step 2. Install the memory module in reverse order.

Speakers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board. Then, disconnect the speaker cables from the system board and audio board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 17. Disconnect the battery pack cable and speaker cables

Step 2. Remove four screws and remove the speakers.




Figure 18. Remove four screws and speakers

Table 12. Screws used to secure the speakers

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	2	1 ± 0.1	4

Step 3. Install the speakers in reverse order.

Audio board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board. Then, disconnect the audio board cable and the speaker cable from the audio board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 19. Disconnect the battery pack cable, the audio board cable, and the speaker cable

Step 2. Remove one screw and remove the audio board.




Figure 20. Remove one screw and the audio board

Table 13. Screw used to secure the audio board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	1

Step 3. Install the audio board in reverse order.

PMIC board (for selected models)

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board. Then, disconnect the EDP cable from the PMIC board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 21. Disconnect the battery pack cable and EDP cable

- **Legion 5 15IAX11:**




Figure 22. Disconnect the battery pack cable and EDP cable

Step 2. Remove one screw and remove the PMIC board.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 23. Remove one screw and the PMIC board

- **Legion 5 15IAX11:**




Figure 24. Remove one screw and the PMIC board

Table 14. Screw used to secure the PMIC board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	1

Step 3. Install the PMIC board in reverse order.

DC-in bracket

Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 25. Disconnect the battery pack cable

Step 2. Remove two screws and remove the DC-in bracket.




Figure 26. Remove two screws and the DC-in bracket

Table 15. Screws used to secure the DC-in bracket

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4	1.85 ± 0.15	2

Step 3. Install the DC-in bracket in reverse order.

Legion 5 15IAX11

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.

- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board and remove the DC-in bracket mylar.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 27. Disconnect the battery pack cable and remove the DC-in bracket mylar

Step 2. Remove one screw and remove the DC-in bracket.




Figure 28. Remove one screw and the DC-in bracket

Table 16. Screw used to secure the DC-in bracket

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4	1.85 ± 0.15	1

Step 3. Install the DC-in bracket in reverse order.

Thermal module

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
“Lower case” on page 29

Step 1. Disconnect the battery pack cable from the system board. Peel back the mylar.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 29. Disconnect the battery pack cable and peel back the mylar

- **Legion 5 15IAX11:**




Figure 30. Disconnect the battery pack cable and peel back the mylar

Step 2. Disconnect the fan cables and the EDP cable from the system board. Then, disconnect the EDP cable from the PMIC board. Remove the antennas from the cable guide.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**




Figure 31. Disconnect the fan cables and EDP cable, and remove the antennas

- **Legion 5 15IAX11:**




Figure 32. Disconnect the fan cables and EDP cable, and remove the antennas

Step 3. Remove the thermal module.

- **Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11:**

Remove two screws, loosen eight screws in alphabetical order, and remove the thermal module.




Figure 33. Remove two screws, loosen eight screws, and remove the thermal module

Table 17. Screws used to secure the thermal module

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
6	M2	4	1.85 ± 0.15	2
7	M2	7.9	3.62	8

- **Legion 5 15IAX11:**

Remove four screws, loosen eight screws in alphabetical order, and remove the thermal module.




Figure 34. Remove four screws, loosen eight screws, and remove the thermal module

Table 18. Screws used to secure the thermal module

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
6	M2	4	1.85 ± 0.15	4
7	M2	7.9	3.62	8

Step 4. Install the thermal module in reverse order.

Handling thermal interface materials

Thermal interface materials are typically applied between a heat sink and a CPU (and/or GPU) die to enhance the heat transfer capability of the heat sink. If thermal interface materials are exposed during computer servicing, such as when replacing the heat sink or system board, it is important to handle the thermal interface materials properly.

- You need to completely remove the old thermal interface materials from the CPU and/or GPU die.
- You need to apply new thermal interface materials onto the heat sink according to the type, quantity, and application areas specified in this publication.

Related tasks

“Thermal module” on page 48

“System board, USB board cable (for selected models), and audio board cable” on page 55

Type, quantity, and areas of thermal interface materials application on the thermal module

The table and figure below provide information on the type and quantity of thermal interface materials, as well as the specific areas on the thermal module where these materials should be applied.

Model	Area	Type	Quantity
Legion 5 15AGP11 and Legion 5 15AHP11	a	PTM-7958-SP	0.12 g, 13.32 mm × 15.7 mm × 0.25 mm
	b		0.13 g, 12.49 mm × 19.09 mm × 0.25 mm
Legion 5 15IPH11	a		0.12 g, 13.32 mm × 15.7 mm × 0.25 mm
	b		0.17 g, 22.5 mm × 13.58 mm × 0.25 mm
Legion 5 15IAX11	a	PTM-7958/PTM-7958-SP	0.15 g, 15.7 mm × 13.32 mm × 0.25 mm
	b		0.27 g, 27.8 mm × 13.74 mm × 0.25 mm

- **Legion 5 15AGP11 and Legion 5 15AHP11:**




Figure 35. Areas on the thermal module where thermal interface materials should be applied

- **Legion 5 15IPH11:**




Figure 36. Areas on the thermal module where thermal interface materials should be applied

- **Legion 5 15IAX11:**




Figure 37. Areas on the thermal module where thermal interface materials should be applied

Areas on the system board where thermal interface materials are applied

The following figure shows the areas on the system board where thermal interface materials are applied.

- **Legion 5 15AGP11 and Legion 5 15AHP11:**




Figure 38. Areas on the system board where thermal interface materials are applied

- **Legion 5 15IPH11:**




Figure 39. Areas on the system board where thermal interface materials are applied

- **Legion 5 15IAX11:**




Figure 40. Areas on the system board where thermal interface materials are applied

USB board (for selected models)

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Thermal module” on page 48

Step 1. Disconnect the USB board cable from the USB board, remove one screw, and remove the USB board.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 41. Disconnect the USB board cable and remove one screw and the USB board

Table 19. Screw used to secure the USB board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3	1.85 ± 0.15	1

Step 2. Install the USB board in reverse order.

System board, USB board cable (for selected models), and audio board cable

Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Battery pack” on page 31
 - “M.2 solid-state drive” on page 33
 - “Wi-Fi card and Wi-Fi card mylar” on page 36
 - “Memory module shielding” on page 38
 - “Memory module” on page 39
 - “DC-in bracket (for Legion 5 15AGP11, Legion 5 15AHP11, and Legion 5 15IPH11)” on page 45
 - “Thermal module” on page 48

Step 1. Peel off the mylar from the system board.




Figure 42. Peel off the mylar

Step 2. Disconnect the USB board cable from the USB board and the audio board cable from the audio board. Then, disconnect the keyboard backlight cable, touchpad cable, keyboard cable, speaker cable, and camera cable from the system board.




Figure 43. Disconnect the USB board cable, audio board cable, keyboard backlight cable, touchpad cable, keyboard cable, speaker cable, and camera cable

Step 3. Remove eight screws and remove the system board.




Figure 44. Remove eight screws and the system board

Table 20. Screws used to secure the system board

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
4	M2	4	1.85 ± 0.15	3
5	M2	7	1.85 ± 0.15	1
6	M2	3	1.85 ± 0.15	4

- Step 4. Disconnect the USB board cable and audio board cable from the system board and remove the USB board cable and audio board cable.




Figure 45. Disconnect and remove the USB board cable and audio board cable

- Step 5. Install the USB board cable, audio board cable, and system board in reverse order.

Legion 5 15IAX11

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

- “Lower case” on page 29
- “Battery pack” on page 31
- “M.2 solid-state drive” on page 33
- “Wi-Fi card and Wi-Fi card mylar” on page 36
- “Memory module shielding” on page 38
- “Memory module” on page 39
- “DC-in bracket (for Legion 5 15IAX11)” on page 46
- “Thermal module” on page 48

Step 1. Peel off the mylar from the system board.




Figure 46. Peel off the mylar

Step 2. Disconnect the audio board cable from the audio board. Then, disconnect the keyboard backlight cable, touchpad cable, keyboard cable, speaker cable, and camera cable from the system board.




Figure 47. Disconnect the audio board cable, keyboard backlight cable, touchpad cable, keyboard cable, speaker cable, and camera cable

Step 3. Remove 13 screws and remove the system board.




Figure 48. Remove 13 screws and the system board

Table 21. Screws used to secure the system board

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
4	M2	4	1.85 ± 0.15	3
5	M2	7	1.85 ± 0.15	1
6	M2	3	1.85 ± 0.15	9

Step 4. Disconnect the audio board cable from the system board and remove the audio board cable.




Figure 49. Disconnect and remove the audio board cable

Step 5. Install the audio board cable and system board in reverse order.

Write key product information to a replacement system board

Some key product information and settings are stored in the ROMs of the PC's system board. The information and settings are essential for using and servicing a Lenovo PC. After replacing a system board for a Lenovo PC, you need to use a Lenovo-provided software tool to write key information—including machine type model (MTM), serial number (SN), and product name—as well as settings such as keyboard language to the replacement system board.

For service technicians, go to <https://support.lenovo.com/us/en/solutions/ht102004> for detailed instructions on how to create and use a Golden Key U1 tool or a normal BIOS tool.

For users, follow the following steps:

Attention: Take extra caution when entering the MTM and SN and when selecting the product name and keyboard language. Carefully verify these details before committing the writing action. Once recorded on the system board, they cannot be altered. Consult Lenovo service if you are uncertain about the MTM, SN, and product name for your PC.

- Step 1. Connect the ac power adapter and turn on the computer.
- Step 2. Download the tool package and double-click the WinMBDWizard.exe file to run the tool. To download the tool, go to <https://support.lenovo.com/solutions/HT516532>.
- Step 3. Follow the on-screen instructions to input the MTM and SN, select the product name and keyboard language of the computer.

- Step 4. Click **Start Update** to update the product information.
- Step 5. Click **Yes** in the confirmation window to continue the update.
- Step 6. Click **Finish** to close the tool.
- Step 7. Click **Yes** in the confirmation window to restart the computer and apply the configuration on the system board.

Note: Do not turn off the computer or disconnect the computer from ac power during the whole process.

Hinge cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Battery pack” on page 31
 - “M.2 solid-state drive” on page 33
 - “Wi-Fi card and Wi-Fi card mylar” on page 36
 - “Memory module shielding” on page 38
 - “Memory module” on page 39
 - “DC-in bracket” on page 45
 - “Thermal module” on page 48
 - “System board, USB board cable (for selected models), and audio board cable” on page 55

- Step 1. Remove four screws.




Figure 50. Remove four screws

Table 22. Screws used to secure the hinge cover

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4	1.85 ± 0.15	4

Step 2. Remove the hinge cover.




Figure 51. Remove the hinge cover

Step 3. Install the hinge cover in reverse order.

LCD/OLED module

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Battery pack” on page 31
 - “M.2 solid-state drive” on page 33
 - “Wi-Fi card and Wi-Fi card mylar” on page 36
 - “Memory module shielding” on page 38
 - “Memory module” on page 39
 - “DC-in bracket” on page 45
 - “Thermal module” on page 48
 - “System board, USB board cable (for selected models), and audio board cable” on page 55
 - “Hinge cover” on page 61

Step 1. Remove six screws and lift the camera cable.




Figure 52. Remove six screws and lift the camera cable

Table 23. Screws used to secure the LCD/OLED module

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2.5	4	3 ± 0.3	6

Step 2. Remove the LCD/OLED module.




Figure 53. Remove the LCD/OLED module

Table 24. Screws used to secure the LCD/OLED module

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2.5	4	3 ± 0.3	2

Notes: For LCD/OLED panel with the factory color calibration feature, do the following to install new color profiles:

1. Connect your computer to the network and close the X-Rite Color Assistant program.
2. Go to <https://pcsupport.lenovo.com/us/en/downloads/DS543953> to download the installation software. Double-click the EXE file and follow the on-screen instructions to finish the installation.
3. Go to C:\Program files (x86)\X-Rite Color Assistant and locate the ProfileUpdaterForDisplayReplacement.exe file. Double-click the EXE file. Follow the on-screen instructions to input the display serial number and click Submit. You can find the display serial number and instructions on a sticker fixed to the front of the new LCD/OLED part. When the new color profiles are installed successfully, a prompted window will be displayed.

Step 3. Install the LCD/OLED module in reverse order.

LCD Self Test

When you turn on the computer and the LCD goes black, run LCD Self Test to help you determine whether the LCD functions normally.

To run LCD Self Test:

Ensure that the computer is connected to ac power. Then, press the power button for about seven seconds to turn off the computer.

Press Fn, left Ctrl, and the power button at the same time. If the computer displays five solid colors in sequence across the entire screen, it indicates that the LCD functions normally.

The test lasts for about 20 seconds and then exits automatically. You also can press the power button to exit the test.

Upper case (with keyboard)

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “Battery pack” on page 31
 - “M.2 solid-state drive” on page 33
 - “Wi-Fi card and Wi-Fi card mylar” on page 36
 - “Memory module shielding” on page 38
 - “Memory module” on page 39
 - “Speakers” on page 40
 - “Audio board” on page 41
 - “PMIC board (for selected models)” on page 43
 - “DC-in bracket” on page 45
 - “Thermal module” on page 48
 - “USB board (for selected models)” on page 54
 - “System board, USB board cable (for selected models), and audio board cable” on page 55
 - “USB board cable” on page 55

“Audio board cable” on page 55

“Hinge cover” on page 61

“LCD/OLED module” on page 62

Disassemble the LCD/OLED module

Before disassembling the LCD/OLED module, make sure it has been detached from the upper case assembly.

LCD/OLED bezel

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

“LCD/OLED module” on page 62

Step 1. Remove the LCD/OLED bezel.




Figure 54. Remove the LCD/OLED bezel

Step 2. Install the LCD/OLED bezel in reverse order.

Camera bracket

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 29

“LCD/OLED module” on page 62

“LCD/OLED bezel” on page 65

Step 1. Remove two screws and remove the camera bracket.




Figure 55. Remove two screws and the camera bracket

Table 25. Screws used to secure the camera bracket

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	2	1 ± 0.1	2

Step 2. Install the camera bracket in reverse order.

Strip cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “LCD/OLED module” on page 62
 - “LCD/OLED bezel” on page 65

Step 1. Remove the strip cover.




Figure 56. Remove the strip cover

Step 2. Install the strip cover in reverse order.

LCD/OLED panel

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “LCD/OLED module” on page 62
 - “LCD/OLED bezel” on page 65
 - “Strip cover” on page 66
- Tools needed: Tweezers

Step 1. Use a pair of tweezers to take out the tabs of three pieces of stretch-release tape. Pull the tabs for the three pieces of stretch-release tape downward to detach them. Then, carefully lift the LCD/OLED panel by its top edge to turn it over.

Attention: Stretch-release tapes lose their adhesive properties when stretched. To effectively detach a stretch-release tape, it is essential to follow a pull-shift-pull pattern. Begin by gripping the tab and pulling the tape downward approximately three to four centimeters. Next, shift your hand to grip the tape as high as possible, and pull again for another three to four centimeters. Continue this pattern until the tape is completely removed.

The LCD/OLED panel is secured to the cover using three pieces of stretch-release tape: two are positioned on the sides and one at the top. The graphic below illustrates the locations of these three pieces of stretch-release tape beneath the screen.




Figure 57. Detach three pieces of stretch-release tape and turn over the LCD/OLED panel

Step 2. Peel back the mylar, disconnect the EDP cable, and remove the LCD/OLED panel.




Figure 58. Disconnect the EDP cable and remove the LCD/OLED panel

Step 3. Install the LCD/OLED panel in reverse order.

Installing the OLED panel

Aligning the OLED panel precisely with the back cover is critical for a successful OLED panel replacement. This alignment is typically achieved on the production line using CCD equipment. In a service context, you can use a set of positioning rubber pads to achieve satisfactory alignment precision.

Note: The set of rubber pads for alignment is available as a Field Replaceable Unit (FRU). You should obtain the rubber pads FRU and the stretch release tapes FRU, along with the OLED panel FRU, prior to replacing the OLED panel.

- Step 1. Peel off the release liner from one side of the stretch release tapes and adhere them to the specified locations as illustrated.



Figure 59. The locations where the stretch release tapes should be attached

- Step 2. Insert six rubber pads into the designated locations as illustrated.




Figure 60. The locations where the rubber pads should be inserted

- Step 3. Peel off a section of the liner that is approximately 6 centimeters long and fold it outwards so that the end of the liner extends beyond the edge of the back cover.
- Step 4. Repeat the operation for the other stretch release tape.
- Step 5. Hold the replacement panel with both hands above the back cover, tilt it slightly downward, and gradually move it toward the upper, right, and left edges of the back cover until the upper, right, and left sides of the panel make firm contact with the six alignment rubber pads.
- Step 6. With the upper edge resting against the two upper rubber pads and using it as pivot points, gradually lower the panel on the back cover.
- Step 7. Pull the liners of the tapes downward to detach them.
- Step 8. Gently slide your fingers over the panel where the stretch release tapes are attached underneath to ensure the panel is securely fastened to the tapes.

Camera board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “LCD/OLED module” on page 62
 - “LCD/OLED bezel” on page 65
 - “Camera bracket” on page 65
 - “Strip cover” on page 66
 - “LCD/OLED panel” on page 67

Step 1. Disconnect the camera cable from the camera board and remove the camera board.




Figure 61. Disconnect the camera cable and remove the camera board

Step 2. Install the camera board in reverse order.

Microphone rubbers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “LCD/OLED module” on page 62
 - “LCD/OLED bezel” on page 65
 - “Camera bracket” on page 65
 - “Strip cover” on page 66
 - “LCD/OLED panel” on page 67
 - “Camera board” on page 70

Step 1. Remove the microphone rubbers.



Figure 62. Remove the microphone rubbers

Step 2. Install the microphone rubbers in reverse order.

LCD/OLED cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 29.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 29
 - “LCD/OLED module” on page 62
 - “LCD/OLED bezel” on page 65
 - “Camera bracket” on page 65
 - “Strip cover” on page 66
 - “LCD/OLED panel” on page 67
 - “Camera board” on page 70

Appendix A. Important notice for Quebec consumers

In regard to section 79.18 of Quebec's Regulation respecting the application of the Consumer Protection Act, Lenovo in no way guarantees the availability of (a) replacement parts; (b) repair services; and (c) information necessary to maintain or repair the goods. For up-to-date information on the technical support and parts available for your purchase, please consult <https://support.lenovo.com/ca/en>.

En ce qui concerne l'article 79.18 du Règlement d'application de la Loi sur la protection du consommateur du Québec, Lenovo ne garantit en aucune façon la disponibilité des éléments suivants : (a) les pièces de rechange ; (b) les services de réparation ; et (c) les renseignements nécessaires à l'entretien à la réparation du bien. Pour obtenir des renseignements à jour sur le soutien technique et les pièces disponibles pour votre achat, veuillez consulter <https://support.lenovo.com/ca/fr>.

Appendix B. Self-help resources

Use the following self-help resources to learn more about the computer and troubleshoot problems.

Resources	How to access?
Troubleshooting and frequently asked questions	• https://www.lenovo.com/tips • https://forums.lenovo.com
Accessibility information	https://www.lenovo.com/accessibility
Reset or restore Windows	• Use Lenovo recovery options. 1. Go to https://support.lenovo.com/HowToCreateLenovoRecovery. 2. Follow the on-screen instructions. • Use Windows recovery options. 1. Go to https://pcsupport.lenovo.com. 2. Detect your computer or manually select your computer model. 3. Click Troubleshoot & Diagnose → Custom Troubleshooting → Operating System Diagnostics and then follow the on-screen instructions.
Use Legion Space or Lenovo PC Manager to: • Download and install the latest drivers and firmware. • Configure hardware settings. • Diagnose computer hardware problems.	Use Windows Search.
Product documentation: • Generic Safety and Compliance Notices • <i>Safety and Warranty Guide</i> • <i>Setup Guide</i> • <i>User Guide</i> • <i>This Hardware Maintenance Manual</i> • <i>Regulatory Notice</i>	Go to Lenovo Documentation Center and search by product.
Lenovo Support Web site with the latest support information on the following: • Drivers and software • Diagnostic solutions • Product and service warranty • Product and parts details • Knowledge base and frequently asked questions	Visit https://support.lenovo.com .
Windows help information	• Use Get Help or Tips. • Use Windows Search. • Microsoft Support Web site: https://support.microsoft.com

Trademarks

LENOVO and the LENOVO logo are trademarks of Lenovo.

All other trademarks are the property of their respective owners. © 2026 Lenovo.

Lenovo