KVR1333D3N8/1G

1GB 128M x 64-Bit PC3-10600
CL8 240-Pin DIMM

Preliminary

DESCRIPTION:

This document describes ValueRAM's 128M x 64-bit 1GB (1024MB) DDR3-1333 CL8 SDRAM (Synchronous DRAM) memory module, based on sixteen 64M x 8-bit DDR3-1333 FBGA components. The SPD is programmed to JEDEC standard latency 1333Mhz timing of 8-8-8 at 1.5V. This 240-pin DIMM uses gold contact fingers and requires +1.5V. The electrical and mechanical specifications are as follows:

FEATURES:

- ☑ JEDEC standard 1.5V ± 0.075V Power Supply
- ☑ VDDQ = 1.5V ± 0.075V
- ☑ 667MHz fCK for 1333Mb/sec/pin
- ☑ 8 independent internal bank
- ☑ Programmable CAS Latency: 5,6,7,8,9,10
- ☑ Posted CAS
- ☑ Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- ☑ Programmable CAS Write Latency(CWL) = 8(DDR3-1333)
- ☑ 8-bit pre-fetch
- ☑ Burst Length: 8 (Interleave without any limit, sequential with starting address “000” only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- ☑ Bi-directional Differential Data Strobe
- ☑ Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm ± 1%)
- ☑ On Die Termination using ODT pin
- ☑ Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- ☑ Asynchronous Reset
- ☑ 1066Mbps CL7 doesn’t have backward compatibility with 800Mbps CL5
- ☑ PCB : Height 1.180” (30.00mm), double sided component

PERFORMANCE:

☑ CL(IDD)	8 cycles
☑ Row Cycle Time (tRCmin)	48ns (min.)
☑ Refresh to Active/Refresh Command Time (tRFCmin)	90ns
☑ Row Active Time (tRASmin)	36ns (min.)
☑ Power	TBD W (operating)
☑ UL Rating	94 V - 0
☑ Operating Temperature	0° C to 85° C
☑ Storage Temperature	-55° C to +100° C

MODULE DIMENSIONS:



