



2-Port Cat6 10G Shielded RJ45 Wall Plate

Flush Mount with Faceplate, STP, Signal White RAL9003

SKU: 771900 | EAN-13: 0766623771900 | UPC: 766623771900

Cat6 Wall Plate - Flush-mount with 2 ports and faceplate for in-wall wiring projects

The 2-Port Cat6 10G Shielded RJ45 Wall Plate from Intellinet Network Solutions is the flush-mount outlet you need for your next network-wiring installation. Its clean faceplate provides cover for the 40°-angled outlet jacks that help keep cables close to the wall for a more professional look. This Wall Plate's Cat6 ports support 10G data transmissions with frequencies up to 250 MHz and all PoE applications up to PoE++. For an optional surface mount, use the patch box #771894.

Features:

- Cat6 STP 360° shielded RJ45 wall plate for 10G, HDBaseT and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Two 40° angled outlet jacks
- Mounts flush against the wall
- Gold-plated contacts for corrosion-free connections
- Supports solid wire with AWG 26/1 to 22/1
- Compliant with ISO/IEC 11801, DIN EN 50173-1, and ANSI/TIA-568
- European 80 x 80 mm faceplate design
- Adjustable strain relief
- Standard 8P8C design, compatible with all network RJ45 connections
- Integrated writable label
- LSA punch-down type, compatible with 110, Krone, and other punch-down tools
- Fits round cable
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- ISO/IEC 11801
- DIN EN 50173-1

General

- Supports transfer speeds up to 10 Gbps
- Max. operating frequency: 250 MHz
- Supports all PoE standards up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Mating cycles: ≥750

Material

- Contacts: phosphor bronze, zinc-plated
- Contact plating: 3 micro-inch gold
- IDC: phosphor bronze

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Shielding: zinc alloy
- Housing: ABS plastic

Electrical

- Insulation resistance: ≤ 250 MOhm
- Dielectric withstanding voltage: 1,000 V DC/700 V AC, 60 Hz for 1 minute
- Contact resistance: 20 MOhm

Physical

- Dimensions (L x W x H): 80 x 80 x 31 mm (3.15 x 3.15 x 1.22 in.)
- Net weight: 150 g (5.29 oz.)
- Gross weight: 160 g (5.64 oz.)

Environmental

- Operating temperature: -10 - 60°C (14 - 140°F)
- Storage temperature: -40 - 70°C (-40 - 158°F)
- Operating humidity (non-condensing): 10 - 90% RH

Package Contents

- 2-Port Cat6 10G Shielded RJ45 Wall Plate
- Two screws for surface mount trunking; suitable for #771894 Surface Mount Patch Box

Also available for this product:

- #771917 - Cat6a version
- #771894 - Surface Mount Patch Box



