



ESUB-8F/WS

Order No.: 0259300

PRODUCTINFOS

Active subwoofer system, 50 W

- Compact active subwoofer of elegant design as an addition to compact speakers for hi-fi, PA, home cinema and home recording
- Beside volume control, a phase switch and an automatic switch-on, the amplifier also features an adjustable crossover frequency (50-250 Hz)
- High-quality bass-reflex MDF cabinet, high-gloss white
- 20 cm (8") bass speaker
- Inputs via 1 x RCA L/R or screw terminals for high-level L/R
- Parallel line out RCA L/R
- Additional outputs high-level L/R for mid-high range speakers. Thus, well suited for connection to already existing speaker lines
- White fabric front cover

TECHNICAL SPECIFICATIONS

ESUB-8F/WS

Active/passive

active

ESUB-8F/WS

Total output power	90 W
Power rating (RMS)	50 W
Frequency range	30-250 Hz
Input signal	185 mV/9 k Ω (RCA L/R) 4 V/480 Ω (high IN)
Bass speaker	20 cm (8") bass speaker
Number of speakers	1
Speaker size	20 cm (8")
SPL	87 dB/W/m
Max. rated SPL	105 dB
Housing material	wood
Colour	white, high-gloss
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/152 VA
Dimensions	300 x 330 x 340 mm
Width	300 mm
Height	330 mm
Depth	340 mm
Weight	9.8 kg
Inputs	1 x RCA (L/R), unbal., IN 1 x screw terminals (stereo), high-level IN
Outputs	1 x RCA (L/R) 1 x screw terminals (stereo), high-level OUT
Packing dimensions (W x H x L)	0.41 x 0.435 x 0.41 m
Gross weight	12.52 kg
Net weight	10.31 kg