



PA-806DAP

Order No.: 1000234

PRODUCTINFOS

Mono class D PA mixing amplifier,

with integrated MP3 player, FM/DAB+ tuner and Bluetooth.

- 1 x 60 W
- Class D concept with high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- Bluetooth version 4.2
- MP3 player with USB/SD interface, FM/DAB+ radio, LED display, infrared remote control
- Reception of interference-free 'digital radio' (DAB+)
- 1 balanced XLR microphone input with 48 V phantom power and priority selection for announcements
- 2 unbalanced inputs, switchable mic/line
- 2 unbalanced line inputs
- 1 TEL input
- 1 Music-On-Hold output (MOH)
- Speaker outputs via screw contacts
- Mute function via screw contact
- 2 line outputs
- Input level control and output level control
- 2-way tone control for the output
- LEDs for indicating operation, clipping, protect and signal level

TECHNICAL SPECIFICATIONS

PA-806DAP

Power rating	60 W
Channels	1
Zones	1
Inputs	4.5 mV/600 Ω (channel 1), 4.5 mV/120 mV (channels 2-3), 60 mV (channels 4-5) 90 mV (tel.)
Frequency range	60-15,000 Hz
Equalizer bass	yes
Equalizer treble	yes
S/N ratio	72 dB (mic, channels 1-3) 85 dB (line, channels 2-5)
THD	< 0.5%
Phantom power	48 V
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	160 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	4.2 A
Admiss. ambient temp.	0-40 °C
Width	320 mm
Height	95 mm
Depth	245 mm
Weight	4.1 kg
Connections	1 x XLR (channel 1), 2 x 6.3 mm jack (channels 2-3), 2 x RCA L/R (channels 4-5), 2 x RCA (record out), 1 x F jack (FM/DAB+), screw contacts (tel. input), screw contacts (MOH), screw contacts (DC 24 V), screw contacts (mute), screw contacts (speakers)
Packing dimensions (W x H x L)	0.39 x 0.16 x 0.31 m
Gross weight	4.86 kg
Net weight	4.09 kg

