





|                                           |                                  |
|-------------------------------------------|----------------------------------|
| Description                               | RCCB WITH OVERCURRENT PROTECTION |
| Code                                      | MDC 60                           |
| No. of poles                              | 1P+N                             |
| No. modules                               | 2                                |
| Rated current                             | 6 A                              |
| Rated residual operating current          | 300 mA                           |
| Type                                      | A                                |
| Curve                                     | B                                |
| Rated voltage (EN/IEC 61009-1, 61009-2-1) | 230/240 V                        |

|                                         |                                   |                                    |                                   |
|-----------------------------------------|-----------------------------------|------------------------------------|-----------------------------------|
| Standard                                | IEC/EN 61009-1, IEC/EN 61009-2-1  | Rated frequency (Hz)               | 50/60 Hz                          |
| Breaking capacity EN 61009-1 230V (Icn) | 6000 A                            | Breaking capacity EN 61009-1 (Ics) | 1 x Icn                           |
| Breaking capacity EN 60947-2 230V (Icu) | 7.5 kA                            | Breaking capacity EN 60947-2 (Ics) | 100% Icu                          |
| Insulation voltage                      | 500 V                             | Level of immunity (8/20 μs)        | 250 A                             |
| Rated impulse withstand voltage         | 4 kV                              | Overvoltage category               | III                               |
| Electrical endurance                    | 10.000                            | Mechanical endurance               | 20.000                            |
| Section rigid cable                     | <=1x35 - <=2x16 - <=1x16+2x10 mm² | Section flexible cable             | <=1x35 - <=2x16 - <=1x16+2x10 mm² |
| Double connection                       | YES (only down stream)            | Rated tightening torque            | 2 Nm                              |
| Operating temperature                   | -25 +40 °C                        | Stocking temperature               | -40 +70 °C                        |
| Auxiliaries compatibility               | Yes                               | ReStart compatibility              | Yes                               |
| Assembly position                       | Any                               |                                    |                                   |

#### DIMENSIONAL



#### WIRING DIAGRAM



#### STANDARDS/APPROVALS

