

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class H

VCE 44 H AC-Kit

Order number 446.025



Technical attributes

Power input P. max.	1400 watt
Max. volume flow	4500 l/min
Max. vacuum	25000 Pa
Filter surface	5000 cm ²
Container volume	42 l
Liquid capacity	26 l
Power take off	100-2400 watt
Size (W x L x H)	565 x 385 x 650 mm
Cable length	7,5 m
Weight	17,6 kg

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class H

- + Adapter plate that can be installed without using tools, for fixing L-BOXXes and Tanos systainers on the head of the vacuum cleaner
- + The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- + Continuous automatic flat filter cleaning ensures no loss of suction
- + The flat-fold filter with Teflon coating / nanocoating allows optimum use of the tank volume
- + With permanent socket and electronic automatic on/off switch
- + Flow sensor technology monitors the flow rate and emits a visual and audible signal to indicate any drop below the statutory minimum value of $\leq 20\text{m/s}$
- + Visual and audible signal for monitoring the HEPA filter
- + The flow rate control via the rotary switch minimises possible vacuums on the surface during intermediate and finish sanding
- + Suction diameter selector switch for adjusting the optimum flow rate
- + Suitable for wet vacuuming: with electronic liquid level control
- + Soft start stops any voltage peaks at the start and the run-on feature (15 sec. overrun) empties any remaining dust in the vacuum hose
- + Double-walled sturdy container with integrated grip recess for emptying the container easily
- + Dust-protected antistatic finish prevents electric charging of the suction hose
- + Equipped with large wheels and two swivel guide rollers made of metal
- + Separate motor air cooling duct with coarse dirt filter. Protects the turbine against the ingress of ambient air and thereby extends the service life. (Fine dust filter PES available as an accessory)
- + Simple filter change without removing the suction head
- + With hose retainer and expander for easy, quick securing of the power cable
- + With 4 clamping loops (2 on each side) for attaching straps and a giraffe holder
- + Safety vacuum cleaner class H: suitable for all dusts with OEL values $< 0.1\text{ mg/m}^3$ with additional audit "asbestos" by TRGS 519
- + Suitable for dry, non-flammable dusts that are harmful to the health and carcinogenic substances incl. asbestos
- + Ideal to remove mould, restore roofs and walls insulated with mineral wool. Sanding dust

Standard equipment

Antistatic suction hose Ø 32 mm x 4 m with clip connection including auxiliary air control and suction adapter SAD-C D25-32AS	406.708
1 L-BOXX® holder	445.169
1 flat-fold filter PES L/M/H	445.118
1 flat folded filter class H/HEPA 14	445.126
1 safety filter bag	445.096
1 adapter Ø 25-32 mm, anti-static	445.029
Hose clip	2 pieces
1 cleaning set	445.053

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

from wooden surfaces that have been impregnated with hazardous wood preservatives and from painted surfaces with paint that contains substances such as lead, nickel, cadmium, chromium, zinc chromate, etc.