

DIGITUS 8 Port Fast Ethernet Network Switch, Industrial, Unmanaged, 1 SFP Uplink

DN-651133

EAN 4016032485469



Industrial 8+1 Port Fast Ethernet PoE Switch Unmanaged, 8 RJ45 Ports 10/100 Mbps

DN-651133 is a industrial PoE Ethernet switch with 8-Port 10/100Mbps RJ45 +1 Port 100Mbps base-FX. The industrial graded switch has the operating temperature of $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$, has the super firmness can adapt to all kinds of harsh environment, can also be conveniently placed in the compact space of the control box. The installation characteristics of the guide rail, wide temperature operation, IP40 protection class housing and LED indicator light make the DN-651133 a plug and play industrial grade device, providing a reliable and convenient solution for users to network their Ethernet devices.

DN-651133 is a industrial graded 9-port Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment.

- 8-port 10/100Base-Tx RJ45 with autonegotiation and auto-MDI/MDI-X function
- 1-port 100Base-Fx interface SFP
- 48V to 57V DC, redundant power input
- Enclosure: IP40 aluminum housing
- Supports 6KV DC Ethernet ESD protection
- Supports 6KV DC EFT protection for power line
- Free Fall, Shock and Vibration Stability
- DIN-rail Installation
- Performance Specification: Bandwidth: 1.8Gbps, Packet Buffer Memory: 1,25Mbit, Packet Forwarding Rate: 1.4Mpps, MAC Address Table: 2K
- Flow Control: Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
- LED Indicator: Power: Red, Fiber: Link 2(Green), Ethernet: Yellow

- Power Input: 48 to 57V DC redundant power
- Power Consumption: <8 watts
- Network Protocols: IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u; 100Base-TX/FX;
- Network cables: 10BASE-T: Cat3,4,5 UTP(≤ 100 meter), 100BASE-TX: Cat5 or later UTP(≤ 100 meter)
- Industry Standard: FCC CFR47 Part 15, EN55022/CISPR22, Class A, IEC61000-4-2 (ESD): $\pm 8\text{kV}$ (contact), $\pm 12\text{kV}$ (air), IEC61000-4-3 (RS): 10V/m (80~1000MHz),
- Dimensions (W x D x H): 142.5 x 107.1 x 53.5 mm
- Weight: Product Weight: 0.70KG
- Working Environment: working temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$; Storage temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
- Relative Humidity: 5%~95% (no condensation)
- Relative humidity: 5% to max. 95% (non-condensing)
- Number of ports: 8
- PoE standard: IEEE802.3af (PoE)
- Ethernet speed: Fast Ethernet
- Ethernet speed: Fast Ethernet
- Industrial usage: yes
- Managed: no
- Number of ports (Uplink): 1
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vanadism: no
- Uplink port connection: SFP
- VLAN: no

Package contents

- 8+1 Port-PoE Ethernet-Switch
- Manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	14	12.85	22.50	39.00	46.50	40,803.80
Packaging Unit Inside	1	0.92	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.92	6.60	15.80	21.30	2,221.16
Net single without Packaging	1	0.76	4.40	10.30	14.40	0.00

More images:

