

AL-W High-Performance Grease

400 g



1 kg



5 kg



25 kg



Special lubricant | also for underwater applications

WEICON AL-W offers effective protection against aggressive liquids such as sea or wastewater, both in the maritime sector and in wet plants. The lubricant is suitable for rolling and sliding bearings even in mixed friction operation, for joints, levers, sliding guides, spindles, spline shafts, open gears, worm gears, chains and wire cables, and at all sliding speeds permitted for grease lubrication.

High-Performance Greases

Lubricating and Multifunctional Oils

Technische Daten

Short description	KPL 1-2 E -25	
Consistency classification	DIN 51818	NLGI grade 1-2
Base	Spec. Calcium soap / mineral oil	
Colour	beige	
Density	(+20°C) DIN 51757	0,94 g/cm³
Silicone-free	yes	
Four ball weld test property load	DIN 51350	3.200 N
Four ball weld test weld load	DIN 51350	0,7 N
Four ball weld test calotte value	DIN 51350 (1min/1000N)	3.400 N
Rotation speed parameter	450.000	
Cone penetration	DIN ISO 2137	285 - 315 1/10 mm
Water resistance	DIN 51807	0 - 40
Heat capacity	DIN EN ISO 22007-4	1,762 J/(g·K)
Thermal conductivity	0,494 W/m·K	
Dielectric strength	DIN EN 60243-1 (20°C)	9,5 kV/mm
Dripping point	IP 396	> 100 °C
Kinematic viscosity (40 °C)	DIN 51 562	100 mm²/s
Kinematic viscosity (+100 °C)	DIN 51 562	9 mm²/s
EMCOR-corrosion test	DIN 51 802	0 / 0
Complies with	German Bundeswehr TL 9150-0066, NATO Spez. G-460	
Salt spray test	keine Korrosion	
Temperature conductivity	0,296 mm²/s	
ISSA Code	53.052.10/11	
Temperature resistance	-25°C to +80°C	
IMPA Code	450437/38	
Shelf life	24 mon.	

Surface pre-treatment

First clean the surface to be lubricated with WEICON Cleaner S, depending on the degree of soiling. If screws have already been used, process with the wire brush and clean with WEICON Cleaner S.

Processing

Apply AL-W evenly.

Storage

Store in tightly closed original container. Do not store with oxidising agents. Keep container tightly closed and store in a cool, well-ventilated area. Recommended storage temperature: Room temperature.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.l. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr

AL-W High-Performance Grease

High-Performance Greases Lubricating and Multifunctional Oils

Available sizes:

26450012	AL-W High-Performance Grease, 120 g, beige
26450040	AL-W High-Performance Grease, 0,4 kg, beige
26450100	AL-W High-Performance Grease, 1 kg, beige
26450500	AL-W High-Performance Grease, 5 kg, beige
26450925	AL-W High-Performance Grease, 25 kg, beige

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.l. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr