

47903515



IP55

Combination series switch/SCHUKO socket outlet with hinged cover surface-mounted Berker W.1, grey/light grey matt

Technical features

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Electric current

Switching current	10 AX

Cover, door

- with hinged cover that falls back, manual clip-in
- Complete housing

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Colour	iron grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Contact spacing	> 3 mm

Installation, mounting

- for vertical mounting
- for screw fastening

Connection

Connection terminals	according to VDE 0620-1

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- series switch and socket outlet connectable separately

Safety

Protection index IP	IP55

- without enhanced contact protection

Use conditions

Operating temperature	-40 … 30 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK