

Product information

Cable Grease (Spray)

PI 18/10/05/2021



Description

High quality lubricant for the lubrication and preservation of wire cables. Its excellent corrosion protection enables use for cavity sealing and underfloor protection in the automotive sector.

Properties

- excellent corrosion protection
- drives out moisture
- has a lasting effect
- excellent penetration action
- highest load-carrying capacity
- optimum effectiveness when the product is used unmixed
- no aromatic hydrocarbons
- high bond strength

Technical data

| | |
|---|-----------------------|
| Color / appearance | brown |
| Flash point | -60 °C |
| Dropping point | > 85 °C |
| Base | additives, polymers |
| Viscosity at 40 °C | 22 mm ² /s |
| Form | aerosol, liquid |
| Odor | characteristic |
| Shelf life in original sealed container | 30 Monate |
| Recommended storage temperature | 10 - 30 °C |

Areas of application

For the preventive lubrication, relubrication and preservation of wire cables. Ideally suited for the cavity sealing and underfloor protection of vehicles.

Comment

Shake before using. After use, clear spray nozzle by inverting the can and spraying until only the propellant emerges.

Application

Shake well before use. The aerosol is applied to the cables by spraying. An adherent film is formed after the solvent evaporates. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.

Use of the LIQUI MOLY Cavity Seal Spray Probe (part no. 6208) is possible.

Available pack sizes



Available pack sizes

500 ml Can aerosol 6135
D-GB-I-E

Our information is based on thorough research and may be considered reliable, although not legally binding.