



30653512



Blind series switch insert 1pole with rocker 2gang with imprinted symbol Arrows surface-mounted/flush-mounted Berker W.1, polar white matt

Technical features

Architecture

Type of control unit	double rocker
----------------------	---------------

Configuration

- with mechanical and electrical interlock to prevent mutual switch-on

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX
-------------------	-------

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	42 mm
Height	71 mm
Width	71 mm

Installation, mounting

- for screw fastening

Connection

- with plug-in terminals

Cable

- with cable entry at top and bottom

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Pins of quick-release lock made of ZAMAK
- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.