

DIGITUS aluminum outlet strip, 10 outlets, 2 m supply IEC C14 plug

DN-95404
EAN 4016032266426



1U Aluminum PDU, rackmountable 10A, 2500W, 250VAC 50/60Hz, overl-prot.,1xC14

The DIGITUS® power distribution units are the perfect solution for you 482.6 mm (19") network- or server cabinet. Optimized for rack installation with 220-240V 50-60 Hz the DIGITUS® PDU offer you the best performance with qualified efficiency. The 482.6 mm (19") fixing material provides an optimized enclosing on the profile rails of your cabinets. Every PDU can be mounted horizontally as well as vertically and has the possibility, according to the cabinet, to be mounted faced up or down.

Safe and professional power in the 482.6 mm (19") range

- 10 IEC C13 Socket outlets 250VAC 50/60Hz / 10A / 2500W
- Aluminium profile
- 2x angle profiles for cabinet mounting
- 2 m Cable H05VV-F 3G1,5 mm² with IEC C14 plug
- Plastic components made by ABS UL-94V-0
- Grounding on aluminium profile
- IEC C13 straight outlets
- Overload protection
- Overload protection
- USB-C Products: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	21.00	104.00	46.00	27.00	129,168.00
Packaging Unit Inside	1	1.05	6.80	50.00	9.10	3,094.00
Packaging Unit Single	1	1.05	6.80	50.00	9.10	3,094.00
Net single without Packaging	1	0.95	6.80	50.00	9.10	3,094.00

More images:



