

Maintenance and Service Guide

SUMMARY

This guide provides information about spare parts, removal and replacement of parts, security, backing up, and more.

© Copyright 2021 HP Development Company,

AMD, Athlon, Ryzen, and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. SDHC, SDXC, and microSD are trademarks or registered trademarks of SD-3C LLC. USB Type-C and USB-C are registered trademarks of USB Implementers Forum. Miracast and Wi-Fi are registered trademarks

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

First Edition: April 2021

Document Part Number: M41299-001

Product notice

This guide describes features that are common to most models. Some features may not be available on your computer.

Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. Go to http://www.microsoft.com for details.

To access the latest user guides, go to http://www.hp.com/support, and follow the instructions to find your product. Then select **Manuals**.

Software terms

By installing, copying, downloading, or otherwise using any software product preinstalled on this computer, you agree to be bound by the terms of the HP End User License Agreement (EULA). If you do not accept these license terms, your sole remedy is to return the entire unused product (hardware and software) within 14 days for a full refund subject to the refund policy of your seller.

For any further information or to request a full refund of the price of the computer, please contact your seller.

Safety warning notice

Reduce the possibility of heat-related injuries or of overheating the computer by following the practices described.

⚠ **WARNING!** To reduce the possibility of heat-related injuries or of overheating the computer, do not place the computer directly on your lap or obstruct the computer air vents. Use the computer only on a hard, flat surface. Do not allow another hard surface, such as an adjoining optional printer, or a soft surface, such as pillows or rugs or clothing, to block airflow. Also, do not allow the AC adapter to come into contact with the skin or a soft surface, such as pillows or rugs or clothing, during operation. The computer and the AC adapter comply with the user-accessible surface temperature limits defined by applicable safety standards.

Table of contents

1 Product description	
2 Getting to know your computer	5
Right side	
Left side	
Display	
Low blue light mode (select products only)	
Keyboard area	
Touchpad settings and components	8
Touchpad settings	g
Adjusting touchpad settings	<u>c</u>
Turning on the touchpad	<u>c</u>
Touchpad components	g
Lights	10
Button, speakers, and fingerprint reader	10
Special keys	12
Bottom	13
Labels	14
3 Illustrated parts catalog	15
Computer major components	15
Display assembly subcomponents	18
Miscellaneous parts	21
4 Removal and replacement procedures preliminary requirements	23
Tools required	23
Service considerations	23
Plastic parts	23
Cables and connectors	23
Drive handling	23
Electrostatic discharge information	24
Generating static electricity	24
Preventing electrostatic damage to equipment	
Personal grounding methods and equipment	
Grounding the work area	26
Recommended materials and equipment	26

	Cleaning your computer	. 27
	Enabling HP Easy Clean (select products only)	27
	Removing dirt and debris from your computer	. 27
	Cleaning your computer with a disinfectant	28
	Caring for wood veneer (select products only)	29
	Packaging and transporting guidelines	. 29
	Accessing support information	. 29
5 D		24
5 Kem	noval and replacement procedures for authorized service provider parts	
	Preparation for disassembly	
	Bottom cover and rubber feet	
	Battery	
	Memory modules	
	WLAN module	
	Hard drive Fingerprint reader	
	USB board	
	Touchpad	
	Fan	
	Heat sink	
	System board	
	Speakers	
	Display assembly	
	Power connector cable	
	Keyboard with top cover	
	Reybourd With top cover	
6 Usin	ng Setup Utility (BIOS)	56
	Starting Setup Utility (BIOS)	56
	Updating Setup Utility (BIOS)	. 56
	Determining the BIOS version	56
	Preparing for a BIOS update	57
	Downloading a BIOS update	. 57
	Installing a BIOS update	57
7 Bacl	king up, restoring, and recovering	. 59
	Backing up information and creating recovery media	
	Using Windows tools for backing up	
	Using the HP Cloud Recovery Download Tool to create recovery media (select products only)	

Restoring and recovering your system	59
Creating a system restore	60
Restoring and recovery methods	60
Recovering using HP Recovery media	60
Changing the computer boot order	60
Using HP Sure Recover (select products only)	61
8 Using HP PC Hardware Diagnostics	62
Using HP PC Hardware Diagnostics Windows (select products only)	62
Using an HP PC Hardware Diagnostics Windows hardware failure ID code	62
Accessing HP PC Hardware Diagnostics Windows	62
Accessing HP PC Hardware Diagnostics Windows from HP Help and Support (select products only)	62
Accessing HP PC Hardware Diagnostics Windows from Support Assistant	
Accessing HP PC Hardware Diagnostics Windows from the Start menu (select products only)	63
Downloading HP PC Hardware Diagnostics Windows	63
Downloading the latest HP PC Hardware Diagnostics Windows version from HP	63
Downloading the HP PC Hardware Diagnostics Windows from the Microsoft Store .	63
Downloading HP Hardware Diagnostics Windows by product name or number (select products only)	64
Installing HP PC Hardware Diagnostics Windows	64
Using HP PC Hardware Diagnostics UEFI	64
Using an HP PC Hardware Diagnostics UEFI hardware failure ID code	64
Starting HP PC Hardware Diagnostics UEFI	65
Downloading HP PC Hardware Diagnostics UEFI to a USB flash drive	65
Downloading the latest HP PC Hardware Diagnostics UEFI version	65
Downloading HP PC Hardware Diagnostics UEFI by product name or number (select products only)	65
Using Remote HP PC Hardware Diagnostics UEFI settings (select products only)	
Downloading Remote HP PC Hardware Diagnostics UEFI	
Downloading the latest Remote HP PC Hardware Diagnostics UEFI version	
Downloading Remote HP PC Hardware Diagnostics UEFI by product name or number	
Customizing Remote HP PC Hardware Diagnostics UEFI settings	
9 Specifications	68
Computer specifications	68
Display specifications	68
Solid-state drive specifications	69

10 Power cord set requirements	71
Requirements for all countries	71
Requirements for specific countries and regions	71
11 Recycling 7	73
Index7	74

1 Product description

This table provides detailed product information.

Table 1-1 Product components and their descriptions

Category	Description		
Product Name	HP 17 Laptop		
	Model number: 17-cp0xxx		
Processors	AMD® processors		
	AMD Ryzen™ 7 5700U (1.80 GHz base frequency, up to 4.30 GHz, 8 MB cache, 8 cores)		
	AMD Ryzen 5 5500U (2.10 GHz base frequency, up to 4.00 GHz, 8 MB cache, 6 cores)		
	AMD Ryzen 3 5300U (2.60 GHz base frequency, up to 3.80 GHz, 4 MB cache, 4 cores)		
	AMD Ryzen 3 3250U (2.60 GHz base frequency, up to 3.50 GHz, 4 MB cache, 2 cores)		
	AMD Athlon™ Gold 3150U (2.40 GHz base frequency, up to 3.30 GHz, 4 MB cache, 2 cores)		
	AMD Athlon Silver 3050U (2.30 GHz base frequency, up to 3.20 GHz, 4 MB cache, 2 cores)		
	AMD 3020e (1.20 GHz base frequency, up to 2.60 GHz, 4 MB cache, 2 cores)		
Graphics	Internal graphics		
	AMD Radeon™ Graphics		
Display	43.9 cm (17.3 in), LED, micro-edge, eDP 1.2 without PSR, 250 nits		
	Full high definition (FHD) (1920 × 1080), UWVA, 45% NTSC, antiglare		
	High definition (HD+) (1600 × 900), SVA, 60% NTSC, antiglare		
	HD+, SVA, 60% NTSC, BrightView, touch-on panel (TOP)		
	HD+, SVA, 60% NTSC, BrightView		
Memory	Not customer-accessible		
	Up to 16 GB of DDR4-3200, DDR4-2666, or DDR4-2400 dual-channel support		
	Supports the following configurations:		
	• 16 GB (8 × 2)		
	• 12 GB (8 + 4)		
	• 8 GB (8 × 1 or 4 × 2)		
	• 4 GB (4 × 1)		
Primary storage	M.2 2280 solid-state drives (NGFF)		
	1 TB, PCIe, value		
	512 GB, PCIe, value		
	256 GB, PCIe, value		

Table 1-1 Product components and their descriptions (continued)

Category	Description		
	128 GB, PCle-3 × 2, TLC		
	Hard drives		
	2 TB, 5400 rpm		
	1 TB, 5400 rpm		
	Combination hard drive + solid-state drive		
1 TB, 5400 rpm hard drive + 512 GB, PCIe, solid-state drive 1 TB, 5400 rpm hard drive + 256 GB, PCIe, solid-state drive			
			1 TB, 5400 rpm hard drive + 128 GB, PCle, solid-state drive
Audio and video	HP TrueVision HD Camera: indicator LED, USB2.0, HD BSI sensor, f2.0, WDR		
	720p by 30 frames per second		
	Dual array digital microphone with appropriate software: beam forming, echo cancellation, and noise suppression		
	HP Audio Center		
	Dual speakers		
	Supports Cortana (far field)		
	Supports Alexa		
	Supports XiaoWei		
Wireless	Wireless Local Area Network (WLAN) (select products only)		
	Realtek RTL8821CE 802.11b/g/n/a/ac (1 × 1) MU-MIMO supported and Bluetooth® 4.2 combo		
	Realtek 802.11b/g/n/a/ac (2 × 2) MU-MIMO supported and Bluetooth 5		
	Realtek 8852AE Wi-Fi® 6 Bluetooth 5.2 WLAN		
	Realtek 8852AE-VT Wi-Fi 6 Bluetooth 5.2 WLAN		
	Compatible with Miracast® devices		
	Supports modern standby (connected) (select products only)		
	Intel BT Audio Offload		
Card reader	HP Multi-Format Digital Media Card Reader		
	Supports SDHC™, SDXC™		
	Push-pull insertion/removal		
Ports	HDMI 1.4b		
	Audio-out (headphone)/audio-in (microphone) combo jack		
	USB 3.2 Gen 1 Type-C (supports data transfer)		
	(2) USB 3.2 Gen 1 Type-A port		
	AC Smart Pin adapter plug		

Table 1-1 Product components and their descriptions (continued)

Category	Description	
Keyboard/pointing devices	Keyboard	
uevices	Natural silver, island style, with or without backlight	
	Snow white, island style, with or without backlight	
	Opulent aubergine, island style, with or without backlight	
	Light underwater teal, island style, with or without backlight	
	Jet black, not backlit	
	Evening blue, not backlit	
	Clickpad with image sensor	
	Multitouch gestures enabled	
	Precision Touchpad support	
	Supports modern trackpad gestures	
	Taps enabled as default	
Power requirements	Battery	
	3 cell, 41 Whr	
	Long life	
	Fast charge technology	
	Smart AC adapters	
	45 W, right angle, standard barrel, nPFC, 4.5 mm, 1.8 m (6.0 ft)	
	Power cord	
	C5, 1.0 m (3.3 ft) conventional	
Security	Trusted Platform Module (fTPM) 2.0	
	Fingerprint reader (select products only)	
Operating system	Windows® 10 Home 64	
	Windows 10 Home 64 Advanced	
	Windows 10 Home 64 Advanced Single Language	
	Windows 10 Home 64 Plus	
	Windows 10 Home 64 Plus Single Language	
	Windows 10 Home 64 Plus Single Language Africa Market PPP	
	Windows 10 Home 64 Single Language	
	Windows 10 Home 64 Single Language Africa Market PPP	
	Windows 10 Home S 64	
	Windows 10 Home S 64 Entry	
	Windows 10 Home S 64 Plus	

Table 1-1 Product components and their descriptions (continued)

Category	Description
	Windows 10 Home S 64 Value
	FreeDOS 3.0
Serviceability	End user replaceable parts
	AC adapter

2 Getting to know your computer

Your computer features top-rated components. This chapter provides details about your components, where they are located, and how they work.

Right side

Identify the components on the right side of the computer.




Table 2-1 Right-side components and their descriptions

Component			Description	
(1)	راء	Power light Power light	On: The computer is on.	
	0		 Blinking (select products only): The computer is in the Sleep state, a power-saving state. The computer shuts off power to the display and other unnecessary components. 	
			 Off: Depending on your computer model, the computer is off, in Hibernation, or in Sleep. Hibernation is the power- saving state that uses the least amount of power. 	
(2)	8	Drive light	Blinking white: The hard drive is being accessed.	
(3)	SD	Memory card reader (select products only)	Reads optional memory cards that enable you to store, manage, share, or access information.	
			To insert a card:	
			 Hold the card label-side up, with connectors facing the computer. 	
			Insert the card into the memory card reader, and then press in on the card until it is firmly seated.	
			To remove a card:	
			Pull the card out of the memory card reader.	
(4)	ss←	USB SuperSpeed port	Connects a USB device, provides high-speed data transfer, and (for select products) charges small devices (such as a smartphone) when the computer is on or in Sleep mode.	

Table 2-1 Right-side components and their descriptions (continued)

Compo	nent		Description
			NOTE: Use a standard USB Type-A charging cable or cable adapter (purchased separately) when charging a small external device.
(5)		AC adapter and battery light	 White: The AC adapter is connected and the battery is fully charged.
			 Blinking amber: The AC adapter is disconnected and the battery has reached a low battery level.
			 Amber: The AC adapter is connected and the battery is charging.
			Off: The battery is not charging.
(6)	Ą	Power connector	Connects an AC adapter.

Left side

Identify the components on the left side of the computer.




Table 2-2 Left-side components and their descriptions

Come	Component		Description
Component			Description
(1)	ss⇔	USB SuperSpeed port	Connects a USB device, provides high-speed data transfer, and (for select products) charges small devices (such as a smartphone) when the computer is on or in Sleep mode.
			NOTE: Use a standard USB Type-A charging cable or cable adapter (purchased separately) when charging a small external device.
(2)	наті	HDMI port	Connects an optional video or audio device, such as a high- definition television, any compatible digital or audio component, or a high-speed High-Definition Multimedia Interface (HDMI) device.
(3)	ss←	USB Type-C [®] SuperSpeed port	Connects a USB device, provides high-speed data transfer, and (for select products) charges small devices (such as a smartphone) when the computer is on or in Sleep mode.

Table 2-2 Left-side components and their descriptions (continued)

Component			Description	
			NOTE: Use a standard USB Type-C charging cable or cable adapter (purchased separately) when charging a small external device.	
(4)	O	Audio-out (headphone)/Audio-in (microphone) combo jack	Connects optional powered stereo speakers, headphones, earbuds, a headset, or a television audio cable. Also connects an optional headset microphone. This jack does not support optional standalone microphones.	
			WARNING! To reduce the risk of personal injury, adjust the volume before putting on headphones, earbuds, or a headset. For additional safety information, see the <i>Regulatory, Safety, and Environmental Notices</i> .	
			To access this guide:	
			▲ Type HP Documentation in the taskbar search box, and then select HP Documentation.	
			NOTE: When a device is connected to the jack, the computer speakers are disabled.	

Display

The computer display can include essential components such as speakers, antennas, cameras, and microphones.

Low blue light mode (select products only)

Your computer display is shipped from the factory in low blue light mode for improved eye comfort and safety. Also, blue light mode automatically adjusts blue light emissions when you are using the computer at night or for reading.

MARNING! To reduce the risk of serious injury, read the Safety & Comfort Guide. It describes proper workstation setup and proper posture, health, and work habits for computer users. The Safety & Comfort Guide also provides important electrical and mechanical safety information. The Safety & Comfort Guide is available on the web at http://www.hp.com/ergo.




Table 2-3 Display components and their descriptions

Component		Description
(1)	WLAN antennas*	Send and receive wireless signals to communicate with wireless local area networks (WLANs).
(2)	Internal microphones (2)	Record sound.
(3)	Camera light	On: The camera is in use.
(4)	Camera	Allows you to video chat, record video, and record still images. Some cameras also allow a facial recognition logon to Windows, instead of a password logon.
		NOTE: Camera functions vary depending on the camera hardware and software installed on your product.

^{*}The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions.

For wireless regulatory notices, see the section of the *Regulatory, Safety, and Environmental Notices* that applies to your country or region.

To access this guide:

▲ Type HP Documentation in the taskbar search box, and then select HP Documentation.

Keyboard area

Keyboards can vary by language.

Touchpad settings and components

Learn the touchpad settings and components

Touchpad settings

Learn how to adjust touchpad settings.

Adjusting touchpad settings

Use these steps to adjust touchpad settings and gestures.

- 1. Type touchpad settings in the taskbar search box, and then press enter.
- **2.** Choose a setting.

Turning on the touchpad

Follow these steps to turn on the touchpad.

- 1. Type touchpad settings in the taskbar search box, and then press enter.
- 2. Using an external mouse, click the **touchpad** button.

If you are not using an external mouse, press the Tab key repeatedly until the pointer rests on the **touchpad** button. Then press the spacebar to select the button.

Touchpad components

Identify the touchpad components.




Table 2-4 Touchpad components and their descriptions

Component		Description
(1)	Touchpad zone	Reads your finger gestures to move the pointer or activate items on the screen.
(2)	Left control zone	Textured area that allows you to perform additional gestures.
(3)	Right control zone	Textured area that allows you to perform additional gestures.

Lights

Identify the lights on the computer.





Table 2-5 Lights and their descriptions

Component			Description	
(1)		Caps lock light	On: Caps lock is on, which switches the key input to all capital letters.	
(2)	₽	Mute light	On: Computer sound is off.Off: Computer sound is on.	
(3)	ψ	Power light	 On: The computer is on. Blinking (select products only): The computer is in the Sleep state, a power-saving state. The computer shuts off power to the display and other unnecessary components. Off: Depending on your computer model, the computer is off, in Hibernation, or in Sleep. Hibernation is the power-saving state that uses the least amount of power. 	

Button, speakers, and fingerprint reader

Identify the computer button, speakers and fingerprint reader.



Fingerprint readers, which enable a fingerprint logon, can be located on the touchpad, on a side panel of the computer, or on the top cover below the keyboard.

IMPORTANT: To verify that your computer supports fingerprint reader sign-in, type Sign-in options in the taskbar search box and follow the on-screen instructions. If **Fingerprint reader** is not listed as an option, then your computer does not include a fingerprint reader.

Table 2-6 Button, speakers, and fingerprint reader and their descriptions

Component		Description
(1)	Speakers (2)	Produce sound.
(2)	Power button	 When the computer is off, press the button briefly to turn on the computer.
		 When the computer is on, press the button briefly to initiate Sleep.
		 When the computer is in the Sleep state, press the buttor briefly to exit Sleep (select products only).
		 When the computer is in Hibernation, press the button briefly to exit Hibernation.
		IMPORTANT: Pressing and holding down the power button results in the loss of unsaved information.
		If the computer has stopped responding and shutdown procedures are ineffective, press and hold the power button down for at least 10 seconds to turn off the computer.
		To learn more about your power settings, see your power options:

Table 2-6 Button, speakers, and fingerprint reader and their descriptions (continued)

Component			Description	
	▲ Right-click the Power icon Options .			
(3)	<u></u>	Fingerprint reader (select products only)	Allows a fingerprint logon to Windows, instead of a password logon.	
	.,.		Swipe down across the fingerprint reader.	
			IMPORTANT: To prevent fingerprint logon issues, be sure when you register your fingerprint that all sides of your finger are registered by the fingerprint reader.	

Special keys

Identify the special keys.




Table 2-7 Special keys and their descriptions

Comp	onent		Description	
(1)		esc key	Displays system information when pressed in combination with the fn key.	
(2)		fn key	Executes specific functions when pressed in combination with another key.	
(3)	4	Windows key	Opens the Start menu. NOTE: Pressing the Windows key again will close the Start menu.	
(4)		Action keys	Execute frequently used system functions as defined by the icon symbols on f1 through f12 function keys.	
(5)	மு	Power button	 When the computer is off, press the button briefly to turn on the computer. When the computer is on, press the button briefly to initiate Sleep. 	

Table 2-7 Special keys and their descriptions (continued)

Component	t	Description
		 When the computer is in the Sleep state, press the button briefly to exit Sleep (select products only).
		 When the computer is in Hibernation, press the button briefly to exit Hibernation.
		IMPORTANT: Pressing and holding down the power button results in the loss of unsaved information.
		If the computer has stopped responding and shutdown procedures are ineffective, press and hold the power button down for at least 10 seconds to turn off the computer.
		To learn more about your power settings, see your power options:
		Right-click the Power icon , and then select Power
		Options.
(6)	num lk key	Alternates between the navigational and numeric functions on the integrated numeric keypad.
(7)	Integrated numeric keypad	A separate keypad to the right of the alphabet keyboard. When num lk is pressed, the keypad can be used like an external numeric keypad.
		NOTE: If the keypad function is active when the computer is turned off, that function is reinstated when the computer is turned back on.

Bottom

Identify the bottom components.




Table 2-8 Bottom components and their descriptions

Component	Description
Vent	Enables airflow to cool internal components.
	NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.

Labels

The labels affixed to the computer provide information that you might need when you troubleshoot system problems or travel internationally with the computer. Labels can be in paper form or imprinted on the product.

- IMPORTANT: Labels described in this section might be located at the bottom of the computer, inside the battery bay, under the service door, on the back of the display, or on the bottom of a tablet kickstand.
 - Service label—Provides important information to identify your computer. When contacting support, you
 might be asked for the serial number, the product ID, or the model number. Locate this label before you
 contact support.



Table 2-9 Service label components

Comp	Component		
(1)	Serial number		
(2)	Product ID		
(3)	HP product name, model number		

- Regulatory labels—Provide regulatory information about the computer.
- Warranty information—Included in the regulatory information.
- Wireless certification labels—Provide information about optional wireless devices and the approval markings for the countries or regions in which the devices have been approved for use.

3 Illustrated parts catalog

Use this table to determine the spare parts that are available for the computer.

Computer major components

To identify the computer major components, use this illustration and table.

- NOTE: HP continually improves and changes product parts. For complete and current information about supported parts for your computer, go to http://partsurfer.hp.com, select your country or region, and then follow the on-screen instructions.
- **NOTE:** Details about your computer, including model, serial number, product key, and length of warranty, are on the service tag at the bottom of your computer.




Table 3-1 Computer major component descriptions and part numbers

ltem	Component	Spare part number		
(1)	Display assembly	not available as a spare part		
	NOTE: Display spare parts are available only as subcomponents.			
(2)	Top cover/keyboard			
	Backlit, natural silver, no fingerprint reader	M50456-xx1		
	Backlit, natural silver, fingerprint reader	M50457-xx1		
	Not backlit, natural silver, no fingerprint reader	M50458-xx1		
	Not backlit, natural silver, fingerprint reader	M50459-xx1		
	Backlit, snow white, no fingerprint reader	M50464-xx1		
	Backlit, snow white, fingerprint reader	M50465-xx1		
	Not backlit, snow white, no fingerprint reader	M50466-xx1		
	Not backlit, snow white, fingerprint reader	M50467-xx1		
	Not backlit, jet black, no fingerprint reader	M50468-xx1		
	Not backlit, jet black, fingerprint reader	M50469-xx1		
	Not backlit, evening blue, no fingerprint reader	M50470-xx1		
	Backlit, opulent aubergine, fingerprint reader	M59358-xx1		
	Not backlit, opulent aubergine, fingerprint reader	M59359-xx1		
	Backlit, underwater teal, fingerprint reader	M59360-xx1		
	Not backlit, underwater teal, fingerprint reader	M59361-xx1		
(3)	Touchpad			
	NOTE: The touchpad cable is available as spare part number M50423-001.			
	Jet black	M50414-001		
	Evening blue	M50415-001		
	Natural silver	M50416-001		
	Snowflake white	M50417-001		
	Opulent aubergine	M59354-001		
	Underwater teal	M59355-001		
(4)	Heat sink (includes replacement thermal material)			
	For use with 6 W processors	M53875-001		
	For use with 15 W processors	M50401-001		
(5)	Fan	M50402-001		
(6)	Fan insert	not available as a spare part		
(7)	System board (includes integrated processor)			

(7) System board (includes integrated processor)

NOTE: All system board spare part kits include replacement thermal material.

All system boards use the following part numbers:

Table 3-1 Computer major component descriptions and part numbers (continued)

ltem	Component	Spare part number
	xxxxxx-001: Non-Windows operating systems	
	xxxxxx-601: Windows operating system	
	AMD Ryzen7 5700U processor	M51689-xx1
	AMD Ryzen5 5500U processor	M51688-xx1
	AMD Ryzen3 5300U processor	M51687-xx1
	AMD Ryzen3 3250U processor	M51686-xx1
	AMD Athlon 3150U processor	M51685-xx1
	AMD Athlon 3050U processor	M51684-xx1
	AMD 3020e processor	M51683-xx1
(8)	Battery (3 cell, 41 Whr)	L97300-005
(9)	Power connector cable	M50400-001
(10)	Bottom cover	
	Jet black	M50394-001
	Evening blue	M50395-001
	Natural silver	M50396-001
	Snowflake white	M50397-001
	Pale gold	M50398-001
	Pale rose gold	M50399-001
	Opulent aubergine	M59350-001
	Underwater teal	M59351-001
(11)	WLAN module	
	Realtek 8852AE Wi-Fi 6 Bluetooth 5.2	M34027-005
	Realtek 802.11b/g/n/a/ac (2 × 2) MU-MIMO supported and Bluetooth 5	L44796-005
	Realtek 8821CE 802.11b/g/n/a/ac (1 × 1) MU-MIMO supported and Bluetooth 4.2 combo	M09870-005
	Realtek 8852AE-VT Wi-Fi 6 Bluetooth 5.2	M34029-005
	Memory modules (not illustrated)	
	8 GB (DDR4, PC-3200)	L46598-005
	8 GB (DDR4, PC-2666)	L76708-006
	4 GB (DDR4, PC-3200)	L83673-005
	4 GB (DDR4, PC-2666)	L76710-006
(12)	Fingerprint reader	
	NOTE: The fingerprint reader cable is available in the Cable Kit as spare part number M50424-001.	
	Starry blue	M50418-001

Table 3-1 Computer major component descriptions and part numbers (continued)

ltem	Component	Spare part number
	Natural silver	M50419-001
	Snowflake white	M50420-001
	Opulent aubergine	M59356-001
	Underwater teal	M59357-001
(13)	Solid-state drive (PCIe)	
	1 TB	L85370-005
	512 GB	L85364-005
	256 GB	L85354-005
	128 GB, TLC	M06792-005
	Hard drive (not illustrated)	
	2 TB, 5400 rpm	912487-855
	1 TB, 5400 rpm	L30422-001
(14)	USB board	M50413-001
	NOTE: The USB board cable is available as spare part number M50422-001.	
(15)	Speakers (left and right)	M50412-001
(16)	Rubber feet	
	Jet black	M50428-001
	Evening blue	M50429-001
	Natural silver	M50430-001
	Ash silver	M50431-001
	Pale gold	M50432-001
	Pale rose gold	M50433-001

Display assembly subcomponents

To identify the display assembly subcomponents, use this illustration and table.




Table 3-2 Display component descriptions and part numbers

ltem	Component	Spare part number
(1)	Display panel	
	HD, antiglare	M51681-001
	HD, BrightView	M51682-001
	HD, BrightView, touch-on panel (TOP)	M51679-001
	FHD, antiglare	M51680-001
(2)	Display bezel	
	Standard	M50434-001
	Opulent aubergine	M59352-001
	Underwater teal	M59353-001

Table 3-2 Display component descriptions and part numbers (continued)

ltem	Component	Spare part number
(3)	Camera module	M50436-001
(4)	Hinges (left and right)	
	Touch screen models	M50410-001
	Nontouch models	M50409-001
(5)	Touch control board	M50421-001
(6)	Display and camera cable	
	HD, touch screen	M50425-001
	HD, nontouch	M50426-001
	FHD, nontouch	M50427-001
(7)	WLAN antennas and cables	
	Dual antenna	M50375-001
	Single antenna	M50374-001
(8)	Display back cover	
	Models with dual antennas:	
	Jet black, nontouch	M50377-001
	Evening blue, nontouch	M50379-001
	Natural silver, nontouch	M50382-001
	Natural silver, touch screen	M50383-001
	Pale gold, nontouch	M50386-001
	Pale gold, touch screen	M50387-001
	Pale rose gold, nontouch	M50390-001
	Pale rose gold, touch screen	M50391-001
	Snowflake white, nontouch	M50393-001
	Opulent aubergine, nontouch	M59344-001
	Opulent aubergine, touch screen	M59345-001
	Underwater teal, nontouch	M59348-001
	Underwater teal, touch screen	M59349-001
	Models with a single antenna:	
	Jet black, nontouch	M50376-001
	Evening blue, nontouch	M50378-001
	Natural silver, nontouch	M50380-001
	Natural silver, touch screen	M50381-001
	Pale gold, nontouch	M50384-001

Table 3-2 Display component descriptions and part numbers (continued)

ltem	Component	Spare part number
	Pale gold, touch screen	M50385-001
	Pale rose gold nontouch	M50388-001
	Pale rose gold, touch screen	M50389-001
	Snowflake white, nontouch	M50392-001
	Opulent aubergine, nontouch	M59342-001
	Opulent aubergine, touch screen	M59343-001
	Underwater teal, nontouch	M59346-001
	Underwater teal, touch screen	M59347-001
(9)	Hinge cover	
	Jet black	M50403-001
	Evening blue	M50404-001
	Natural silver	M50405-001
	Snowflake white	M50406-001
	Pale gold	M50407-001
	Pale rose gold	M50408-001

Miscellaneous parts

To identify the miscellaneous parts, use this table.

Table 3-3 Miscellaneous part descriptions and part numbers

Component	Spare part number
AC adapters	
45 W, nPFC, SMART, RC, 4.5 mm, nonslim	741727-001
Screw Kit	M50411-001
Mouse, HP Z3700, underwater teal	M73438-001
Mouse, HP Z3700, opulent aubergine	M73439-001
Back cover/panel adhesive tape	M50435-001
HP USB external DVD-RW drive	747080-001
Adapters	
HDMI-to-VGA adapter	701943-001
USB-to-Gigabit RJ-45 adapter	829941-001
USB-C-to-RJ-45 adapter	855560-001
USB-C-to-USB-A adapter	833960-001

Table 3-3 Miscellaneous part descriptions and part numbers (continued)

Component	Spare part number
Power cord (C5, conventional, 1.0 m [3.3 ft])	
Denmark	L19360-001
Europe (Austria, Belgium, Finland, France, Germany, the Netherlands, Norway, and Sweden)	L19361-001
North America	L19367-001
Switzerland	L19370-001
The United Kingdom	L19373-001

Removal and replacement procedures preliminary requirements

Use this information to properly prepare to disassemble and reassemble the computer.

Tools required

You need the following tools to complete the removal and replacement procedures:

- **Tweezers**
- Nonconductive, nonmarking pry tool
- Magnetic Phillips P1 screwdriver

Service considerations

The following sections include some of the considerations that you must keep in mind during disassembly and assembly procedures.



NOTE: As you remove each subassembly from the computer, place the subassembly (and all accompanying screws) away from the work area to prevent damage.

Plastic parts

Using excessive force during disassembly and reassembly can damage plastic parts.

Cables and connectors

Handle cables with extreme care to avoid damage.

IMPORTANT: When servicing the computer, be sure that cables are placed in their proper locations during the reassembly process. Improper cable placement can damage the computer.

Apply only the tension required to unseat or seat the cables during removal and insertion. Handle cables by the connector whenever possible. In all cases, avoid bending, twisting, or tearing cables. Be sure that cables are routed so that they cannot be caught or snagged as you remove or replace parts. Handle flex cables with extreme care; these cables tear easily.

Drive handling

Note the following guidelines when handling drives.

IMPORTANT: Drives are fragile components. Handle them with care. To prevent damage to the computer, damage to a drive, or loss of information, observe these precautions:

Before removing or inserting a hard drive, shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.

Before handling a drive, be sure that you are discharged of static electricity. While handling a drive, avoid touching the connector.

Before removing an optical drive, be sure that a disc is not in the drive, and be sure that the optical drive tray is closed.

Handle drives on surfaces covered with at least 2.54 cm (1 inch) of shock-proof foam.

Avoid dropping drives from any height onto any surface.

After removing a hard drive or an optical drive, place it in a static-proof bag.

Avoid exposing an internal hard drive to products that have magnetic fields, such as monitors or speakers.

Avoid exposing a drive to temperature extremes or liquids.

If a drive must be mailed, place the drive in a bubble pack mailer or other suitable form of protective packaging, and label the package "FRAGILE."

Electrostatic discharge information

A sudden discharge of static electricity from your finger or other conductor can destroy static-sensitive devices or microcircuitry. Often the spark is neither felt nor heard, but damage occurs. An electronic device exposed to electrostatic discharge (ESD) might not appear to be affected at all and can work perfectly throughout a normal cycle. The device might function normally for a while, but it has been degraded in the internal layers, reducing its life expectancy.

Networks built into many integrated circuits provide some protection, but in many cases, the discharge contains enough power to alter device parameters or melt silicon junctions.

IMPORTANT: To prevent damage to the device when you remove or install internal components, observe these precautions:

Keep components in their electrostatic-safe containers until you are ready to install them.

Before touching an electronic component, discharge static electricity by using the guidelines described Personal grounding methods and equipment on page 25.

Avoid touching pins, leads, and circuitry. Handle electronic components as little as possible.

If you remove a component, place it in an electrostatic-safe container.

Generating static electricity

Follow these static electricity guidelines.

- Different activities generate different amounts of static electricity.
- Static electricity increases as humidity decreases.

Table 4-1 Static electricity occurrence based on activity and humidity

	Relative humidity		
Event	55%	40%	10%
Walking across carpet	7,500 V	15,000 V	35,000 V

Table 4-1 Static electricity occurrence based on activity and humidity (continued)

	R	elative humidity	
Walking across vinyl floor	3,000 V	5,000 V	12,000 V
Motions of bench worker	400 V	800 V	6,000 V
Removing DIPs (dual in-line packages) from plastic tube	400 V	700 V	2,000 V
Removing DIPs from vinyl tray	2,000 V	4,000 V	11,500 V
Removing DIPs from polystyrene foam	3,500 V	5,000 V	14,500 V
Removing bubble pack from PCB (printed circuit board)	7,000 V	20,000 V	26,500 V
Packing PCBs in foam-lined box	5,000 V	11,000 V	21,000 V
Multiple electric components can be packaged together in plastic tubes, trays, or polystyrene foam.			



NOTE: As little as 700 V can degrade a product.

Preventing electrostatic damage to equipment

Many electronic components are sensitive to ESD. Circuitry design and structure determine the degree of sensitivity. The following packaging and grounding precautions are necessary to prevent static electricity damage to electronic components.

- To avoid hand contact, transport products in static-safe containers such as tubes, bags, or boxes.
- Protect all electrostatic parts and assemblies with conductive or approved containers or packaging.
- Keep electrostatic-sensitive parts in their containers until they arrive at static-free stations.
- Place items on a grounded surface before removing them from their container.
- Always be properly grounded when touching a sensitive component or assembly.
- Avoid contact with pins, leads, or circuitry.
- Place reusable electrostatic-sensitive parts from assemblies in protective packaging or conductive foam.

Personal grounding methods and equipment

Using certain equipment can prevent static electricity damage to electronic components.

- **Wrist straps** are flexible straps with a maximum of 1 M Ω ±10% resistance in the ground cords. To provide proper ground, a strap must be worn snug against bare skin. The ground cord must be connected and fit snugly into the banana plug connector on the grounding mat or workstation.
- Heel straps/Toe straps/Boot straps can be used at standing workstations and are compatible with most types of shoes or boots. On conductive floors or dissipative floor mats, use them on both feet with a maximum of 1 M Ω ±10% resistance between the operator and ground.

Table 4-2 Static shielding protection levels

Static shielding protection levels		
Method	Voltage	
Antistatic plastic	1,500	

Table 4-2 Static shielding protection levels (continued)

Static shielding protection levels		
Carbon-loaded plastic	7,500	
Metallized laminate	15,000	

Grounding the work area

To prevent static damage at the work area, follow these precautions.

- Cover the work surface with approved static-dissipative material.
- Use a wrist strap connected to a properly grounded work surface and use properly grounded tools and equipment.
- Use static-dissipative mats, foot straps, or air ionizers to give added protection.
- Handle electrostatic sensitive components, parts, and assemblies by the case or PCB laminate. Handle them only at static-free work areas.
- Turn off power and input signals before inserting and removing connectors or test equipment.
- Use fixtures made of static-safe materials when fixtures must directly contact dissipative surfaces.
- Keep the work area free of nonconductive materials, such as ordinary plastic assembly aids and polystyrene foam.
- Use conductive field service tools, such as cutters, screwdrivers, and vacuums.
- Avoid contact with pins, leads, or circuitry.

Recommended materials and equipment

HP recommends certain materials and equipment to prevent static electricity.

- Antistatic tape
- Antistatic smocks, aprons, or sleeve protectors
- Conductive bins and other assembly or soldering aids
- Conductive foam
- Conductive tabletop workstations with ground cord of 1 M Ω ±10% resistance
- Static-dissipative table or floor mats with hard tie to ground
- Field service kits
- Static awareness labels
- Wrist straps and footwear straps providing 1 M Ω ±10% resistance
- Material handling packages
- Conductive plastic bags
- Conductive plastic tubes
- Conductive tote boxes
- Opaque shielding bags

- Transparent metallized shielding bags
- Transparent shielding tubes

Cleaning your computer

Cleaning your computer regularly removes dirt and debris so that your device continues to operate at its best. Use the following information to safely clean the external surfaces of your computer.

Enabling HP Easy Clean (select products only)

HP Easy Clean helps you to avoid accidental input while you clean the computer surfaces. This software disables devices such as the keyboard, touch screen, and touchpad for a preset amount of time so that you can clean all computer surfaces.

- 1. Start HP Easy Clean in one of the following ways:
 - Select the **Start** menu, and then select **HP Easy Clean**.
 - or -
 - Select the HP Easy Clean icon in the taskbar.
 - or –
 - Select **Start**, and then select the **HP Easy Clean** tile.
- Now that your device is disabled for a short period, see <u>Removing dirt and debris from your computer on page 27</u> for the recommended steps to clean the high-touch, external surfaces on your computer. After you remove the dirt and debris, you can also clean the surfaces with a disinfectant. See <u>Cleaning your computer with a disinfectant on page 28</u> for guidelines to help prevent the spread of harmful bacteria and viruses.

Removing dirt and debris from your computer

Here are the recommended steps to clean dirt and debris from your computer.

For computers with wood veneer, see Caring for wood veneer (select products only) on page 29.

- Wear disposable gloves made of latex (or nitrile gloves, if you are latex-sensitive) when cleaning the surfaces.
- 2. Turn off your device and unplug the power cord and other connected external devices. Remove any installed batteries from items such as wireless keyboards.
- **CAUTION:** To prevent electric shock or damage to components, never clean a product while it is turned on or plugged in.
- 3. Moisten a microfiber cloth with water. The cloth should be moist, but not dripping wet.
- **IMPORTANT:** To avoid damaging the surface, avoid abrasive cloths, towels, and paper towels.
- 4. Wipe the exterior of the product gently with the moistened cloth.
- **IMPORTANT:** Keep liquids away from the product. Avoid getting moisture in any openings. If liquid makes its way inside your HP product, it can cause damage to the product. Do not spray liquids directly on the product. Do not use aerosol sprays, solvents, abrasives, or cleaners containing hydrogen peroxide or bleach that might damage the finish.

- 5. Start with the display (if applicable). Wipe carefully in one direction, and move from the top of the display to the bottom. Finish with any flexible cables, like power cord, keyboard cable, and USB cables.
- Be sure that surfaces have completely air-dried before turning the device on after cleaning.
- 7. Discard the gloves after each cleaning. Clean your hands immediately after you remove the gloves.

See <u>Cleaning your computer with a disinfectant on page 28</u> for recommended steps to clean the high-touch, external surfaces on your computer to help prevent the spread of harmful bacteria and viruses.

Cleaning your computer with a disinfectant

The World Health Organization (WHO) recommends cleaning surfaces, followed by disinfection, as a best practice for preventing the spread of viral respiratory illnesses and harmful bacteria.

After cleaning the external surfaces of your computer using the steps in Removing dirt and debris from your computer on page 27, Caring for wood veneer (select products only) on page 29, or both, you might also choose to clean the surfaces with a disinfectant. A disinfectant that is within HP's cleaning guidelines is an alcohol solution consisting of 70% isopropyl alcohol and 30% water. This solution is also known as rubbing alcohol and is sold in most stores.

Follow these steps when disinfecting high-touch, external surfaces on your computer:

- Wear disposable gloves made of latex (or nitrile gloves, if you are latex-sensitive) when cleaning the surfaces.
- 2. Turn off your device and unplug the power cord and other connected external devices. Remove any installed batteries from items such as wireless keyboards.
- **CAUTION:** To prevent electric shock or damage to components, never clean a product while it is turned on or plugged in.
- 3. Moisten a microfiber cloth with a mixture of 70% isopropyl alcohol and 30% water. The cloth should be moist, but not dripping wet.
 - CAUTION: Do not use any of the following chemicals or any solutions that contain them, including spray-based surface cleaners: bleach, peroxides (including hydrogen peroxide), acetone, ammonia, ethyl alcohol, methylene chloride, or any petroleum-based materials, such as gasoline, paint thinner, benzene, or toluene.
- IMPORTANT: To avoid damaging the surface, avoid abrasive cloths, towels, and paper towels.
- **4.** Wipe the exterior of the product gently with the moistened cloth.
 - **IMPORTANT:** Keep liquids away from the product. Avoid getting moisture in any openings. If liquid makes its way inside your HP product, it can cause damage to the product. Do not spray liquids directly on the product. Do not use aerosol sprays, solvents, abrasives, or cleaners containing hydrogen peroxide or bleach that might damage the finish.
- 5. Start with the display (if applicable). Wipe carefully in one direction, and move from the top of the display to the bottom. Finish with any flexible cables, like power cord, keyboard cable, and USB cables.
- 6. Be sure that surfaces have completely air-dried before turning the device on after cleaning.
- 7. Discard the gloves after each cleaning. Clean your hands immediately after you remove the gloves.

Caring for wood veneer (select products only)

Your product might feature high-quality wood veneer. As with all natural wood products, proper care is important for best results over the life of the product. Because of the nature of natural wood, you might see unique variations in the grain pattern or subtle variations in color, which are normal.

- Clean the wood with a dry, static-free microfiber cloth or chamois.
- Avoid cleaning products containing substances such as ammonia, methylene chloride, acetone, turpentine, or other petroleum-based solvents.
- Do not expose the wood to sun or moisture for long periods of time.
- If the wood becomes wet, dry it by dabbing with an absorbent, lint-free cloth.
- Avoid contact with any substance that might dye or discolor the wood.
- Avoid contact with sharp objects or rough surfaces that might scratch the wood.

See <u>Removing dirt and debris from your computer on page 27</u> for the recommended steps to clean the high-touch, external surfaces on your computer. After you remove the dirt and debris, you can also clean the surfaces with a disinfectant. See <u>Cleaning your computer with a disinfectant on page 28</u> for sanitizing guidelines to help prevent the spread of harmful bacteria and viruses.

Packaging and transporting guidelines

Follow these grounding guidelines when packaging and transporting equipment.

- To avoid hand contact, transport products in static-safe tubes, bags, or boxes.
- Protect ESD-sensitive parts and assemblies with conductive or approved containers or packaging.
- Keep ESD-sensitive parts in their containers until the parts arrive at static-free workstations.
- Place items on a grounded surface before removing items from their containers.
- Always be properly grounded when touching a component or assembly.
- Store reusable ESD-sensitive parts from assemblies in protective packaging or nonconductive foam.
- Use transporters and conveyors made of antistatic belts and roller bushings. Be sure that mechanized
 equipment used for moving materials is wired to ground and that proper materials are selected to avoid
 static charging. When grounding is not possible, use an ionizer to dissipate electric charges.

Accessing support information

Use this information to find the HP support that you need.

Table 4-3 Support information locations

Service consideration	Path to access information	
Records of reported failure incidents stored	Windows: Pre-operating system failures are logged in the BIOS Event Log. To view the BIOS Event Log:	
on the computer		
	1. Press the power button.	
	2. Immediately and repeatedly press esc when the power button light turns white.	

Table 4-3 Support information locations (continued)

Service consideration	Path to access information	
	NOTE: If you do not press esc at the appropriate time, you must restart the computer and again repeatedly press esc when the power button light turns white to access the utility.	
	3. Press f10 to enter the BIOS setup.	
	(On commercial products) Under the Main tab, select BIOS event log, and ther select View BIOS Event Log.	
	- or -	
	(On consumer products) Under the Main tab, select System Log .	
	Post operating system failures are logged in the Event Viewer.	
	1. Turn on the computer and allow the operating system to open.	
	2. Click the search icon in the taskbar.	
	3. Type Event Viewer, and then press enter.	
	4. Select the log from the left panel. Details display in the right panel.	
	Chrome:	
	1. Go to support.google.com/chrome.	
	2. Search collect Chrome device logs.	
Technical bulletins	To locate technical bulletins:	
	1. Go to www.hp.com.	
	2. Place the cursor over Problem solving to display more options.	
	3. Select Support & Troubleshooting.	
	4. Type the serial number, product number, or product name to go to the product support page.	
	5. Select Advisories to view technical bulletins.	
Repair professionals	To locate repair professionals:	
	1. Go to www.hp.com.	
	2. Place the cursor over Support resources to display more options.	
	3. Select Authorized service providers.	
Component and diagnosis information, failure	To locate diagnosis information and actions:	
detection, and required action	1. Go to http://www.hp.com/go/techcenter/pcdiags.	
	2. Select Get Support.	
	3. Near the bottom of the window, select Notebook PCs , and the select your location.	

5 Removal and replacement procedures for authorized service provider parts

This chapter provides removal and replacement procedures for authorized service provider parts.

- **IMPORTANT:** Components described in this chapter should be accessed only by an authorized service provider. Accessing these parts can damage the computer or void the warranty.
- **NOTE:** Details about your computer, including model, serial number, product key, and length of warranty, are on the service tag at the bottom of your computer.

Component replacement procedures

To remove and replace computer components, use these procedures.

NOTE: HP continually improves and changes product parts. For complete and current information about supported parts for your computer, go to http://partsurfer.hp.com, select your country or region, and then follow the on-screen instructions.

You must remove, replace, or loosen as many as 61 screws when you service the parts described in this chapter. Make special note of each screw size and location during removal and replacement.

Preparation for disassembly

To remove and replace computer components, use these procedures.

See Removal and replacement procedures preliminary requirements on page 23 for initial safety procedures.

- 1. Turn off the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect the power from the computer by unplugging the power cord from the computer.
- Disconnect all external devices from the computer.

Bottom cover and rubber feet

To remove the bottom cover and rubber feet, use this procedure and illustration.

Table 5-1 Bottom cover and rubber feet descriptions and part numbers

Description	Spare part number
Bottom cover, jet black	M50394-001
Bottom cover, evening blue	M50395-001
Bottom cover, natural silver	M50396-001
Bottom cover, snowflake white	M50397-001
Bottom cover, pale gold	M50398-001
Bottom cover, pale rose gold	M50399-001


Table 5-1 Bottom cover and rubber feet descriptions and part numbers (continued)

Description	Spare part number
Bottom cover, opulent aubergine	M59350-001
Bottom cover, underwater teal	M59351-001
Rubber feet, jet black	M50428-001
Rubber feet, evening blue	M50429-001
Rubber feet, natural silver	M50430-001
Rubber feet, ash silver	M50431-001
Rubber feet, pale gold	M50432-001
Rubber feet, pale rose gold	M50433-001


Before removing the bottom cover and rubber feet, prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).

Remove the rubber feet and bottom cover:

1. Peel the feet off the bottom of the computer.



Remove the six Phillips 2.5×6.0 screws (1) from under the feet and the four Phillips 2.5×7.0 screws (2) that secure the bottom cover to the computer.



Starting near the bottom-left of the bottom cover, use a nonmarking, nonconductive tool to release the edges of the bottom cover from the computer (1).



To replace the bottom cover and rubber feet, reverse the removal procedures.

Battery

To remove the battery, use this procedure and illustration.

Table 5-2 Battery description and part number

Description	Spare part number
Battery, 3 cell, 41 Whr	L97300-005

WARNING! To avoid personal injury and damage to the product:


- Do not puncture, twist, or crack the battery.
- Do not cause an external puncture or rupture to the battery. They can cause a short inside the battery, which can result in battery thermal runaway.
- Do not handle or touch the battery enclosure with sharp objects such as tweezers or pliers, which might puncture the battery.
- Do *not* compress or squeeze the battery case with tools or heavy objects stacked on top of the case. These actions can apply undue force on the battery.
- Do *not* touch the connectors with any metallic surface or object, such as metal tools, screws, or coins, which can cause shorting across the connectors.

Before removing the battery, follow these steps:

- Prepare the computer for disassembly (see Preparation for disassembly on page 31).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- **WARNING!** To reduce potential safety issues, use only the user-replaceable battery provided with the computer, a replacement battery provided by HP, or a compatible battery purchased from HP.
- **IMPORTANT:** Removing a battery that is the sole power source for the computer can cause loss of information. To prevent loss of information, save your work or shut down the computer through Windows before you remove the battery.

Remove the battery:

- 1. Remove the four Phillips M2.0 × 4.0 screws (1) that secure the battery to the computer.
- 2. Lift the bottom of the battery and remove it from the computer (2).



To install the battery, reverse the removal procedures.

Memory modules

To remove the memory modules, use this procedure and illustration.

Table 5-3 Memory module descriptions and part numbers


Description	Spare part number
8 GB (DDR4, PC-3200)	L46598-005
8 GB (DDR4, PC-2666)	L76708-006
4 GB (DDR4, PC-3200)	L83673-005
4 GB (DDR4, PC-2666)	L76710-006

Before removing the memory, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).

If you are replacing a memory module, remove the existing memory module:

- ▲ Spread the two retention clips outward (1) until the memory module tilts up at a 45° angle, and then remove the module (2). Use the same procedure to remove all memory modules.
- **IMPORTANT:** To prevent damage to the memory module, hold the memory module by the edges only. Do not touch the components on the memory module.




To protect a memory module after removal, place it in an electrostatic-safe container.

To install a memory module:

1. Align the notched edge of the module with the tab in the slot (1), and then press the module into the slot at an angle until it is seated (2).

2. Press down on the module until the side retention clips snap into place (3).



Solid-state drive

To remove the M.2 solid-state drive, use this procedure and illustration.

Table 5-4 Solid-state drive descriptions and part numbers

Description	Spare part number
1 TB, PCIe	L85370-005
512 GB, PCle	L85364-005
256 GB, PCle	L85354-005
128 GB, PCIe, TLC	M06792-005


Before removing the solid-state drive, follow these steps:

- 1. Prepare the computer for disassembly (see Preparation for disassembly on page 31).
- 2. Remove the bottom cover (see <u>Bottom cover and rubber feet on page 31</u>).
- 3. Remove the battery (see <u>Battery on page 33</u>).

Remove the solid-state drive:

1. Remove the Phillips M2.0 × 2.5 screw (1) that secures the drive to the computer.

Pull the drive away from the socket to remove it (2).



To install the solid-state drive, reverse the removal procedures.

WLAN module

To remove the WLAN module, use this procedure and illustration.

Table 5-5 WLAN module descriptions and part numbers

Description	Spare part number
Realtek 8852AE Wi-Fi 6 Bluetooth 5.2	M34027-005
Realtek 802.11b/g/n/a/ac (2 × 2) MU-MIMO supported and Bluetooth 5	L44796-005
Realtek 8821CE 802.11b/g/n/a/ac (1 × 1) MU-MIMO supported and Bluetooth 4.2 combo	M09870-005
Realtek 8852AE-VT Wi-Fi 6 Bluetooth 5.2	M34029-005

IMPORTANT: To prevent an unresponsive system, replace the wireless module only with a wireless module authorized for use in the computer by the governmental agency that regulates wireless devices in your country or region. If you replace the module and then receive a warning message, remove the module to restore device functionality, and then contact technical support.


Before removing the WLAN module, follow these steps:

- Prepare the computer for disassembly (see Preparation for disassembly on page 31). 1.
- Remove the bottom cover (see Bottom cover and rubber feet on page 31). 2.
- Remove the battery (see <u>Battery on page 33</u>).


Remove the WLAN module:

- Remove the tape that covers the antenna connectors on the WLAN module (1). 1.
- Carefully disconnect the two antenna cables from the module (2). 2.

- 3. Remove the Phillips M2.0 × 2.5 screw (3), and then remove the WLAN module (4).
- NOTE: Models have either one or two WLAN antennas. On models with two antennas, the #1 white WLAN antenna cable connects to the WLAN module #1 Main terminal. The #2 black WLAN antenna cable connects to the WLAN module #1 Aux terminal.



4. If the WLAN antenna is not connected to the terminal on the WLAN module, install a protective sleeve on the antenna connector, as shown in the following illustration.



Reverse this procedure to install the WLAN module.

Hard drive

To remove the hard drive, use these procedures and illustrations.

Fingerprint reader

To remove the fingerprint reader, use this procedure and illustration.

Table 5-6 Fingerprint reader description and part number


Description	Spare part number
Fingerprint reader, starry blue	M50418-001
Fingerprint reader, natural silver	M50419-001
Fingerprint reader, snowflake white	M50420-001
Fingerprint reader, opulent aubergine	M59356-001
Fingerprint reader, underwater teal	M59357-001
Fingerprint reader cable	M50424-001

Before removing the fingerprint reader, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see <u>Bottom cover and rubber feet on page 31</u>).
- 3. Remove the battery (see Battery on page 33).
- 4. Remove the hard drive (see <u>Hard drive on page 38</u>).

Remove the fingerprint reader:

- 1. Remove the Phillips M2.0 × 3.0 screw (1) that secures the fingerprint reader bracket to the computer, and then remove the bracket (2).
- 2. Disconnect the cable from the ZIF connector on the fingerprint reader board (3).
- **3.** Remove the fingerprint reader from the computer **(4)**.



Reverse this procedure to install the fingerprint reader.

USB board

To remove the USB board, use this procedure and illustration.

Table 5-7 USB board description and part number


Description	Spare part number
USB board	M50413-001
USB board cable	M50422-001

Before removing the USB board, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).

Remove the USB board:

- 1. Remove the two Phillips M2.0 × 4.0 screws (1) that secure the USB board to the computer.
- 2. Lift the board up and turn it over to access the cable connected to the bottom (2).
- 3. Disconnect the cable from the ZIF connector on the bottom of the board (3).



Reverse this procedure to install the USB board.

Touchpad

To remove the touchpad, use this procedure and illustration.

Table 5-8 Touchpad description and part number

Description	Spare part number
Touchpad, jet black	M50414-001
Touchpad, evening blue	M50415-001
Touchpad, natural silver	M50416-001

Table 5-8 Touchpad description and part number (continued)


Description	Spare part number
Touchpad, snowflake white	M50417-001
Touchpad, opulent aubergine	M59354-001
Touchpad, underwater teal	M59355-001
Touchpad cable	M50423-001

Before removing the touchpad, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see <u>Bottom cover and rubber feet on page 31</u>).
- **3.** Remove the battery (see <u>Battery on page 33</u>).


Remove the touchpad:

- 1. Remove the three Phillips M2.0.× 2.0 screws (1) that secure the touchpad bracket to the computer.
- **2.** Remove the bracket from the computer **(2)**.



- 3. Disconnect the cable from the ZIF connector on the touchpad module (1).
- **4.** Remove the three Phillips M2.0 × 2.0 screws **(2)** that secure the touchpad to the computer.

5. Remove the touchpad from the computer (3).



Reverse this procedure to install the touchpad.

Fan

To remove the fan, use this procedure and illustration.

Table 5-9 Fan description and part number

Description	Spare part number
Fan	M50402-001


Before removing the fan, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).


Remove the fan assembly:

1. Remove the three Phillips M2.0 \times 4.0 screws (1) that secure the fan to the computer.

Disconnect the fan cable from the system board (2), and then remove the fan from the computer (3).



If you need to remove the fan insert, remove the three Phillips M2.0 × 4.0 screws (1) that secure the insert to the computer, and then remove the insert from the computer (2).



Reverse this procedure to install the fan or fan assembly.

Heat sink

To remove the heat sink, use these procedures and illustrations.

Table 5-10 Heat sink description and part number


Description	Spare part number	
Heat sink for use with 6 W processors	M53875-001	
Heat sink for use with 15 W processors	M50401-001	

Before removing the heat sink, follow these steps:

- 1. Prepare the computer for disassembly (see Preparation for disassembly on page 31).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- **3.** Remove the battery (see <u>Battery on page 33</u>).


Remove the heat sink:

- 1. In the order indicated on the heat sink, remove the four Phillips M2.0 × 2.8 screws (1) that secure the heat sink to the computer.
- **2.** Remove the heat sink from the computer **(2)**.



3. Thoroughly clean the thermal material from the surfaces of the heat sink and the system board components each time the heat sink is removed. Replacement thermal material is included with the heat sink and system board spare part kits. The following illustration shows the replacement thermal material locations.

Thermal paste is used on the system board component (1) and on the heat sink area (2) that services it.



Reverse this procedure to install the heat sink.

System board


To remove the system board, use these procedures and illustrations.

Table 5-11 System board descriptions and part numbers


Description	Spare part number
System board (includes processor)	
All system boards use the following part numbers:	
xxxxxx-001: Non-Windows operating system	
xxxxxx-601: Windows 10 operating system	
AMD Ryzen7 5700U processor	M51689-xx1
AMD Ryzen5 5500U processor	M51688-xx1
AMD Ryzen3 5300U processor	M51687-xx1
AMD Ryzen3 3250U processor	M51686-xx1
AMD Athlon 3150U processor	M51685-xx1
AMD Athlon 3050U processor	M51684-xx1
AMD 3020e processor	M51683-xx1

Before removing the system board, follow these steps:

- 1. Prepare the computer for disassembly (see Preparation for disassembly on page 31).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).
- 4. Remove the solid-state drive (see Solid-state drive on page 36).
- 5. Remove the memory modules (see Memory modules on page 34).
- 6. Remove the WLAN module (see WLAN module on page 37).
- **7.** Remove the fan (see <u>Fan on page 42</u>).
- 1. Disconnect the following cables from the system board:
 - Power connector cable (1)
 - Left fan cable (2)
 - Display cable (ZIF) (3)
 - Speaker cable (4)
 - Keyboard cable (ZIF) (5)
 - Backlight cable (ZIF) (6) (select products only)
 - Touchpad board (ZIF) (7)
 - Hard drive cable (ZIF) (8)
 - Fingerprint reader cable (ZIF) (9) (select products only)
 - USB board cable (ZIF) (10)



- 2. Remove the three Phillips M2.0 × 4.0 screws (1) and the three Phillips M2.0 × 2.5 screws (2) that secure the system board to the computer.
- 3. Lift the side of the system board upward (3), and then pull the system board away from the connectors on the side of the computer to remove it (4).



Reverse this procedure to install the system board.

Speakers

To remove the speakers, use this procedure and illustration.

Table 5-12 Speaker description and part number


Description	Spare part number
Speaker Kit	M50412-001

Before removing the speakers, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).
- 4. Remove the WLAN module (see WLAN module on page 37).
- **5.** Remove the solid-state drive (see <u>Solid-state drive on page 36</u>).
- **6.** Remove the fan (see Fan on page 42).
- **7.** Remove the system board (see <u>System board on page 45</u>).

Remove the speakers:

- 1. Lift the protective tape that covers the cable between the speakers (1).
- 2. Use a tool to release both speakers (2). The speakers are secured with adhesive.
- **3.** Remove the speakers from the computer **(3)** .



Reverse this procedure to install the speakers.

Display assembly

To remove and disassemble the display assembly, use these procedures and illustrations.

Full hinge-up displays are not available as spare parts. Spare parts for displays are available only at the subcomponent level.


Before removing the display panel, follow these steps:

- 1. Prepare the computer for disassembly (see <u>Preparation for disassembly on page 31</u>).
- 2. Remove the bottom cover (see <u>Bottom cover and rubber feet on page 31</u>).
- 3. Remove the battery (see <u>Battery on page 33</u>).


Remove the display assembly:

1. Disconnect the display cable from the system board ZIF connector (1), and then remove the tape that secures the display cable to the system board (2).

2. Disconnect the antenna cables from the WLAN module (3), and then remove the cables from the clips on the bottom and left sides of the speaker (4).



- 3. Remove the six Phillips M2.5 × 6.0 screws (1) that secure the display assembly to the computer.
- **4.** Rotate the display to open the hinges **(2)**.
- 5. Separate the display assembly from the computer (3).



- **6.** If you need to remove the hinge cover:
 - ▲ Squeeze the hinge cover (1), and then remove the hinge cover from the display (2).

The hinge covers are available as the following spare part numbers:


M50403-001: Jet black

M50404-001: Evening blue M50405-001: Natural silver

M50406-001: Snowflake white

M50407-001: Pale gold

M50408-001: Pale rose gold



If you need to remove the bezel:

Flex the top (1), the left and right sides (2), and then the bottom of the bezel (3) to release it.


Remove the bezel from the display (4). b.

The bezel is available as the following spare part numbers:

M50434-001: Standard


M59352-001: Opulent aubergine

M59353-001: Underwater teal



If you need to remove the camera module:

■ Use a tool to lift up evenly across the module and peel the module up from the display back cover (1), and then disconnect the cable from the module (2). The camera module is available as spare part number M50436-001.



- **9.** If you need to remove the display panel:
 - a. The display panel is secured to the display enclosure with tape that is installed under the left and right sides of the panel. To remove the panel, use tweezers to grasp the end of the tape (1). While turning the tweezers, wrap the tape around the tweezers (2) as you continue to pull the tape out from behind the display panel (3). You must pull the tape multiple times before it is completely removed.


b. Rotate the display panel over and place it next to the display rear cover (4).

Display panels are available as the following spare part numbers:


M51681-001: HD, antiglare panel M51682-001: HD, BrightView panel

M51679-001: HD, BrightView, touch-on panel (TOP)

M51680-001: FHD, antiglare panel




Lift the tape from the connector on the display panel (1), rotate the locking lever (2), and then disconnect the cable from the panel (3).




- **10.** If you need to remove the hinges from the display rear cover:
 - Remove the three Phillips M2.5 × 2.5 screws (1) from each hinge.
 - b. Remove the Phillips M2.5 \times 4.0 screw (2) from each hinge.
 - Remove the hinges from the display back cover (3).

The hinges are available in the Hinge Kit as spare part number M50409-001 for nontouch models and M50410-001 for touch screen models.



- **11.** If you need to remove the touch control board from the display:
 - **a.** Remove the Phillips M2.0 × 3.0 screw **(1)** that secures the board to the display.
 - **b.** Lift the board up enough to disconnect the cables.
 - **c.** Disconnect the cable from the end of the board **(3)** and the two larger ZIF cables **(4)** from the board.


The touch control board is available as spare part number M50421-001.




12. If you need to remove the display and camera cable, disconnect the cable from the camera module (1), and then release the cable from the display rear cover (2).

The display and camera cable is available as the following spare part numbers:

M50425-001: HD, touch screen M50426-001: HD, nontouch M50427-001: FHD, nontouch



13. If you need to remove the WLAN antenna cables, remove the cables from the clips on the left (1) and right (2) sides of the display rear cover, and then peel the antennas off the inside of the display rear cover (3). The wireless antennas and cables are available as spare part number M50375-001 for models with dual antennas and M50374-001 for models with a single antenna.



For a list of display rear cover spare part numbers, see <u>Display assembly subcomponents on page 18</u>.

Reverse this procedure to reassemble and replace the display assembly.

Power connector cable

To remove the power connector cable, use this procedure and illustration.

Table 5-13 Power connector cable description and part number


Description	Spare part number
Power connector cable	M50400-001

Before removing the power connector cable, follow these steps:

- 1. Prepare the computer for disassembly (see Preparation for disassembly on page 31).
- 2. Remove the bottom cover (see Bottom cover and rubber feet on page 31).
- 3. Remove the battery (see <u>Battery on page 33</u>).
- 4. Remove the display (see Display assembly on page 47).

Remove the power connector cable:

- 1. Disconnect the power connector cable from the system board (1).
- 2. Use a tool to release the power connector from the computer (2).



Reverse this procedure to install the power connector cable.

Keyboard with top cover

The top cover with keyboard remains after removing all other spare parts from the computer. In this section, the first table provides the main spare part number for the top cover/keyboards. The second table provides the country codes.

Table 5-14 Keyboard with top cover descriptions and part numbers

Description	Spare part number
Backlit, natural silver, no fingerprint reader	M50456-xx1
Backlit, natural silver, fingerprint reader	M50457-xx1
Not backlit, natural silver, no fingerprint reader	M50458-xx1

Table 5-14 Keyboard with top cover descriptions and part numbers (continued)

Description	Spare part number
Not backlit, natural silver, fingerprint reader	M50459-xx1
Backlit, snow white, no fingerprint reader	M50464-xx1
Backlit, snow white, fingerprint reader	M50465-xx1
Not backlit, snow white, no fingerprint reader	M50466-xx1
Not backlit, snow white, fingerprint reader	M50467-xx1
Not backlit, jet black, no fingerprint reader	M50468-xx1
Not backlit, jet black, fingerprint reader	M50469-xx1
Not backlit, evening blue, no fingerprint reader	M50470-xx1
Backlit, opulent aubergine, fingerprint reader	M59358-xx1
Not backlit, opulent aubergine, fingerprint reader	M59359-xx1
Backlit, underwater teal, fingerprint reader	M59360-xx1
Not backlit, underwater teal, fingerprint reader	M59361-xx1

Table 5-15 Spare part country codes

For use in country or region	Spare part number	For use in country or region	Spare part number	For use in country or region	Spare part number
Belgium	-A41	Hungary	-211	Saudi Arabia	-171
Brazil	-201	Iceland	-DD1	Slovenia	-BA1
Bulgaria	-261	India	-002	South Korea	-AD1
Chile	-161	Israel	-BB1	Spain	-071
Czech Republic/Slovakia	-FL1	Italy	-061	Switzerland	-BG1
Denmark	-081	Japan	-291	Taiwan	-AB1
Denmark, Finland, and Norway	-DH1	The Netherlands	-B31	Thailand	-281
French Canada	-DB1	Northern Africa	-FP1	Turkey	-141
Finland/Sweden	-B71	Norway	-091	Turkey-F	-541
France	-051	Portugal	-131	Ukraine	-BD1
Germany	-041	Romania	-271	United Kingdom	-031
Greece	-151	Russia	-251	United States	-001

Using Setup Utility (BIOS) 6

Setup Utility, or Basic Input/Output System (BIOS), controls communication between all the input and output devices on the system (such as disk drives, display, keyboard, mouse, and printer). Setup Utility (BIOS) includes settings for the types of devices installed, the startup sequence of the computer, and the amount of system and extended memory.



NOTE: To start Setup Utility on convertible computers, your computer must be in notebook mode and you must use the keyboard attached to your notebook.

Starting Setup Utility (BIOS)

You have several ways to access the Setup Utility (BIOS).

- IMPORTANT: Use extreme care when making changes in Setup Utility (BIOS). Errors can prevent the computer from operating properly.
 - Turn on or restart the computer and guickly press f10.

- or -

Turn on or restart the computer, quickly press esc, and then press f10 when the Start menu is displayed.

Updating Setup Utility (BIOS)

Updated versions of Setup Utility (BIOS) might be available on the HP website. Most BIOS updates on the HP website are packaged in compressed files called SoftPags. Some download packages contain a file named Readme.txt, which contains information regarding installing and troubleshooting the file.

Determining the BIOS version

To decide whether you need to update Setup Utility (BIOS), first determine the BIOS version on your computer.

To reveal the BIOS version information (also known as ROM date and System BIOS), use one of these options.

- **HP Support Assistant**
 - Type support in the taskbar search box, and then select the **HP Support Assistant** app.

– or –

Select the question mark icon in the taskbar.

- Select **My notebook**, and then select **Specifications**.
- Setup Utility (BIOS)
 - Start Setup Utility (BIOS) (see Starting Setup Utility (BIOS) on page 56).
 - Select Main, and then make note of the BIOS version. 2.
 - Select **Exit**, select one of the options, and then follow the on-screen instructions.
- In Windows, press ctrl+alt+s.

To check for later BIOS versions, see Preparing for a BIOS update on page 57.

Preparing for a BIOS update

Be sure to follow all prerequisites before downloading and installing a BIOS update.

- IMPORTANT: To reduce the risk of damage to the computer or an unsuccessful installation, download and install a BIOS update only when the computer is connected to reliable external power using the AC adapter. Do not download or install a BIOS update while the computer is running on battery power, docked in an optional docking device, or connected to an optional power source. During the download and installation, follow these instructions:
 - Do not disconnect power from the computer by unplugging the power cord from the AC outlet.
 - Do not shut down the computer or initiate Sleep.
 - Do not insert, remove, connect, or disconnect any device, cable, or cord.
- NOTE: If your computer is connected to a network, consult the network administrator before installing any software updates, especially system BIOS updates.

Downloading a BIOS update

After you review the prerequisites, you can check for and download BIOS updates.

Type support in the taskbar search box, and then select the HP Support Assistant app.

- or -

Select the guestion mark icon in the taskbar.

- 2. Select **Updates**, and then select **Check for updates and messages**.
- 3. Follow the on-screen instructions.
- **4.** At the download area, follow these steps:
 - a. Identify the most recent BIOS update and compare it to the BIOS version currently installed on your computer. If the update is more recent than your BIOS version, make a note of the date, name, or other identifier. You might need this information to locate the update later, after it has been downloaded to your hard drive.
 - **b.** Follow the on-screen instructions to download your selection to the hard drive.

Make a note of the path to the location on your hard drive where the BIOS update is downloaded. You will need to access this path when you are ready to install the update.

Installing a BIOS update

BIOS installation procedures vary. Follow any instructions that appear on the screen after the download is complete. If no instructions appear, follow these steps.

- 1. Type file in the taskbar search box, and then select **File Explorer**.
- 2. Select your hard drive designation. The hard drive designation is typically Local Disk (C:).
- Using the hard drive path you recorded earlier, open the folder that contains the update.
- **4.** Double-click the file that has an .exe extension (for example, *filename*.exe).
 - The BIOS installation begins.
- 5. Complete the installation by following the on-screen instructions.



NOTE: After a message on the screen reports a successful installation, you can delete the downloaded file from your hard drive.

7 Backing up, restoring, and recovering

You can use Windows tools or HP software to back up your information, create a restore point, reset your computer, create recovery media, or restore your computer to its factory state. Performing these standard procedures can return your computer to a working state faster.

IMPORTANT: If you will be performing recovery procedures on a tablet, the tablet battery must be at least 70% charged before you start the recovery process.

IMPORTANT: For a tablet with a detachable keyboard, connect the tablet to the keyboard base before beginning any recovery process.

Backing up information and creating recovery media

These methods of creating recovery media and backups are available on select products only.

Using Windows tools for backing up

HP recommends that you back up your information immediately after initial setup. You can do this task either using Windows Backup locally with an external USB drive or using online tools.

- **IMPORTANT:** Windows is the only option that allows you to back up your personal information. Schedule regular backups to avoid information loss.
- NOTE: If computer storage is 32 GB or less, Microsoft® System Restore is disabled by default.

Using the HP Cloud Recovery Download Tool to create recovery media (select products only)

You can use the HP Cloud Recovery Download Tool to create HP Recovery media on a bootable USB flash drive.

For details:

- ▲ Go to http://www.hp.com/support, search for HP Cloud Recovery, and then select the result that matches the type of computer that you have.
- NOTE: If you cannot create recovery media yourself, contact support to obtain recovery discs. Go to http://www.hp.com/support, select your country or region, and then follow the on-screen instructions.
- **IMPORTANT:** HP recommends that you follow the <u>Restoring and recovery methods on page 60</u> to restore your computer before you obtain and use the HP recovery discs. Using a recent backup can return your machine to a working state sooner than using the HP recovery discs. After the system is restored, reinstalling all the operating system software released since your initial purchase can be a lengthy process.

Restoring and recovering your system

You have several tools available to recover your system both within and outside of Windows if the desktop cannot load.

HP recommends that you attempt to restore your system using the <u>Restoring and recovery methods</u> on page 60.

Creating a system restore

System Restore is available in Windows. The System Restore software can automatically or manually create restore points, or snapshots, of the system files and settings on the computer at a particular point.

When you use System Restore, it returns your computer to its state at the time you made the restore point. Your personal files and documents should not be affected.

Restoring and recovery methods

After you run the first method, test to see whether the issue still exists before you proceed to the next method, which might now be unnecessary.

- Run a Microsoft System Restore.
- Run Reset this PC.
 - **NOTE:** The options **Remove everything** and then **Fully clean the drive** can take several hours to complete and leave no information on your computer. It is the safest way to reset your computer before you recycle it.
- Recover using HP Recovery media. For more information, see Recovering using HP Recovery media on page 60.

For more information about the first two methods, see the Get Help app:

Select the **Start** button, select the **Get Help** app, and then enter the task you want to perform.



NOTE: You must be connected to the internet to access the Get Help app.

Recovering using HP Recovery media

You can use HP Recovery media to recover the original operating system and software programs that were installed at the factory. On select products, it can be created on a bootable USB flash drive using the HP Cloud Recovery Download Tool.

For details, see Using the HP Cloud Recovery Download Tool to create recovery media (select products only) on page 59.



NOTE: If you cannot create recovery media yourself, contact support to obtain recovery discs. Go to http://www.hp.com/support, select your country or region, and then follow the on-screen instructions.

To recover your system:

Insert the HP Recovery media, and then restart the computer.



NOTE: HP recommends that you follow the Restoring and recovery methods on page 60 to restore your computer before you obtain and use the HP recovery discs. Using a recent backup can return your machine to a working state sooner than using the HP recovery discs. After the system is restored, reinstalling all the operating system software released since your initial purchase can be a lengthy process.

Changing the computer boot order

If your computer does not restart using the HP Recovery media, you can change the computer boot order, the order of devices listed in BIOS for startup information. You can select an optical drive or a USB flash drive, depending on the location of your HP Recovery media.

IMPORTANT: For a tablet with a detachable keyboard, connect the tablet to the keyboard base before beginning these steps.

To change the boot order:

- Insert the HP Recovery media.
- **2.** Access the system **Startup** menu.
 - For computers or tablets with keyboards attached, turn on or restart the computer or tablet, quickly press esc, and then press f9 for boot options.
 - For tablets without keyboards, turn on or restart the tablet, quickly press and hold the volume up button, and then select **f9**.

- or -

Turn on or restart the tablet, quickly press and hold the volume down button, and then select **f9**.

3. Select the optical drive or USB flash drive from which you want to boot, and then follow the on-screen instructions.

Using HP Sure Recover (select products only)

Select computer models are configured with HP Sure Recover, a PC operating system (OS) recovery solution built into the hardware and software. HP Sure Recover can fully restore the HP OS image without installed recovery software.

Using HP Sure Recover, an administrator or user can restore the system and install:

- Latest version of the operating system
- Platform-specific device drivers
- Software applications, in the case of a custom image

To access the latest documentation for HP Sure Recover, go to http://www.hp.com/support. Follow the onscreen instructions to find your product and locate your documentation.

8 Using HP PC Hardware Diagnostics

You can use the HP PC Hardware Diagnostics utility to determine whether your computer hardware is running properly. The three versions are HP PC Hardware Diagnostics Windows, HP PC Hardware Diagnostics UEFI (Unified Extensible Firmware Interface), and (for select products only) Remote HP PC Hardware Diagnostics UEFI, a firmware feature.

Using HP PC Hardware Diagnostics Windows (select products only)

HP PC Hardware Diagnostics Windows is a Windows-based utility that allows you to run diagnostic tests to determine whether the computer hardware is functioning properly. The tool runs within the Windows operating system to diagnose hardware failures.

If HP PC Hardware Diagnostics Windows is not installed on your computer, first you must download and install it. To download HP PC Hardware Diagnostics Windows, see Downloading HP PC Hardware Diagnostics Windows on page 63.

Using an HP PC Hardware Diagnostics Windows hardware failure ID code

When HP PC Hardware Diagnostics Windows detects a failure that requires hardware replacement, a 24-digit failure ID code is generated for select component tests. For interactive tests, such as keyboard, mouse, or audio and video palette, you must perform troubleshooting steps before you can receive a failure ID.

- You have several options after you receive a failure ID:
 - Click **Next** to open the Event Automation Service (EAS) page, where you can log the case.
 - or –
 - Scan the QR code with your mobile device, which takes you to the EAS page, where you can log the case.
 - or -
 - Click the box next to the 24-digit failure ID to copy your failure code and send it to support.

Accessing HP PC Hardware Diagnostics Windows

After HP PC Hardware Diagnostics Windows is installed, you can access it from HP Help and Support, HP Support Assistant, or the Start menu.

Accessing HP PC Hardware Diagnostics Windows from HP Help and Support (select products only)

After HP PC Hardware Diagnostics Windows is installed, follow these steps to access it from HP Help and Support.

- Select the Start button, and then select HP Help and Support.
- 2. Select HP PC Hardware Diagnostics Windows.
- When the tool opens, select the type of diagnostic test that you want to run, and then follow the onscreen instructions.

NOTE: To stop a diagnostic test, select **Cancel**.

Accessing HP PC Hardware Diagnostics Windows from Support Assistant

After HP PC Hardware Diagnostics Windows is installed, follow these steps to access it from HP Support Assistant.

- 1. Type support in the taskbar search box, and then select the **HP Support Assistant** app.

Select the question mark icon in the taskbar.

- Select **Troubleshooting and fixes**.
- 3. Select **Diagnostics**, and then select **HP PC Hardware Diagnostics Windows**.
- When the tool opens, select the type of diagnostic test that you want to run, and then follow the onscreen instructions.



NOTE: To stop a diagnostic test, select **Cancel**.

Accessing HP PC Hardware Diagnostics Windows from the Start menu (select products only)

After HP PC Hardware Diagnostics Windows is installed, follow these steps to access it from the Start menu.

- Select the Start button.
- Right-click HP PC Hardware Diagnostics for Windows, select More, and then select Run as administrator.
- When the tool opens, select the type of diagnostic test that you want to run, and then follow the onscreen instructions.



NOTE: To stop a diagnostic test, select **Cancel**.

Downloading HP PC Hardware Diagnostics Windows

The HP PC Hardware Diagnostics Windows downloading instructions are provided in English only. You must use a Windows computer to download this tool because only .exe files are provided.

Downloading the latest HP PC Hardware Diagnostics Windows version from HP

To download HP PC Hardware Diagnostics Windows from HP, follow these steps.

- Go to http://www.hp.com/go/techcenter/pcdiags. The HP PC Diagnostics home page is displayed.
- Select **Download HP Diagnostics Windows**, and then select the specific Windows diagnostics version to download to your computer or a USB flash drive.

The tool downloads to the selected location.

Downloading the HP PC Hardware Diagnostics Windows from the Microsoft Store


You can download the HP PC Hardware Diagnostics Windows from the Microsoft Store.

- Select the Microsoft Store app on your desktop or enter Microsoft Store in the taskbar search box.
- Enter HP PC Hardware Diagnostics Windows in the Microsoft Store search box.
- Follow the on-screen directions.

The tool downloads to the selected location.

Downloading HP Hardware Diagnostics Windows by product name or number (select products only)

You can download HP PC Hardware Diagnostics Windows by product name or number.



- 1. Go to http://www.hp.com/support.
- 2. Select **Software and Drivers**, select your type of product, and then enter the product name or number in the search box that is displayed.
- 3. In the **Diagnostics** section, select **Download**, and then follow the on-screen instructions to select the specific Windows diagnostics version to be downloaded to your computer or USB flash drive.


The tool downloads to the selected location.

Installing HP PC Hardware Diagnostics Windows

To install HP PC Hardware Diagnostics Windows, navigate to the folder on your computer or the USB flash drive where the .exe file downloaded, double-click the .exe file, and then follow the on-screen instructions.

Using HP PC Hardware Diagnostics UEFI

HP PC Hardware Diagnostics UEFI (Unified Extensible Firmware Interface) allows you to run diagnostic tests to determine whether the computer hardware is functioning properly. The tool runs outside the operating system so that it can isolate hardware failures from issues that are caused by the operating system or other software components.



If your PC does not start in Windows, you can use HP PC Hardware Diagnostics UEFI to diagnose hardware issues.

Using an HP PC Hardware Diagnostics UEFI hardware failure ID code

When HP PC Hardware Diagnostics UEFI detects a failure that requires hardware replacement, a 24-digit failure ID code is generated.

For assistance in solving the problem:

- ▲ Select **Contact HP**, accept the HP privacy disclaimer, and then use a mobile device to scan the failure ID code that appears on the next screen. The HP Customer Support Service Center page appears with your failure ID and product number automatically filled in. Follow the on-screen instructions.
 - or –

Contact support, and provide the failure ID code.

- NOTE: To start diagnostics on a convertible computer, your computer must be in notebook mode, and you must use the attached keyboard.
- **NOTE:** If you need to stop a diagnostic test, press esc.

Starting HP PC Hardware Diagnostics UEFI

To start HP PC Hardware Diagnostics UEFI, follow this procedure.

- 1. Turn on or restart the computer, and quickly press esc.
- 2. Press f2.

The BIOS searches three places for the diagnostic tools, in the following order:

- a. Connected USB flash drive
- NOTE: To download the HP PC Hardware Diagnostics UEFI tool to a USB flash drive, see Downloading the latest HP PC Hardware Diagnostics UEFI version on page 65.
- **b.** Hard drive
- c. BIOS
- 3. When the diagnostic tool opens, select a language, select the type of diagnostic test you want to run, and then follow the on-screen instructions.

Downloading HP PC Hardware Diagnostics UEFI to a USB flash drive

Downloading HP PC Hardware Diagnostics UEFI to a USB flash drive can be useful in some situations.

- HP PC Hardware Diagnostics UEFI is not included in the preinstallation image.
- HP PC Hardware Diagnostics UEFI is not included in the HP Tool partition.
- The hard drive is damaged.
- NOTE: The HP PC Hardware Diagnostics UEFI downloading instructions are provided in English only, and you must use a Windows computer to download and create the HP UEFI support environment because only .exe files are provided.

Downloading the latest HP PC Hardware Diagnostics UEFI version

To download the latest HP PC Hardware Diagnostics UEFI version to a USB flash drive, follow this procedure.

- 1. Go to http://www.hp.com/go/techcenter/pcdiags. The HP PC Diagnostics home page is displayed.
- 2. Select **Download HP Diagnostics UEFI**, and then select **Run**.

Downloading HP PC Hardware Diagnostics UEFI by product name or number (select products only)

You can download HP PC Hardware Diagnostics UEFI by product name or number (select products only) to a USB flash drive.

- NOTE: For some products, you might have to download the software to a USB flash drive by using the product name or number.
 - 1. Go to http://www.hp.com/support.
 - 2. Enter the product name or number, select your computer, and then select your operating system.
 - 3. In the **Diagnostics** section, follow the on-screen instructions to select and download the specific UEFI Diagnostics version for your computer.

Using Remote HP PC Hardware Diagnostics UEFI settings (select products only)

Remote HP PC Hardware Diagnostics UEFI is a firmware (BIOS) feature that downloads HP PC Hardware Diagnostics UEFI to your computer. It can then execute the diagnostics on your computer, and it might upload results to a preconfigured server.

For more information about Remote HP PC Hardware Diagnostics UEFI, go to http://www.hp.com/go/techcenter/pcdiags, and then select **Find out more**.

Downloading Remote HP PC Hardware Diagnostics UEFI

HP Remote PC Hardware Diagnostics UEFI is also available as a SoftPag that you can download to a server.

Downloading the latest Remote HP PC Hardware Diagnostics UEFI version

You can download the latest HP PC Hardware Diagnostics UEFI version to a USB flash drive.

- Go to http://www.hp.com/go/techcenter/pcdiags. The HP PC Diagnostics home page is displayed.
- 2. Select **Download Remote Diagnostics**, and then select **Run**.

Downloading Remote HP PC Hardware Diagnostics UEFI by product name or number

You can download HP Remote PC Hardware Diagnostics UEFI by product name or number.

- **NOTE:** For some products, you might have to download the software by using the product name or number.
 - 1. Go to http://www.hp.com/support.
 - Select Software and Drivers, select your type of product, enter the product name or number in the search box that is displayed, select your computer, and then select your operating system.
 - In the Diagnostics section, follow the on-screen instructions to select and download the Remote UEFI version for the product.

Customizing Remote HP PC Hardware Diagnostics UEFI settings

Using the Remote HP PC Hardware Diagnostics setting in Computer Setup (BIOS), you can perform several customizations.

- Set a schedule for running diagnostics unattended. You can also start diagnostics immediately in interactive mode by selecting Execute Remote HP PC Hardware Diagnostics.
- Set the location for downloading the diagnostic tools. This feature provides access to the tools from the HP website or from a server that has been preconfigured for use. Your computer does not require the traditional local storage (such as a hard drive or USB flash drive) to run remote diagnostics.
- Set a location for storing the test results. You can also set the user name and password that you use for uploads.
- Display status information about the diagnostics run previously.

To customize Remote HP PC Hardware Diagnostics UEFI settings, follow these steps:

- 1. Turn on or restart the computer, and when the HP logo appears, press f10 to enter Computer Setup.
- 2. Select **Advanced**, and then select **Settings**.

- Make your customization selections. 3.
- Select Main, and then Save Changes and Exit to save your settings.

Your changes take effect when the computer restarts.

9 Specifications

This chapter provides specifications for your computer.

Computer specifications

This section provides specifications for your computer. When traveling with your computer, the computer dimensions and weights, as well as input power ratings and operating specifications, provide helpful information.

Table 9-1 Computer specifications

	Metric	U.S.	
Dimensions			
Width	400.7 mm	15.8 in	
Depth	257.9 mm	10.2 in	
Height	19.9 mm	0.78 in	
Weight (lowest configuration)	2.06 kg	4.53 lbs	
Input power			
Operating voltage and current	19.5 V dc @ 2.31 A – 45 W		
	19.5 V dc @ 3.33 A – 65 W		
Temperature			
Operating	5°C to 35°C	41°F to 95°F	
Nonoperating	-20°C to 60°C	–4°F to 140°F	
Relative humidity (noncondensing)			
Operating	10% to 90%	10% to 90%	
Nonoperating	5% to 95%	5% to 95%	
Maximum altitude (unpressurized)			
Operating	–15 m to 3,048 m	-50 ft to 10,000 ft	
Nonoperating	–15 m to 12,192 m	−50 ft to 40,000 ft	

Display specifications

This section provides specifications for your display.

Table 9-2 Display specifications

	Metric	U.S.
Active diagonal size	43.9 cm	17.3 in
Resolution	1920 × 1080 (FHD)	
	1600 × 900 (HD+)	
Surface treatment	Antiglare	
	BrightView	
Brightness	250 nits	
Viewing angle	UWVA (FHD panels)	
	SVA (HD+ panels)	
Backlight	LED	
Display panel interface	eDP	

Solid-state drive specifications

This section provides specifications for your solid-state drives.

Table 9-3 Solid-state drive specifications

	128 GB*	256 GB*	512 GB*	1 TB*
Dimensions				
Height	1.0 mm	1.0 mm	1.0 mm	1.0 mm
Length	50.8 mm	50.8 mm	50.8 mm	50.8 mm
Width	28.9 mm	28.9 mm	28.9 mm	28.9 mm
Weight	< 10 g	< 10 g	< 10 g	< 10 g
Interface type	PCIe	PCIe	PCIe	PCIe
Ready time, maximum (to not busy)	1.0 ms	1.0 ms	< 1.0 ms	1.0 ms
Access times, logical	1.0 ms	0.1 ms	0.1 ms	0.1 ms
Transfer rate				
Sequential read	up to 2150 MB/s	up to 2150 MB/s	up to 2150 MB/s	up to 2150 MB/s
Random read	Up to 300,000 IOPs	Up to 300,000 IOPs	Up to 300,000 IOPs	Up to 300,000 IOPs
Sequential write	up to 1550 MB/s	up to 1550 MB/s	up to 1550 MB/s	up to 1550 MB/s
Random write	Up to 100,000 IOPs	Up to 100,000 IOPs	Up to 100,000 IOPs	Up to 100,000 IOPs
Total logical sectors	234,441,648	468,883,296	1,000,215,216	1,500,336,388
Operating temperature	0°C to 70°C (32°F t	o 158°F)		

Table 9-3 Solid-state drive specifications (continued)

128 GB*	256 GB*	512 GB*	1 TB*

^{*1} GB = 1 billion bytes when referring to hard drive storage capacity. Actual accessible capacity is less. Actual drive specifications can differ slightly.

NOTE: Certain restrictions and exclusions apply. Contact support for details.

10 Power cord set requirements

This chapter provides power cord requirements for countries and regions.

The wide-range input feature of the computer permits it to operate from any line voltage from 100 V ac to 120 V ac, or from 220 V ac to 240 V ac.

The three-conductor power cord set included with the computer meets the requirements for use in the country or region where the equipment is purchased.

Power cord sets for use in other countries or regions must meet the requirements of the country and region where the computer is used.

Requirements for all countries

These power cord requirements are applicable to all countries and regions.

- The length of the power cord set must be at least 1.0 m (3.3 ft) and no more than 2.0 m (6.5 ft).
- All power cord sets must be approved by an acceptable accredited agency responsible for evaluation in the country or region where the power cord set will be used.
- The power cord sets must have a minimum current capacity of 10 A and a nominal voltage rating of 125 V ac or 250 V ac, as required by the power system of each country or region.
- The appliance coupler must meet the mechanical configuration of an EN 60 320/IEC 320 Standard Sheet
 C13 connector for mating with the appliance inlet on the back of the computer.

Requirements for specific countries and regions

To determine power cord requirements for specific countries and regions, use this table.

Table 10-1 Power cord requirements for specific countries and regions

Country/region	Accredited agency	Applicable note number
Argentina	IRAM	1
Australia	SAA	1
Austria	OVE	1
Belgium	CEBEC	1
Brazil	ABNT	1
Canada	CSA	2
Chile	IMQ	1
Denmark	DEMKO	1
Finland	FIMKO	1
France	UTE	1
Germany	VDE	1

Table 10-1 Power cord requirements for specific countries and regions (continued)

Country/region	Accredited agency	Applicable note number
India	BIS	1
Israel	SII	1
Italy	IMQ	1
Japan	JIS	3
Netherlands	KEMA	1
New Zealand	SANZ	1
Norway	NEMKO	1
People's Republic of China	ССС	4
Saudi Arabia	SASO SASO	7
Singapore	PSB	1
South Africa	SABS	1
South Korea	KTL	5
Sweden	SEMKO	1
Switzerland	SEV	1
Taiwan	BSMI	6
Thailand	TISI	1
United Kingdom	ASTA	1
United States	UL	2

- The flexible cord must be Type HO5VV-F, three-conductor, 0.75 mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used
- The flexible cord must be Type SVT/SJT or equivalent, No. 18 AWG, three-conductor. The wall plug must be a two-pole grounding type with a NEMA 5-15P (15 A, 125 V ac) or NEMA 6-15P (15 A, 250 V ac) configuration. CSA or C-UL mark. UL file number must be on each element.
- 3. The appliance coupler, flexible cord, and wall plug must bear a T mark and registration number in accordance with the Japanese Dentori Law. The flexible cord must be Type VCTF, three-conductor, 0.75 mm² or 1.25 mm² conductor size. The wall plug must be a two-pole grounding type with a Japanese Industrial Standard C8303 (7 A, 125 V ac) configuration.
- 4. The flexible cord must be Type RVV, three-conductor, 0.75 mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the CCC certification mark.
- 5. The flexible cord must be Type H05VV-F three-conductor, 0.75 mm² conductor size. KTL logo and individual approval number must be on each element. Approval number and logo must be printed on a flag label.
- The flexible cord must be Type HVCTF three-conductor, 1.25 mm² conductor size. Power cord set fittings (appliance coupler, cable, and wall plug) must bear the BSMI certification mark.
- 7. For 127 V ac, the flexible cord must be Type SVT or SJT 3-conductor, 18 AWG, with plug NEMA 5-15P (15 A, 125 V ac), with UL and CSA or C-UL marks. For 240 V ac, the flexible cord must be Type H05VV-F three-conductor, 0.75 mm² or 1.00 mm² conductor size, with plug BS 1363/A with BSI or ASTA marks.

11 Recycling

When a nonrechargeable or rechargeable battery has reached the end of its useful life, do not dispose of the battery in general household waste. Follow the local laws and regulations in your area for battery disposal.

HP encourages customers to recycle used electronic hardware, HP original print cartridges, and rechargeable batteries. For more information about recycling programs, see the HP website at http://www.hp.com/recycle.

Index

A AC adapter and battery light, identifying 6 action key, identifying 12 audio-out (headphone)/audio-in (microphone) combo jack, identifying 7	HP Easy Clean 27 removing dirt and debris 27 components bottom 13 display 7 keyboard area 8 left side 6	H hard drive specifications 68 HDMI port identifying 6 heat sink removal 43
В	lights 10 right side 5	spare part numbers 43 HP PC Hardware Diagnostics UEFI
backup, creating 59 backups 59 BIOS	touchpad 8, 9 computer major components 15 computer specifications 68	downloading 65 failure ID code 64 starting 65
determining version 56 downloading an update 57 starting the Setup Utility 56	connectors power 6 control zone 9	using 64 HP PC Hardware Diagnostics Windows accessing 62, 63
updating 56 Bluetooth label 14 boot order, changing 60	D display	downloading 63 failure ID code 62 installing 64
bottom components 13 bottom cover removal 31	specifications 68 display assembly subcomponents 18	using 62 HP Recovery media recovery 60
rubber feet feet 31, removal 31,	display components 7 drive light, identifying 5	HP Sure Recover 61
spare part number 31, spare part number feet 31,	electrostatic discharge (ESD) 23, 24 preventing damage 23, 24, 25	illustrated parts catalog 15 integrated numeric keypad, identifying 13
removal 31, spare part number 31, buttons	esc key, identifying 12	internal microphones, identifying 8
left touchpad 9 power 11, 12	fan removal 42	jacks audio-out (headphone)/audio-in
right touchpad 9	spare part number 42 fingerprint reader 12 removal 39	(microphone) 7
camera identifying 8 camera light, identifying 8	spare part numbers 39 fn key, identifying 12	keyboard product description 3 keyboard with top cover
caps lock light 10 caring for your computer 27 cautions	grounding methods 23, 24, 25 guidelines	spare part numbers 54 keypad, integrated numeric 13 keys
electrostatic discharge 23, 24 cleaning your computer 27 caring for wood veneer 29 disinfecting 28	packaging 23, 29 transporting 23, 29 workstation 23	action 12 esc 12 fn 12

num lk 13	requirements for specific	special keys
Windows 12	countries and regions 71	identifying 12
	set requirements 71	using 12
L	power light, identifying 5, 10	specifications
- labels		•
	product description	computer 68
Bluetooth 14	keyboard 3	display 68
regulatory 14	pointing device 3	hard drive 68
serial number 14	ports 2	solid-state drive 69
service 14	product name and number,	static electricity 23, 24
wireless certification 14	computer 14	support information 29
WLAN 14	compater 11	system board
left control zone, identifying 9	R	removal 45
left side components 6	recovery 59	
lights	discs 60	spare part numbers 45
		system restore 60
AC adapter and battery 6	media 60	system restore point, creating 59
camera 8	USB flash drive 60	
caps lock 10	recovery media 59	Т
drive 5	creating using HP Cloud Recovery	touchpad
mute 10	Download Tool 59	removal 40
power 5, 10	creating using Windows tools 59	settings 9
touchpad 9	regulatory information	spare part number 40
low blue light mode 7	regulatory label 14	touchpad buttons
	wireless certification labels 14	identifying 9
М	Remote HP PC Hardware Diagnostics	touchpad components 8
memory modules	UEFI settings	touchpad light, identifying 9
removal 34	_	
	customizing 66	touchpad settings, adjusting 9
spare part numbers 34	using 66	touchpad zone, identifying 9
mute light, identifying 10	removal and replacement	transporting guidelines 23, 29
	procedures 31	traveling with the computer 14
N	solid-state drive 36	
num lk key, identifying 13	restoring 59	U
	restoring and recovery methods 60	USB board
P	right control zone, identifying 9	removal 40
packaging guidelines 23, 29	right side components 5	spare part numbers 40
pointing device, product	3	USB SuperSpeed port, identifying 5
description 3	S	6
ports	serial number, computer 14	USB Type-C SuperSpeed port,
HDMI 6	service labels, locating 14	identifying 6
product description 2		identifying 0
USB SuperSpeed 5, 6	slots	W
	memory card reader 5	V
USB Type-C SuperSpeed 6	microSD memory card reader 5	vents, identifying 14
power button, identifying 11, 12	solid-state drive	
power connector	removal and replacement 36	W
identifying 6	specifications 69	Windows
power connector cable	spare part country codes 54	backup 59
removal 53	speaker	recovery media 59
spare part number 53	removal 46	system restore point 59
power cord	spare part numbers 46	Windows key, identifying 12
requirements for all countries		Windows tools, using 59
71	speakers 11	wireless antennas, identifying 8
<i>,</i> 1		wireless certification label 14
		wireless certification ladel 14

WLAN antennas, identifying 8
WLAN device 14
WLAN label 14
WLAN module
removal 37
spare part numbers 37
workstation guidelines 23