

Surfaces: **brushed gold-optic** Art. no. : **35313250**



- Shower head size: 250 x 250 mm
- Spray pattern: PowderRain, Intense PowderRain
- Select button on thermostat
- dynamic spray nozzles move out while using
- Spray face: metal
- maximum flow rate 17 l/min at 3 bar
- Flow rate PowderRain (at 3 bar): 17 l/min at 3 bar
- flow rate Rain 15 l/min at 3 bar
- Operating pressure: min. 1.5 bar/max. 6 bar
- overhead shower removable for cleaning
- Installation: ceiling mounted

£ 1,780.31



reddot winner 2020



reddot winner 2021

The AXOR logo is centered on a background of a grid of small, light blue dots. The dots are arranged in a regular pattern, with the logo text 'AXOR' appearing in a larger, bold, sans-serif font in the center.

Technical drawing of the 3000 series terminal block showing front and top views with dimensions.

Front View Dimensions:

- Overall width: 145
- Overall height: 71
- Mounting flange height: 25
- Terminal block height: 56

Top View Dimensions:

- Overall width: 238
- Overall height: 238
- Internal width: 106
- Internal height: 145
- Mounting hole diameter: $G1/2$
- Terminal hole diameter: $G1/2$
- Terminal pitch: 22
- Mounting flange thickness: 53
- Mounting flange offset: 50


AXOR ShowerSolutions

Overhead shower 250/250 2jet ceiling

Surfaces: **brushed gold-optic** Art. no. : **35313250**



Flowchart



The consumption was measured in combination with the appropriate fittings (thermostat/mixer/in-wall valve) to reflect actual application in practice.


AXOR ShowerSolutions

Overhead shower 250/250 2jet ceiling


Surfaces: **brushed gold-optic** Art. no. : **35313250**



Installation examples



AXOR 250 2jet
35298000
AXOR 300 2jet
35305000



AXOR 250/250 2jet
35313000
AXOR 300/300 2jet
35321000

