## Overview

### HPE Ethernet 10Gb 2-port 571SFP+ Adapter

The HPE Ethernet 10Gb 2-port 571SFP+ Adapter based on the Performant SFC9020 controller from Solarflare is designed to address issues facing data center managers today. Equipped to handle the application loads of the latest multi-core processors, the HPE Ethernet 571 adapter also delivers unmatched power efficiency for the consolidation and deployment of high-density servers.




**HPE Ethernet 10Gb 2-port 571SFP+ Adapter with the standard bracket**

## Overview




**HPE Ethernet 10Gb 2-port 571SFP+ Adapter with the low profile bracket**

## Platform Information

### Models

| | |
|---|---|
| HPE Ethernet 10Gb 2-port 571SFP+ Adapter | 728987-B21 |

| | |
|---|---|
| **Kit Contents** | HPE Ethernet 10Gb 2-port 571SFP+ Adapter<br>Full height bracket (installed on card), low profile bracket included<br>Quick install card<br>Product warranty statement |
| **Compatibility - Supported Servers** | HPE ProLiant DL360p Gen8<br>HPE ProLiant DL380p Gen8<br>**NOTE:** This is a list of supported servers. Some may be discontinued. |

## Standard Features

| | |
|---|---|
| **Throughput-Theoretical Bandwidth** | This adapter delivers 20 Gb/s bi-directional Ethernet transfer rate per port (40 Gb/s per adapter), providing the network performance needed to improve response times and alleviate bottlenecks. |
| **802.1Q VLANs** | IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of this adapter to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance. |
| **Configuration Utilities** | This adapter ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations. |
| **Interrupt Coalescing** | Interrupt coalescing (interrupt moderation) groups multiple packets, thereby reducing the number of interrupts sent to the host. This process optimizes host efficiency, leaving the CPU available for other duties. |
| **Jumbo Frames** | This adapter supports Jumbo Frames (also known as extended frames), permitting up to a 9,000 byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over five times the size of a standard 1500-byte Ethernet frame. With Jumbo Frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations. |
| **LED Indicators** | LED indicators show link integrity and network activity for easy troubleshooting. |
| **Management Support** | This adapter ships with agents that can be managed from HPE Systems Insight Manager or other management application that support SNMP. |
| **PCI Express Interface** | This adapter is designed with an eight lane (x8) PCI Express bus based on the PCIe 2.0 standard. The adapter is backward compatible with four lane (x4) PCI Express, automatically auto-sensing between x8 and x4 slots. |
| **Preboot eXecution Environment (PXE)** | Support for PXE enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network.Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs. |
| **Server Integration** | This adapter is a validated, tested, and qualified solution that is optimized for HPE ProLiant servers. Hewlett Packard Enterprise validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HPE Intelligent Provisioning and HPE Systems Insight Manager that simplify network management.<br>This approach provides a more robust and reliable networking solution than offerings from other vendors and provides users with a single point of contact for both their servers and their network adapters. |

## Standard Features

| | |
|---|---|
| **Single-Root I/O Virtualization** | Single-Root I/O Virtualization (SR-IOV) provides a mechanism to bypass the host system hypervisor in virtual environments providing near metal performance and server efficiency. SR-IOV provides mechanism to create multiple Virtual Functions (VFs) to share single PCIe resources. The device is capable of SR-IOV, and requires Server BIOS support, controller firmware, and OS support. |
| **TCP/UDP/IP** | For overall improved system response, this adapter supports standard TCP/IP offloading techniques including: TCP/IP, UDP checksum offload (TCO) moves the TCP and IP checksum offloading from the CPU to the network adapter. Large send offload (LSO) or TCP segmentation offload (TSO) allows the TCP segmentation to be handled by the adapter rather than the CPU. |
| **Warranty** | Maximum: The remaining warranty of the HPE product in which it is installed (to a maximum three-year, limited warranty).<br>Minimum: One year limited warranty.<br>**NOTE:** Additional information regarding worldwide limited warranty and technical support is available at: **http://h17007.www1.hpe.com/us/en/enterprise/servers/warranty/index.aspx#.V4e3tPkrJhE** |

## Service & Support

| | |
|---|---|
| **Service and Support** | **NOTE: This adapter is covered under HPE Support Services/ Service Contract applied to the HPE ProLiant Server or enclosure. No separate HPE Support Services# need to be purchased.**<br>Most HPE branded options sourced from HPE that are compatible with your product will be covered under your main product support at the same level of coverage, allowing you to upgrade freely. Additional support is required on select workload accelerators, switches, racks and UPS options 12KVA and over. Coverage of the UPS battery is not included under HPE support services; standard warranty terms and conditions apply. |
| **Warranty and Support Services** | Warranty and Support Services will extend to include HPE options configured with your server or storage device. The price of support service is not impacted by configuration details. HPE sourced options that are compatible with your product will be covered under your server support at the same level of coverage allowing you to upgrade freely. Installation for HPE options is available as needed. To keep support costs low for everyone, some high value options will require additional support. Additional support is only required on select high value workload accelerators, fibre switches, InfiniBand and UPS options 12KVA and over. Coverage of the UPS battery is not included under TS support services; standard warranty terms and conditions apply. |
| **Protect your business beyond warranty with HPE Support Services** | HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HPE to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support you need for your IT and business.<br>Protect your product, beyond warranty. |
| **Parts and Materials** | Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services. The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction. |
| **For more information** | Visit the Hewlett Packard Enterprise Service and Support **website**. |

## Related Options

| | | |
|---|---|---|
| **Cables - Direct Attach** | HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 0.5m Direct Attach Copper Cable | 487649-B21 |
| | HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 1m Direct Attach Copper Cable | 487652-B21 |
| | HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 3m Direct Attach Copper Cable | 487655-B21 |
| | HPE BladeSystem c-Class 10GbE SFP+ to SFP+ 5m Direct Attach Copper Cable | 537963-B21 |
| | HPE FlexNetwork X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable | JD095C |
| | HPE FlexNetwork X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable | JD096C |
| | HPE FlexNetwork X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | JD097C |
| | HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable | JG081C |
| | HPE FlexNetwork X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable | JC784C |
| | **NOTE: Direct Attach Cable (DAC) must be purchased separately for copper environments.** | |
| **Transceivers** | HPE BladeSystem c-Class 10Gb SFP+ SR Transceiver | 455883-B21 |
| | HPE BladeSystem c-Class 10Gb SFP+ LR Transceiver | 455886-B21 |
| | HPE BladeSystem c-Class Virtual Connect 1G SFP SX Transceiver | 453151-B21 |
| | **NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments.** | |

## Technical Specifications

| | | |
|---|---|---|
| **General Specifications** | **Network Processor** | Solarflare (SFC9020) |
| | **Data Rate** | Two ports, each at 20 Gb/s bi-directional; 40 Gb/s aggregate bi-directional theoretical bandwidth. |
| | **Bus type** | PCI Express 2.0 at 5 GT/s, x8 |
| | **Form Factor** | Standard and low profile adapter compliant with the PCIe standard |
| | **IEEE Compliance** | 802.3, 802.1ab, 802.3x, 802.3ad, 802.3p, 802.1q, 802.3ae |
| **Power and Environmental Specifications** | **Power** | 5.9W typical, 7.5W maximum |
| | **Temperature - Operating** | 5° to 55° C (41° to 131° F) |
| | **Humidity - Operating** | 5% to 95% non-condensing |
| | **RoHS Compliance** | 5 of 6 |
| **Operating System and Virtualization Support** | • Red Hat Enterprise Linux (RHEL) 5.8, 5.9, 6.2, 6.3, 7.2<br>• SUSE Linux Enterprise Server (SLES) 10 SP4, 11 SP2<br>**NOTE:** For more Linux OS support and certification information, please visit: **http://h17007.www1.hpe.com/us/en/enterprise/servers/supportmatrix/redhat_linux.aspx#.V4e8tPkrJD8** | |
| **Environment-friendly Products and Approach - End-of-life Management and Recycling** | Hewlett Packard Enterprise offers end-of-life **product return, trade-in, and recycling programs**, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.<br>The EU WEEE Directive (2012/19/EU) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the **Hewlett Packard Enterprise web site**. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment. | |

## Summary of Changes

| Date | Version History | Action | Description of Change |
|---|---|---|---|
| 27-Mar-2017 | From Version 3 to 4 | Changed | SKUs description updated |
| | | Removed | Obsolete SKU was deleted: 453151-B21 |
| 5-Dec-2016 | From Version 2 to 3 | Changed | Technical Specifications section was updated |
| 6-Aug-2016 | From Version 1 to 2 | Changed | Information was updated in Standard Features section. |
| | | Removed | Obsolete SKUs were deleted: 221691-B22, 221691-B23, 21692-B21, 221692-B22, 221692-B23, 221692-B26, 221692-B27, 503746-B21, 412648-B21, 435508-B21, 394791-B21, 394793-B21, 538696-B21, 458492-B21, 468332-B21, 593717-B21, 489892-B21, 581201-B21, 614203-B21,#629135-B21, 629138-B21, 629142-B21 |

**Sign up for updates**

© Copyright 2017 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

C04111359 - 14666 - Worldwide - V4 - 27-March-2017