

Motorbike 4T 5W-40 HC Scooter

Description

High-performance motor oil based on synthetic technology. For maximum performance and protection of the engine under all operating conditions. Ensures optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear.

Properties

- guarantees low oil consumption
- high shear stability
- high wear resistance
- optimum stability to aging
- optimum lubrication under all operating conditions
- outstanding engine cleanliness
- tested for catalytic converters

Specifications and approvals:

API SN • JASO MA2

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Kymco • Piaggio

Technical data

Viscosity SAE class	5W-40 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	90,1 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,65 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D 5481
Pour point	-36 mPas DIN ISO 2909
Evaporation loss (Noack)	11,0 % ASTM D 5800 B
Flash point	228 °C DIN ISO 2592
Total base number	7,7 mg KOH/g DIN ISO 3771



Technical data

Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For the sporty driver.

Application

Note the vehicle and engine manufacturers' operating instructions. **Note:** Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	20829 BOOKLET
4 l Canister plastic	20830 BOOKLET
20 l Canister plastic	20831 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.