

## EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Mini battery uplight IP65 with RGBW LEDs and IR remote control

Art. No.: 41700616

GTIN: 4026397726787



**List price: 153.51 €**

incl. 19% VAT.

### Features:

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 4 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Application possibility: Standing
- Silent operation

### Logistic

EAN / GTIN: 4026397726787

Weight: 1,27 kg

Length: 0.16 m

Width: 0.13 m

Height: 0.13 m

### Technical specifications:

Power supply: 5V 1600 mA

IP classification: IP65

Protection class: Protection class III

|                         |                                                                            |
|-------------------------|----------------------------------------------------------------------------|
| Power connection:       | Battery/battery pack<br>Mains input via USB C (W) mounting version         |
| Battery pack type:      | 1 x lithium ion 11.1 V, 3200 mAh, 35.52 Wh                                 |
| Battery pack:           | Battery operation up to 9h depending on program used<br>Recharging time 5h |
| Lamp type:              | LED lamp                                                                   |
| LED type:               | 4 x 4 W 4in1 QCL RGBW (homogenous color mix)                               |
| Flash rate:             | 1 - 20 Hz                                                                  |
| Cooling:                | Passive convection cooling                                                 |
| Control:                | Sound to light via microphone; stand-alone; IR remote control              |
| Projection:             | Flicker-free                                                               |
| Beam angle:             | 15°                                                                        |
| Beam angle (1/2 peak):  | 15°                                                                        |
| Beam angle (1/10 peak): | 30°                                                                        |
| Housing color:          | Black                                                                      |
| Display type:           | 4 digit 7-segment LED display                                              |
| Dimensions:             | Length: 10 cm<br>Width: 11 cm<br>Height: 12 cm                             |
| Weight:                 | 1.17 kg                                                                    |
| Noise classification:   | Class 0 (no noise at all)                                                  |
| Battery:                | 1 x button cell CR2025                                                     |
| Special product:        | Not designed for household room illumination                               |
| Intended use:           | Show effect lighting                                                       |

## Scope of delivery:

1 x device  
1 x user manual  
1 x remote control  
1 x USB cable