

EcoTank Mono ET-M16600



A3+ print with this fast, feature-rich EcoTank. It offers a low cost per page, 550-sheet tray capacity and 50-sheet ADF.

This feature-rich monochrome EcoTank makes light of A3+ tasks, while offering a low cost per page. A3+ jobs can be accomplished quickly thanks to fast print and scan speeds, two 250-sheet front trays, a 50-sheet rear feed, and a 50-sheet A3 ADF. Print how you like with mobile printing, Ethernet and a 6.8cm LCD touchscreen.

Get more done in less time

Get the edge with this fast and efficient monochrome printer that can deliver a first page in as little as 5½ seconds¹. Coupled with fast double-sided printing, and a high speed Automatic Document Feeder, you'll be able to speed through everyday tasks.

Feature-rich A3+ monochrome EcoTank

The ET-M16600 is designed for A3 tasks with A3+ print, scan and copy. It's easy to navigate the extensive range of features via the 6.8cm LCD touchscreen.

Keep on saving

Making a saving every time you print with this EcoTank that delivers an incredibly low cost per page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

Business quality printing

The fast drying EcoTank 113 ink series features all pigment ink for smudge-free and highlighter-resistant prints. With this reliable and high-quality ink, you can be sure it will deliver great prints with clear text. From one set of replacement ink, you can produce up to 7,500 pages in black².

Print from almost anywhere

It's easy to print from mobiles, tablets and laptops using EcoTank. With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint app³.

Easy to use and reliable

Filling the ink tanks is simple with the resealable, intuitive and drip-free ink bottles. Epson's unique Heat-Free PrecisionCore Technology offers improved reliability, reduced downtime and less environmental impact. No warm up time and the first page prints fast using less power.

DATASHEET / BROCHURE



KEY FEATURES

- **Ultra-fast print speeds**
Up to 25ipm
- **Ultra-low-cost per page**
Economical ink tank system
- **Easy to use front ink tank**
Enjoy hassle and mess-free refills with enhanced ink bottles
- **Mobile printing and connectivity**
Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps³
- **Designed for business**
A3+ multifunction, 2x A3 250-sheet front tray, 50 sheet rear feed

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ Print Head
Minimum Droplet Size	3.8 pl
Ink Technology	DURABrite™ ET
Printing Resolution	4,800 x 2,400 DPI

PRINT

Printing Speed ISO/IEC 24734	25 pages/min Monochrome
Maximum Printing Speed	32 pages/min Monochrome (plain paper 75 g/m²)
Print from	PC, MAC, Mobile Device, USB
Colours	Black [Pigment]
Colours Capacity	Black [127ml]

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

Optical Resolution	1,200 DPI x 2,400 DPI (Horizontal x Vertical)
Scanner type	Contact image sensor (CIS)

PAPER / MEDIA HANDLING

Paper Formats	A3+, A4 (21.0x29.7 cm), A3 (29.7x42.0 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B4 (25.7x36.4 cm), B5 (17.6x25.7 cm), B6 (12.5x17.6 cm), C4 (Envelope), C6 (Envelope), DL (Envelope), Letter, Legal, 10 x 15 cm, 13 x 18 cm, 20 x 25 cm
Duplex	Yes (A4/A3, plain paper)
Automatic Document Feed	50 pages
Paper Tray Capacity	550 Sheets Maximum
Media Handling	ADF 2-sided scan (A4, plain paper), Automatic duplex (A4/A3, plain paper)

GENERAL

Energy Use	19 Watt (standalone copying, ISO/IEC 24712 pattern), 0.7 Watt (sleep mode), 8 Watt (Ready), 0.15 Watt (Power off), TEC 0.13 kWh/week
Product dimensions	515 x 500 x 350 mm (Width x Depth x Height)
Product weight	20.2 kg
Compatible Operating Systems	Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows 8.1 x64 Edition, Windows Server 2003, Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit)
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP)
Mobile and Cloud printing services	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint, Mopria

OTHER FEATURES

Panel	Type: Color, Touchscreen, Diagonal: 6.8 cm
Features	Touchscreen

OTHER

Warranty	12 months Carry in Optional warranty extension available
----------	---

LOGISTICS INFORMATION

SKU	C11CJ41401CA
EAN code	8715946683683
Country of Origin	Indonesia

For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.
Last extracted: 2021-02-09

EcoTank Mono ET-M16600

WHAT'S IN THE BOX

- Warranty document
- Quick Start Guide
- Main unit
- Power cable

INK BOTTLE COMPATIBILITY

● 113



INK BOTTLE YIELD DATA



Included 4,500 pages*

Replacement 7,500 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit <http://www.epson.eu/pageyield>

1. First-Print-Out-Time (FPOT) measurement method: ISO/IEC17629 Office Category Test; paper size A4. A set of Microsoft Word, Microsoft Excel and PDF files (each set containing 4 pages) is continuously printed. Measurement is based on the average time for the first of the four single sided prints to exit the printer. Measurement starts when the print button is pressed and ends when the first page of the set exits.
2. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 based on the replacement ink bottles. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature..
3. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.eu

EPSON®