



360mm · 280mm · 240mm · 120mm

IDEAL APPLICATIONS

Overclocked CPUs High-resolution gaming and PCs Workstations

HIGHLIGHTS

Dampened six-pole pump with three-chamber design Silent Wings 3 PWM high-speed fans ARGB illumination with multiple colors and options

Significant quiet and exceptional cooling

Silent Loop 2 is the very high performance and whisper-quiet all-in-one water-cooling unit for demanding systems with over-clocked CPUs.

Highlights

- Dampened and adjustable pump with six-pole motor for very silent and very high-performance operation
- Powerful three-chamber pump design significantly reduces turbulences and noise
- Silent Wings 3 PWM high-speed fans for high performance and whisper-quiet operation
- Cold plate with high density stack of fins for highest cooling characteristics
- ARGB LEDs for many illumination options and great visual effects
- Easy-to-access refill port and a coolant bottle is supplied, ensuring a long lifespan
- 3-year manufacturer's warranty
- Product conception, design and quality control in Germany



SILENT LOOP 2

| General Data | | | | |
|--|---|---|---|---|
| Model | 360mm | 280mm | 240mm | 120mm |
| Article no. | BW012 | BW011 | BW010 | BW009 |
| EAN code | 4260052188347 | 4260052188330 | 4260052188323 | 4260052188316 |
| Dimensions radiator, incl. fan (H x W x D), (mm) | 390 x 120 x 52 | 314 x 140 x 52 | 272 x 120 x 52 | 153 x 120 x 77 |
| Total weight (g) | 1326 | 1185 | 1046 | 907 |
| Socket compatibility | Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4 | Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4 | Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4 | Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4 |
| Noise level (dB(A)) @ 25 % / 50% /100% rpm | 17.7 / 23.9 / 39.8 | 16.5 / 20.3 / 36.1 | 16.8 / 22.3 / 38.3 | 16.6 / 19.4 / 36.4 |
| Pump speed (rpm) | 2800 | 2800 | 2800 | 2800 |
| Pump connector | 3-pin | 3-pin | 3-pin | 3-pin |
| Refill port | • | > | → | • |
| Radiator specification | | | | |
| Dimensions (H x W x D), (mm) | 390 x 120 x 27 | 314 x 140 x 27 | 272 x 120 x 27 | 153 x 120 x 27 |
| Radiator material / finish | aluminum / black spray painted |
| Base material / finish | copper / nickle plating |
| be quiet! Silent Wings 3 PWM high-speed fa | ins | | | |
| Fan dimensions (mm) / Quantity (pcs.) | 120 x 120 x 25 / 3 | 140 x 140 x 25 / 2 | 120 x 120 x 25 / 2 | 120 x 120 x 25 / 2 |
| Speed @ 100% PWM (rpm) | 2200 | 1600 | 2200 | 2200 |
| Input current (A) | 0.37 | 0.5 | 0.37 | 0.37 |
| Connector | 4-pin PWM | 4-pin PWM | 4-pin PWM | 4-pin PWM |
| Lifespan (h / 25°C) | 300,000 | 300,000 | 300,000 | 300,000 |

| Logistics data | | |
|----------------|------------|---------------|
| Silent Loop 2 | Article no | EAN code |
| 360mm | BW012 | 4260052188347 |
| 280mm | BW011 | 4260052188330 |
| 240mm | BW010 | 4260052188323 |
| 120mm | BW009 | 4260052188316 |



| Contact |
|---------|
|---------|

be quiet! Headquarters

Service hotline: +49 40 7367 686 44

Listan GmbH

Wilhelm-Bergner-Straße 11c

e-mail: service@bequiet.com 21509 Glinde Visit the contact section on bequiet.com

Germany for the right regional service information.