



SATMAN 65 PLUS incl. SCR-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Item no.	Colour
4019588888609	2065/8886	beige
4019588888630	2365/8886	slate/grey
4019588888647	2465/8886	brick/red
4019588888760	2765/8886	polar/white
4019588888654	2565/8886	yellow with Smiley

GENERAL CHARACTERISTICS

Top features: For 1 to multiple participants

Top features: 1 orbital position (for example Astra 19.2° East)

Top features: Ideal for wall and roof mounting

Top features: For distribution to multiple participants on demand, TechniSat distribution elements are required

Material: Aluminium

Material strength: 1.5 mm

Coating: Powder-coated on both sites

INPUT FREQUENCY RANGE

Low band: 10.7 ... 11.7 GHz

High band: 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range: 0.6 dB max.

Upper frequency range: 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1950 MHz

High band: 1100 ... 2150 MHz

PREPARED FOR

Number of orbit positions: 1

Number of clients: 6

TECHNICAL DATA

Rated measurement: 0.65 m

F/D: 0.69

G/T: 14.5 dB/K

Offset angle: 27 °

Gain: 35.7 dBi @11,3 GHz

Mast Ø: 65 mm max.

Feed reception: for UNYSAT-Universal-LNB

LNB CONTROL

Vertical: 11,5 - 14,5 V

Horizontal: 16 - 19 V

LOCAL OSCILLATOR

Low band: 9.75 GHz

High band: 10.7 GHz

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 650, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions

KEYFEATURES

2 subscribers

1 orbit position

4 subscribers

HDTV

1 subscriber

Multiple subscribers