LTAP LTE6 KIT

A compact LTE6 capable weatherproof wireless access point






LtAP LTE6 kit

An upgrade of the heavy-duty LTE access point with GPS support

LtAP LTE6 kit is a compact 4G (LTE) capable weatherproof wireless access point – perfect for busy urban environment or off-the-grid outdoors networking. It has a built-in CAT6 cellular modem that supports 4G (LTE) connectivity out of the box – with up to 300 Mbps download speed!



- 2.4 GHz AP in a rugged case
- LTE installed in miniPCle slot
- Second miniPCle slot for expansions
- Three Mini SIM slots
- Gigabit Ethernet port



- Built-in GPS
- Many powering options (DC jack, POE-in, automotive)
- Serial port and full size USB for other devices
- Perfect for cars or outdoor mobile applications

CAT6 also enables carrier aggregation and allows the device to use multiple bands at the same time. A huge advantage when there are a lot of LTE users in the area. It provides better responsiveness in a crowded environment and higher efficiency for weaker signal situations in the countryside.



The rugged and extremely durable case with a special wall mounting kit will be ideal for almost any challenge: from public transportation, food trucks or logistics to harsh winter and stormy desert environment. LtAP can handle any temperature from -40 °C to +70 °C. It is a superb solution for tracking vehicles in real time. We have provided a simple tracking application example in the RouterOS documentation to help you get started. LtAP LTE6 kit even has 3 Mini-SIM slots for easy roaming management. Saves your time and money worldwide!

The unit comes with an extra miniPCle slot, offering many expansion options. For example, you can install a second LTE modem for redundancy or a 5 GHz interface to have dual concurrent 2.4 GHz / 5 GHz AP + LTE. Another miniPCle slot is already populated with the LTE modem.



LtAP LTE6 kit has a RS232 serial port, which gives you console access for debugging, as well as full size USB for other devices. There is a Gigabit Ethernet LAN port for your wired devices and several power options – DC jack, POE-in and automotive.

The LtAP LTE6 kit is more than an access point – it is what you need it to be wherever you need it to be!



Specifications

| Product code | RBLtAP-2HnD&R11e-LTE6 | |
|----------------------------|--|--|
| CPU | Dual-core MediaTek MT7621 880 MHz | |
| Size of RAM | 128 MB | |
| Storage | 16 MB flash | |
| 10/100/1000 Ethernet ports | 1 | |
| Wireless | 2.4 GHz 802.11b/g/n dual-chain | |
| Wireless regulations | Specific frequency range will be limited by country regulations | |
| Wireless antenna max gain | 2.5 dBi | |
| LTE antenna max gain | 4 dBi (with U.FL connector) | |
| Antenna beam width | 360° | |
| LTE category | 6 (300 Mbps downlink, 50 Mbps uplink) | |
| 3G category | R7 (21 Mbps downlinks, 5.76 Mbps uplink) R8 (42.2 Mbps downlink, 5.76 Mbps uplink) | |
| 2G category | Class12 | |
| Supported input voltage | DC jack or automotive connector 12 - 30 V | |
| PoE in | Passive PoE 12 - 30 V | |
| Dimensions | 170 x 162 x 40 mm | |
| Operating temperature | -30°C +70°C | |
| Operating system | RouterOS, License level 4 | |
| Mini SIM slots | 3 | |
| MiniPCle slot #1 | Top slot supports PCle and USB 2.0 cards, but is shared with the USB 2.0 type A port (can use either USB port or miniPCle slot at the same time) | |
| MiniPCle slot #2 | Bottom slot supports only USB (2.0 and 3.0) miniPCle modems (no PCle support) | |
| USB port | 1 USB 2.0 port type A (can only be used if miniPCle slot #1 is not used) | |
| Built-in GPS | Yes (external antenna option via MMCX connector) | |
| Serial port | RS232 | |
| Max power consumption | 24 W | |
| | | |

Supported 2xCA LTE bands

| 1+1/5/8/20 | 2+2/5/12/17 | 3+3/5/7/8/20 | 7+7/8/12/20 | 8+8 |
|------------|-------------|--------------|-------------|-------|
| 12+12 | 38+38 | 39+39/41 | 40+40 | 41+41 |



Supported bands

| LtΔ | | |
|-----|--|-----|
| | | KIT |
| | | |

| LTE (FDD) bands | 1(2100)/2(1900)/3(1800)/5(850)/7(2600)/8(900)/12(700)/17(700)/20(800)/25(1900)/ 26(850) |
|-----------------|--|
| LTE (TDD) bands | 38(2600)/39(1900)/40(2300)/41n(2500) |
| 3G bands | 1(2100)/2(1900)/5(850)/8(900) |
| 2G bands | 2(1900)/3(1800)/5(850)/8(900) |

Wireless specifications

| Rate (2.4 GHz) | Tx (dBm) | Rx (dBm) |
|----------------|----------|----------|
| 1MBit/s | 25 | -100 |
| 11MBit/s | 25 | -94 |
| 6MBit/s | 26 | -96 |
| 54MBit/s | 23 | -78 |
| MCS0 | 26 | -96 |
| MCS7 | 22 | -73 |

Included parts



24 V 1.2 A power adapter



Screw kits



Automotive cable