



NEW

Switch actuator, 16 A 2gang

Functions at a glance

- 2gang switch actuator
- Potential free contacts parameterisable as NC contact or NO contact
- Manual >local operation< possible.
- Output indication of the contacts
- The bus can be connected via enclosed terminal block.
- Control element: Manual operation possibility for ON/OFF via sliding switch
- Display elements: Status display of the outputs via position of the sliding switches
- Rated voltage: 230 V~, +10 % / -15 %
- Rated frequency: 50 Hz / 60 Hz
- Outputs: 2 Normally open contact, potential free
- suitable for: AC1
 - Rated current: 16 A, $\cos \varphi 0.8$
- suitable for: AC3
 - Rated current: 8 A, $\cos \varphi 0.45$
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions (L x W x D): 90 mm x 36 mm x 64 mm
- Module width: 2
- For software and description please check the current Online-Catalogue.
- 1 MW 18 mm.

Order details

Article No.:	SA/S2.16.2.12
Order No.:	2CDG110261R0021
EAN:	4016779066648
Customs tariff number:	85371091
Price group:	45
Price:	206,00 EUR plus VAT

Downloads

Instruction manual

» [Operating Instructions](#)

Technical manual

» [Product manual Version 1.1](#)

Certificates

» [EU-declaration of conformity](#)

Software

» [ETS5 application , V 1.0](#)
» [Firmware , V 1.3](#)